



IEEE Press Series on Power and Energy Systems
Ganesh Kumar Venayagamoorthy, Series Editor

Smart Energy for Transportation and Health in a Smart City

Chun Sing Lai, Loi Lei Lai, Qi Hong Lai




IEEE PRESS

WILEY

Table of Contents

[Cover](#)

[Series Page](#)

[Title Page](#)

[Copyright Page](#)

[Authors' Biography](#)

[Foreword](#)

[Preface](#)

[Acknowledgments](#)

[1 What Is Smart City?](#)

[1.1 Introduction](#)

[1.2 Characteristics, Functions, and Applications](#)

[1.3 Smart Energy](#)

[1.4 Smart Transportation](#)

[1.5 Smart Health](#)

[1.6 Impact of COVID-19 Pandemic](#)

[1.7 Standards](#)

[1.8 Challenges and Opportunities](#)

[1.9 Conclusions](#)

[Acknowledgements](#)

[References](#)

[2 Lithium-Ion Storage Financial Model](#)

[2.1 Introduction](#)

[2.2 Literature Review](#)

[2.3 Research Background: Hybrid Energy System
in Kenya](#)

[2.4 A Case Study on the Degradation Effect on LCOE](#)

[2.5 Financial Modeling for EES](#)

[2.6 Case Studies on Financing EES in Kenya](#)

[2.7 Sensitivity Analysis of Technical and Economic Parameters](#)

[2.8 Discussion and Future Work](#)

[2.9 Conclusions](#)

[Acknowledgments](#)

[References](#)

[3 Levelized Cost of Electricity for Photovoltaic with Energy Storage](#)

[Nomenclature](#)

[3.1 Introduction](#)

[3.2 Literature Review](#)

[3.3 Data Analysis and Operating Regime](#)

[3.4 Economic Analysis](#)

[3.5 Conclusions](#)

[Acknowledgment](#)

[References](#)

[4 Electricity Plan Recommender System](#)

[Nomenclature](#)

[4.1 Introduction](#)

[4.2 Proposed Matrix Recovery Methods](#)

[4.3 Proposed Electricity Plan Recommender System](#)

[4.4 Simulations and Discussions](#)

[4.5 Conclusion and Future Work](#)

[Acknowledgments](#)

[References](#)

5 Classifier Economics of Semi-intrusive Load Monitoring

5.1 Introduction

5.2 Typical Feature Space of SILM

5.3 Modeling of SILM Classifier Network

5.4 Classifier Locating Optimization with Ensuring on Accuracy and Classifier Economics

5.5 Numerical Study

5.6 Conclusion

Acknowledgements

References

6 Residential Demand Response Shifting Boundary

6.1 Introduction

6.2 Residential Customer Behavior Modeling

6.3 Residential Customer Shifting Boundary

6.4 Case Study

6.5 Case Study on Residential Customer TOU Time Zone Planning

6.6 Case Study on Smart Meter Installation Scale Analysis

6.7 Conclusions and Future Work

Acknowledgements

References

7 Residential PV Panels Planning-Based Game-Theoretic Method

Nomenclature

7.1 Introduction

7.2 System Modeling

7.3 Bi-level Energy Sharing Model for Determining Optimal PV Panels Installation Capacity

[7.4 Stochastic Optimal PV Panels Allocation in the Coalition of Prosumer Agents](#)

[7.5 Numerical Results](#)

[7.6 Conclusion](#)

[Acknowledgements](#)

[References](#)

[8 Networked Microgrids Energy Management Under High Renewable Penetration](#)

[Nomenclature](#)

[8.1 Introduction](#)

[8.2 Problem Description](#)

[8.3 Components Modeling](#)

[8.4 Proposed Two-Stage Operation Model](#)

[8.5 Case Studies](#)

[8.6 Conclusions](#)

[Acknowledgements](#)

[References](#)

[9 A Multi-agent Reinforcement Learning for Home Energy Management](#)

[Nomenclature](#)

[9.1 Introduction](#)

[9.2 Problem Modeling](#)

[9.3 Proposed Data-Driven-Based Solution Method](#)

[9.4 Test Results](#)

[9.5 Conclusion](#)

[Acknowledgements](#)

[References](#)

[10 Virtual Energy Storage Systems Smart Coordination](#)

[10.1 Introduction](#)

[10.2 VESS Modeling, Aggregation, and Coordination Strategy](#)

[10.3 Proposed Approach for Network Loading and Voltage Management by VESSs](#)

[10.4 Case Studies](#)

[10.5 Conclusions and Future Work](#)

[Acknowledgements](#)

[References](#)

[11 Reliability Modeling and Assessment of Cyber-Physical Power Systems](#)

[Nomenclature](#)

[11.1 Introduction](#)

[11.2 Composite Markov Model](#)

[11.3 Linear Programming Model for Maximum Flow](#)

[11.4 Reliability Analysis Method](#)

[11.5 Case Analysis](#)

[11.6 Conclusion](#)

[Acknowledgements](#)

[References](#)

[12 A Vehicle-To-Grid Voltage Support Co-simulation Platform](#)

[12.1 Introduction](#)

[12.2 Related Works](#)

[12.3 Direct-Execution Simulation](#)

[12.4 Co-Simulation Platform for Agent-Based Smart Grid Applications](#)

[12.5 Agent-Based FLISR Case Study](#)

[12.6 Simulation Results](#)

[12.7 Case Study on V2G for Voltage Support](#)

[12.8 Conclusions](#)

[Acknowledgements](#)

[References](#)

[13 Advanced Metering Infrastructure for Electric Vehicle Charging](#)

[13.1 Introduction](#)

[13.2 EVAMI Overview](#)

[13.3 System Architecture, Protocol Design, and Implementation](#)

[13.4 Performance Evaluation](#)

[13.5 Conclusion](#)

[Acknowledgements](#)

[References](#)

[14 Power System Dispatching with Plug-In Hybrid Electric Vehicles](#)

[Nomenclature](#)

[14.1 Introduction](#)

[14.2 Framework of PHEVs Dispatching](#)

[14.3 Framework for the Two-Stage Model](#)

[14.4 The Charging and Discharging Mode](#)

[14.5 The Optimal Dispatching Model with PHEVs](#)

[14.6 Numerical Examples](#)

[14.7 Practical Application - The Impact of Electric Vehicles on Distribution Network](#)

[14.8 Conclusions](#)

[Acknowledgements](#)

[References](#)

[Appendix 14.A](#)

15 Machine Learning for Electric Bus Fast-Charging Stations Deployment

Nomenclature

15.1 Introduction

15.2 Problem Description and Assumptions

15.3 Model Formulation

15.4 Results and Discussion

15.5 Conclusions

Acknowledgements

References

16 Best Practice for Parking Vehicles with Low-power Wide-Area Network

16.1 Introduction

16.2 Related Work

16.3 LP-INDEX for Best Practices of LPWAN Technologies

16.4 Case Study

16.5 Conclusion and Future Work

Acknowledgements

References

17 Smart Health Based on Internet of Things (IoT) and Smart Devices

17.1 Introduction

17.2 Technology Used in Healthcare

17.3 Case Study

17.4 Conclusions

References

18 Criteria Decision Analysis Based Cardiovascular Diseases Classifier for Drunk Driver Detection

[18.1 Introduction](#)

[18.2 Cardiovascular Diseases Classifier](#)

[18.3 Multiple Criteria Decision Analysis of the Optimal CDC](#)

[18.4 Analytic Hierarchy Process Scores and Analysis](#)

[18.5 Development of EDG-Based Drunk Driver Detection](#)

[18.6 ECG-Based Drunk Driver Detection Scheme Design](#)

[18.7 Result Comparisons](#)

[18.8 Conclusions](#)

[Acknowledgements](#)

[References](#)

[19 Bioinformatics and Telemedicine for Healthcare](#)

[19.1 Introduction](#)

[19.2 Bioinformatics](#)

[19.3 Top-Level Design for Integration of Bioinformatics to Smart Health](#)

[19.4 Artificial Intelligence Roadmap](#)

[19.5 Intelligence Techniques for Data Analysis Examples](#)

[19.6 Decision Support System](#)

[19.7 Conclusions](#)

[References](#)

[20 Concluding Remark and the Future](#)

[20.1 The Relationship](#)

[20.2 Roadmap](#)

[20.3 The Future](#)

[References](#)

[Index](#)

[bibliography](#)

[End User License Agreement](#)

List of Tables

Chapter 1

[Table 1.1 Recent Institute of Electrical and Electronics Engineers \(IEEE\) St...](#)

[**Table 1.2** Recent IEEE Standards in development for smart health.](#)

[**Table 1.3** Recent IEEE Standards in development for smart mobility and transp...](#)

[**Table 1.4** Recent IEEE Standards in development for smart education.](#)

[Table 1.5 Recent IEEE Standards in development for smart governance.](#)

[Table 1.6 Smart cities pilot projects in Africa.](#)

[Table 1.7 Smart cities pilot projects in Asia.](#)

[Table 1.8 Smart cities pilot projects in Europe.](#)

[Table 1.9 Smart cities pilot projects in North America and South America....](#)

Chapter 2

[Table 2.1 Comparison of recent techno-economic and financing studies for EES...](#)

[Table 2.2 Technical and economic specifications.](#)

[Table 2.3 Financial modeling results for the six scenarios.](#)

[Table 2.4 Equity NPV \(M\\$\) under different EES's capital costs and retail ele...](#)

Chapter 3

[Table 3.1 Kenya normalized national load demand \[1\]](#)

[Table 3.2 Cost and components size.](#)

Chapter 4

[Table 4.1 Some typical indirect EPRS methods.](#)

[Table 4.2 Some typical matrix recovery methods.](#)

[Table 4.3 The selected appliances.](#)

[Table 4.4 The RMSE performance for 2014 data.](#)

[**Table 4.5** The RMSE performance for 2015 data.](#)

[Table 4.6 The RMSE performance for 2016 data.](#)

[**Table 4.7** The RMSE performance for 2017 data.](#)

[Table 4.8 The RMSE performance for 2018 data.](#)

[Table 4.9 *t*-test result between proposed models and other methods for 2014 d...](#)

[**Table 4.10** *t*-test result between proposed models and other methods for 2015 ...](#)

[**Table 4.11** *t*-test result between proposed models and other methods for 2016 ...](#)

[**Table 4.12** *t*-test result between proposed models and other methods for 2017 ...](#)

[Table 4.13 *t*-test result between proposed models and other methods for 2018 ...](#)

[Table 4.14 The precision performance for 2015 data.](#)

[Table 4.15 The precision performance for 2016 data.](#)

[Table 4.16 The precision performance for 2017 data.](#)

[Table 4.17 The precision performance for 2018 data.](#)

[Table 4.18 *t*-test result between proposed models and other methods for 2015...](#)

[**Table 4.19** *t*-test result between proposed models and other methods for 2016 ...](#)

[**Table 20** *t*-test result between proposed models and other methods for 2017 da...](#)

[Table 4.21 *t*-test result between proposed models and other methods for 2018...](#)

Chapter 5

[Table 5.1 Price sample of meters in Figure 5.2.](#)

[Table 5.2 Device selections in Figure 5.7.](#)

[Table 5.3 Device selections in Figure 5.8.](#)

[Table 5.4 Parameters of random forest and genetic algorithm.](#)

[Table 5.5 Classifier economics optimization result on REDD dataset and fact...](#)

[Table 5.6 Classifier economics optimization result on REDD dataset with dif...](#)

Chapter 6

[Table 6.1 Parameters for Eq. \(6.4\).](#)

[Table 6.2 Parameters for Eq. \(6.5\).](#)

[Table 6.3 Parameters for Eq. \(6.7\).](#)

[Table 6.4 Typical transformation range of daily meals.](#)

[Table 6.5 Details of home appliances in case study.](#)

[Table 6.6 Distribution of family membership.](#)

[Table 6.7 Load variation between TOU and static price.](#)

[Table 6.8 some TOU tariffs selections of time zone planning.](#)

[Table 6.9 Morning_peak variation.](#)

[Table 6.10 Relation between smart meter scale and consumer participation ra...](#)

Chapter 7

[Table 7.1 Related parameters in the 33-node case.](#)

[Table 7.2 Optimal residential PV panels planning result in 33-node system....](#)

[Table 7.3 Residential PV panels planning size and cost and daily revenue wi...](#)

[Table 7.4 Computation performance on solving proposed bi-level energy shari...](#)

[Table 7.5 Optimal residential PV panels planning result in 123-node system....](#)

Chapter 8

[Table 8.1 Parameters of CDGs in each microgrid and MGC \[34\].](#)

[Table 8.2 Parameters of BESSs in each microgrid and MGC \[35\].](#)

[Table 8.3 Operation cost for microgrids components in Case 1.](#)

[Table 8.4 Operation cost for microgrids components in Case 2.](#)

Chapter 9

[Table 9.1 State set, action set, and reward function of each agent.](#)

[Table 9.2 Parameters of each house appliance and EV battery.](#)

[Table 9.3 MAPE of prediction result in cases 1-3.](#)

[Table 9.4 Computational efficiency performance with different number of stat...](#)

[Table 9.5 Comparison of electricity cost with and without.](#)

[Table 9.6 Comparison on computation efficiency by GA optimization method and...](#)

Chapter 10

[Table 10.1 VESS parameters sampling ranges for Monte-Carlo simulation.](#)

[Table 10.2 Rated capacity in each node of the system.](#)

[Table 10.3 Calculation speed and system performance for different network to...](#)

Chapter 11

[Table 11.1 Parameters of composite markov model of acquisition nodes.](#)

[Table 11.2 Parameters of binary-state markov model of routing nodes.](#)

[Table 11.3 Parameters of binary-state markov model of central nodes.](#)

[Table 11.4 Reliability indices by sequential Monte-Carlo simulations with di...](#)

[Table 11.5 Availability in different scenarios.](#)

[Table 11.6 Reliability indices of the physical network.](#)

Chapter 12

[Table 12.1 Characteristics of related works in smart grid co-simulation.](#)

[Table 12.2 Characteristics of simulated network.](#)

[Table 12.3 Simulation event trace for NA1 and NA6.](#)

[Table 12.4 Percentage change of reconfiguration time.](#)

[Table 12.5 Amount of EV and total \(dis\)charging power at each bus.](#)

[Table 12.6 Electrical characteristics of EV.](#)

[Table 12.7 RTT delay of each link.](#)

[Table 12.8 Duration of disruption.](#)

Chapter 13

[Table 13.1 Specification of PLC module.](#)

[Table 13.2 Definition of charging level \[24\].](#)

Chapter 14

[Table 14.1 Parameters of generators of the 6-bus system.](#)

[Table 14.2](#) Hourly load data of the 6-bus system.

[Table 14.3](#) Periods and prices of charging and discharging.

[Table 14.4](#) Bus data of the 6-bus system.

[Table 14.5 Branch data of the 6-bus system.](#)

[Table 14.6 The optimal dispatching schemes with and without PHEVs.](#)

[Table 14.7 The optimal charging and discharging schedules for PHEVs of the 6...](#)

[Table 14.8 The line flow of the 6-bus system.](#)

[Table 14.9 Optimal dispatching schemes under different cost coefficients of ...](#)

[Table 14.10 Electric private vehicle plug-in time.](#)

[Table 14.11 Electric private vehicle charging quantity.](#)

[Table 14.12 Plug-in-time and charging quantity of private vehicles and elect...](#)

[Table 14.13 Electric buses plug-in time.](#)

[Table 14.14 Electric buses charging quantity.](#)

[Table 14.15 Prediction of vehicle PARC in Yangjiang.](#)

[Table 14.16 Prediction of EV PARC in Yangjiang \(From \[B\]\).](#)

Chapter 15

[Table 15.1 Research on e-bus charging stations deployment.](#)

[Table 15.2 Bus dispatching schedule.](#)

[Table 15.3 Planning scheme of fast-charging stations.](#)

[Table 15.4 Cost of fast-charging stations.](#)

[Table 15.5 Parameter values of the battery sizes.](#)

Chapter 16

[Table 16.1 Comparison between LPWAN and other types of wireless technologies...](#)

[Table 16.2 The weightings used for the case study to calculate LP-INDEX.](#)

Chapter 17

[Table 17.1 Number of IoT connected devices worldwide from 2020 to 2030.](#)

Chapter 18

[Table 18.1 Database specification of ECG data for CDC.](#)

[Table 18.2 CDC of each configuration.](#)

[Table 18.3 Pairwise comparison \$7 \times 7\$ matrix \$A_m\$.](#)

[Table 18.4 Performance of NC versus TC.](#)

[Table 18.5 Energy spectral of ECG signal.](#)

Chapter 19

[Table 19.1 Number of electricity, gas, and water smart meters between 2014 a...](#)

List of Illustrations

Chapter 2

[Figure 2.1 Diagram of the hybrid energy system.](#)

[Figure 2.2 Kenya solar irradiance data.](#)

[Figure 2.3 Retail electricity price in Kenya for CI3 customers \[62\].](#)

[Figure 2.4 System LCOE studies with various SOC Threshold](#)

[Figure 2.5 System LCOE with the degradation cost considered.](#)

[Figure 2.6 System LCOE with the degradation cost not considered.](#)

[Figure 2.7 Exemplification of the financial model for EES.](#)

[Figure 2.8 Technical, financial, and economic inputs for EES financial asses...](#)

[Figure 2.9 LCOS with respect to various WACC. The vertical dashed lines are ...](#)

[Figure 2.10 Equity NPV with respect to various WACC. The vertical dashed lin...](#)

[Figure 2.11 Cumulated cash flow to the firm and cumulated cash to the equity...](#)

[Figure 2.12 Cumulated cash flow to the firm and cumulated cash to equity for...](#)

[Figure 2.13 Percentage of the costs for three operating scenarios with EES c...](#)

[Figure 2.14 Relationship between LCOS and EES capital cost under the three o...](#)

[Figure 2.15 The cumulated cash flow to the equity under different retail ele...](#)

[Figure 2.16 Sensitivity analysis on parameters for “High-AD” scenario.](#)

[Figure 2.17 Sensitivity analysis on parameters for “Balanced” scenario.](#)

[Figure 2.18 Sensitivity analysis on parameters for “High-PV” scenario.](#)

[Figure 3.1 Solar insolation and capacity factor for solar farm](#)

[Figure 3.2 Schematic diagram of the hybrid system.](#)

[Figure 3.3 Proposed hybrid system operating regime.](#)

[Figure 3.4 System's power output for summer case.](#)

[Figure 3.5 System's power output for spring case.](#)

[Figure 3.6 EES SOC for 0 and 100% \$SOC_{Threshold}\$ in summer and spring cases....](#)

[Figure 3.7 Fuel consumption curve for AD \[30\].](#)

[Figure 3.8 \$LiCoO_2\$ cycle life function for discharge from 100% SOC.](#)

[Figure 3.9 Comparison of Li-ion EES degradation costs and cycle life for dis...](#)

[Figure 3.10 Number of lifetime EES replacements for different \$SOC_{Threshold}\$ ](#)

[Figure 3.11 System's lifetime SOC_s and SOC differences for \$SOC_{Threshold}\$ at 0...](#)

[Figure 3.12 LCOE for AD, EES and system at different \$SOC_{Threshold}\$ values....](#)

[Figure 3.13 System LCOE with different EES capital costs.](#)

Chapter 4

[Figure 4.1 The dual-stage framework of EPRS.](#)

[Figure 4.2 The recovery example of LRR and RPCA.](#)

[Figure 4.3 The framework of EPRS-EI.](#)

[Figure 4.4 RMSE for different databases with different parameters. \(only sho...](#)

[Figure 4.5 Learning curve with different training data size \(only show 2015-...](#)

[Figure 4.6 Precision for different databases with different parameters \(only...](#)

Chapter 5

[Figure 5.1 SILM/NILM monitoring structure.](#)

[Figure 5.2 Meters. \(a\) For active power only. \(b\) For both active power and ...](#)

[Figure 5.3 Preliminary experiment on classifier performances by increasing d...](#)

[Figure 5.4 Grid connection of each consumer.](#)

[Figure 5.5 Sample section of candidate SILM network.](#)

[Figure 5.6 Modified GA optimization algorithm.](#)

[Figure 5.7 Typical residential network topology for numerical study.](#)

[Figure 5.8 Factory topology for numerical study.](#)

[Figure 5.9 Average meter number of each row in Table 5.5.](#)

[Figure 5.10 Average meter number of each row in Table 5.5.](#)

[Figure 5.11 Average number of advanced meter of each column in Table 5.5....](#)

[Figure 5.12 SILM solution comparison between 130 and 150\\$ with 90% accuracy ...](#)

[Figure 5.13 Cost variation of SILM solution via price of advanced meter and ...](#)

[Figure 5.14 Typical performance comparison among different classifier models...](#)

Chapter 6

[Figure 6.1 Loop interaction structure of PBPs.](#)

[Figure 6.2 Multi-agent system model for loop interaction structure.](#)

[Figure 6.3 Agent structure of consumers DR participated.](#)

[Figure 6.4 Inner structure of decision-making.](#)

[Figure 6.5 Typical time varying at home rate and awake rate for residential ...](#)

[Figure 6.6 Agents' time-varying at home status and sleeping status.](#)

[Figure 6.7 Initial consumer behavior on home appliances before optimization....](#)

[Figure 6.8 Normalized load comparison between the load constructed from surv...](#)

[Figure 6.9 A typical 2-period TOU tariff for Chinese Residents.](#)

[Figure 6.10 Daily load curve comparison between static price and TOU shiftin...](#)

[Figure 6.11 Load curve comparison between static price and TOU shifting boun...](#)

[Figure 6.12 Load curve comparison between static price and TOU shifting boun...](#)

[Figure 6.13 Load curve comparison between static price and TOU shifting boun...](#)

[Figure 6.14 Daily load curve and price comparison among 3 PBPs.](#)

[Figure 6.15 Daily load curve of appliances under different PBPs.](#)

[Figure 6.16 Five-day \(weekdays\) price curve variation comparison between RTP...](#)

[Figure 6.17 Boundary comparison between static price, TOU, and RTP.](#)

[Figure 6.18 Variation of daily bill and daily consumption under different pr...](#)

[Figure 6.19 Daily morning peak variation.](#)

[Figure 6.20 Daily morning peak compare among different peak period start tim...](#)

[Figure 6.21 Variation of original daily evening peak and new peak generated ...](#)

[Figure 6.22 Daily morning peak comparison among different peak period end ti...](#)

[Figure 6.23 Daily load curve comparison among multiple smart meter installat...](#)

[Figure 6.24 Comparison between morning peak, daily peak, and daily valley am...](#)

[Figure 6.25 Daily load curve comparison among multiple smart meter installat...](#)

[Figure 6.26 Comparison between morning peak, daily peak, and daily valley am...](#)

Chapter 7

[Figure 7.1 The proposed energy sharing framework between the coalition and c...](#)

[Figure 7.2 Flowchart of our proposed two-stage game-theoretic residential PV...](#)

[Figure 7.3 IEEE 33-node distribution grid with candidate nodes for PV panels...](#)

[Figure 7.4 Uncertainty scenarios of \(a\) load factor \$\gamma_{tw}^L\$, \(b\) PV output factor](#)

[Figure 7.5 Hourly revenue of the coalition in representative \(a\) scenario 6 ...](#)

[Figure 7.6 PV generation sold to the consumer agents and sold to the utility...](#)

[Figure 7.7 Optimal uniform price of each time period in representative Scena...](#)

[Figure 7.8 Tradeoff curve between the total PV panel size and the daily coal...](#)

[Figure 7.9 IEEE 123-node distribution grid with candidate nodes for PV panel...](#)

[Figure 7.10 Tradeoff curve between the total PV panel size and the daily coa...](#)

Chapter 8

[Figure 8.1 The structure of networked microgrids.](#)

[Figure 8.2 Flowchart of proposed multi-time scale energy management strategy...](#)

[Figure 8.3 Day-ahead forecasted profiles \(a\). Forecasted electricity load and...](#)

[Figure 8.4 Exchanged power results in microgrids in Case 1 and Case 2. \(a\) W...](#)

[Figure 8.5 Distributions of system operation cost in day-ahead market in Cas...](#)

[Figure 8.6 \(a\) Summation of power scheduling of BESS, CDG, and controllable ...](#)

[Figure 8.7 \(a\) Summation of exchanged power in individual microgrids in day-...](#)

Chapter 9

[Figure 9.1 Structure of our proposed HEM system \(REFG, refrigerator; AS, ala...](#)

[Figure 9.2 Schematic of the reinforcement learning-based data-driven HEM sys...](#)

[Figure 9.3 Flowchart of implementing our proposed solution method for each a...](#)

[Figure 9.4 Comparison of the actual and predicted electricity prices on 1-4 ...](#)

[Figure 9.5 Comparison of the actual and predicted solar generations on 1-4 J...](#)

[Figure 9.6 Comparison of operation cost with different prediction accuracy....](#)

[Figure 9.7 The convergence of Q-value for power-shiftable agents on 1 Januar...](#)

[Figure 9.8 Energy consumption of five power-shiftable appliances in each tim...](#)

[Figure 9.9 Energy consumption of AC1 with changing dissatisfaction coefficie...](#)

[Figure 9.10 Energy consumption of all appliances on 1 January 2019, \(a\) with...](#)

[Figure 9.11 Optimization performance comparison of the three methods for sch...](#)

Chapter 10

[Figure 10.1 Schematic of VESS models: \(a\). one-parameter model \(b\). two-para...](#)

[Figure 10.2 Proposed hierarchical coordination strategy of aggregated VESSs ...](#)

[Figure 10.3 Operating conditions for network loading management and voltage ...](#)

[Figure 10.4 Flowchart of proposed control scheme for network loading managem...](#)

[Figure 10.5 One-line diagram of nine-node test feeder.](#)

[Figure 10.6 VESSs aggregator maximum controllable capacity in one day.](#)

[Figure 10.7 Voltage profile in one day_\(a\) Voltage profile before control. \(...\)](#)

[Figure 10.8 Network loading change in one day without and with control.](#)

[Figure 10.9 VESSs aggregator active power contribution.](#)

[Figure 10.10 Voltage performance under Star-shape topology_\(a\) Star-shape to...](#)

[Figure 10.11 Voltage regulation performance under Complete-shape topology_\(a...](#)

[Figure 10.12 Voltage regulation performance and network loading management p...](#)

Chapter 11

[Figure 11.1 Multistate transition in the information layer.](#)

[Figure 11.2 Two-state transition of the physical layer.](#)

[Figure 11.3 Coupling model in both information and physical layers.](#)

[Figure 11.4 Node models in the power information system.](#)

[Figure 11.5 Reliability calculating flow chart.](#)

[Figure 11.6 Network topography of the power information system based on IEEE...](#)

[Figure 11.7 The proposed flowchart using a linear programming model.](#)

[Figure 11.8 Information load rate of intermediate nodes.](#)

[Figure 11.9 Flow distribution in a certain scenario.](#)

[Figure 11.10 Information load rate under different scenarios.](#)

[Figure 11.11 Impact of the overall bandwidth on system reliability.](#)

Chapter 12

[Figure 12.1 Converting JADE and agent code into direct-execution simulators ...](#)

[Figure 12.2 Co-simulation architecture.](#)

[Figure 12.3 \(a\) A modified IEEE 34-bus distribution network, and feeder buse...](#)

[Figure 12.4 Two-tiered MAS hierarchy.](#)

[Figure 12.5 Operation flow of a node agent.](#)

[Figure 12.6 New network configuration, with two restoration trees rooted at ...](#)

[Figure 12.7 Simulation of electrical transients during fault and restoration...](#)

[Figure 12.8 Reconfiguration solution time under different levels of backgrou...](#)

[Figure 12.9 Relationship between reconfiguration solution time and link fail...](#)

[Figure 12.10 Reconfiguration solution time affected by the network location ...](#)

[Figure 12.11 IEEE 14-bus system topology and EV locations.](#)

[Figure 12.12 Connection of PMUs, DMS, aggregators, and EVs.](#)

[Figure 12.13 Voltage waveform of bus 9-14 \(Ideal\).](#)

[Figure 12.14 Voltage waveform of bus 9-14 \(No V2G\).](#)

[Figure 12.15 Voltage waveform of bus 12 \(after fault\).](#)

[Figure 12.16 Voltage waveform of bus 12 \(after reclosing\).](#)

[Figure 12.17 Frequency waveform of bus 12 \(after fault\).](#)

[Figure 12.18 Frequency waveform of bus 12 \(after reclosing\).](#)

Chapter 13

[Figure 13.1 EVAMI overview.](#)

[Figure 13.2 Operation flow of the EVCS.](#)

[Figure 13.3 System architecture.](#)

[Figure 13.4 Interaction between EVCS and DCU during Charging Process.](#)

[Figure 13.5 Data flow during service initialization process.](#)

[Figure 13.6 Data flow during service termination process.](#)

[Figure 13.7 EVCS failure report procedure.](#)

[Figure 13.8 Energy price update procedure. \(a\) DCU exchanges setting report ...](#)

[Figure 13.9 Charging session schedule update.](#)

[Figure 13.10 User interface for service manager.](#)

[Figure 13.11 User interface for EV owner. \(a\) Charging profile and billing i...](#)

[Figure 13.12 Network performance of OCS.](#)

[Figure 13.13 Impact of EV charging level on load profile of a residential bu...](#)

[Figure 13.14 Impact of EV AMI on load profile of a residential building.](#)

Chapter 14

[Figure 14.1 EV aggregator illustration.](#)

[Figure 14.2 The flowchart of the computational procedure.](#)

[Figure 14.3 Topology structure of the 6-bus system.](#)

[Figure 14.4 The plug-in time and charging quantity of electric private vehic...](#)

[Figure 14.5 The plug-in time of buses. \(a\) Plug-in time 00.00–06:00. \(b\) Plu...](#)

[Figure 14.6 The charging quantity of electric buses.](#)

[Figure 14.7 Charging load of private vehicles.](#)

[Figure 14.8 Charging load of buses.](#)

[Figure 14.9 Load curve of the region considering the uncontrolled charging l...](#)

[Figure 14.A.1 Summer time load patterns with PHEV charging.](#)

[Figure 14.A.2 Winter time load patterns with PHEV charging.](#)

Chapter 15

[Figure 15.1 AP-BPSO algorithm flowchart.](#)

[Figure 15.2 Schematic diagram of the planning area.](#)

[Figure 15.3 Deployment of fast-charging stations.](#)

[Figure 15.4 Changes in SOC of bus line 8.](#)

[Figure 15.5 Cost and convergence comparison of different optimization planni...](#)

[Figure 15.6 Deployment comparison under different time headways.](#)

[Figure 15.7 Cost comparison under different time headways.](#)

[Figure 15.8 Deployment comparison under different battery size. \(a\) Number o...](#)

[Figure 15.9 Deployment comparison under different charging power. \(a\) Number...](#)

Chapter 16

[Figure 16.1 Number of IoT devices from 2012 to 2020.](#)

[Figure 16.2 A beautiful city affected by air pollution for \(a\) summer and \(b...](#)

[Figure 16.3 Number of connections by applications and technologies used.](#)

[Figure 16.4 The setup of parking detection sensors.](#)

Chapter 17

[Figure 17.1 Percentage of the world population over 65 from 2020 to 2050....](#)

[Figure 17.2 Conventional blood glucose measuring components.](#)

[Figure 17.3 Conventional blood glucose meter.](#)

[Figure 17.4 A continuous blood glucose meters \[76\].](#)

[Figure 17.5 The pug – A lovely pet or an ugly dog?](#)

[Figure 17.6 A collar-wearing pet cat, living with her owner.](#)

[Figure 17.7 Pets are dressed as family members.](#)

[Figure 17.8 People live with pets as family members.](#)

Chapter 18

[Figure 18.1 Block diagram of the new method.](#)

[Figure 18.2 Conventional drunk driving test.](#)

[Figure 18.3 Devices for electrocardiogram \(ECG\) measurement.](#)

[Figure 18.4 Flowchart of proposed ECG-based drunk driver detection scheme.](#)

[Figure 18.5 Preprocessing of ECG signal.](#)

[Figure 18.6 Comparing DDD with other methods \[50\].](#)

Chapter 19

[Figure 19.1 A top-level smart health with smart meter system design \[29\].](#)

[Figure 19.2 A component and module diagram for smart health with a smart met...](#)

[Figure 19.3 A deep learning approach in decision-making for health status.](#)

[Figure 19.4 Multi-view deep forecasting \(MvDF\) framework.](#)