**Lecture Notes in Electrical Engineering 1105**

N. R. Shetty N. H. Prasad H. C. Nagaraj Editors

# Advances in Communication and Applications Proceedings of ERCICA 2023, Volume 2



# **Lecture Notes in Electrical Engineering**

### Volume 1105

#### **Series Editors**

Leopoldo Angrisani, Department of Electrical and Information Technologies Engineering, University of Napoli Federico II, Napoli, Italy Marco Arteaga, Departament de Control y Robótica, Universidad Nacional Autónoma de México, Coyoacán, Mexico Samarjit Chakraborty, Fakultät für Elektrotechnik und Informationstechnik, TU München, München, Germany Jiming Chen, Zhejiang University, Hangzhou, Zhejiang, China Shanben Chen, School of Materials Science and Engineering, Shanghai Jiao Tong University, Shanghai, China Tan Kay Chen, Department of Electrical and Computer Engineering, National University of Singapore, Singapore, Singapore Rüdiger Dillmann, University of Karlsruhe (TH) IAIM, Karlsruhe, Baden-Württemberg, Germany Haibin Duan, Beijing University of Aeronautics and Astronautics, Beijing, China Gianluigi Ferrari, Dipartimento di Ingegneria dell'Informazione, Sede Scientifica Università degli Studi di Parma, Parma, Italy Manuel Ferre, Centre for Automation and Robotics CAR (UPM-CSIC), Universidad Politécnica de Madrid, Madrid, Spain Faryar Jabbari, Department of Mechanical and Aerospace Engineering, University of California, Irvine, CA, USA Limin Jia, State Key Laboratory of Rail Traffic Control and Safety, Beijing Jiaotong University, Beijing, China Janusz Kacprzyk, Intelligent Systems Laboratory, Systems Research Institute, Polish Academy of Sciences, Warsaw, Poland Alaa Khamis, Department of Mechatronics Engineering, German University in Egypt El Tagamoa El Khames, New Cairo City, Egypt Torsten Kroeger, Intrinsic Innovation, Mountain View, CA, USA Yong Li, College of Electrical and Information Engineering, Hunan University, Changsha, Hunan, China Qilian Liang, Department of Electrical Engineering, University of Texas at Arlington, Arlington, TX, USA Ferran Martín, Departament d'Enginyeria Electrònica, Universitat Autònoma de Barcelona, Bellaterra, Barcelona, Spain Tan Cher Ming, College of Engineering, Nanyang Technological University, Singapore, Singapore Wolfgang Minker, Institute of Information Technology, University of Ulm, Ulm, Germany Pradeep Misra, Department of Electrical Engineering, Wright State University, Dayton, OH, USA Subhas Mukhopadhyay, School of Engineering, Macquarie University, NSW, Australia Cun-Zheng Ning, Department of Electrical Engineering, Arizona State University, Tempe, AZ, USA Toyoaki Nishida, Department of Intelligence Science and Technology, Kyoto University, Kyoto, Japan Luca Oneto, Department of Informatics, Bioengineering, Robotics and Systems Engineering, University of Genova, Genova, Genova, Italy Bijaya Ketan Panigrahi, Department of Electrical Engineering, Indian Institute of Technology Delhi, New Delhi, Delhi, India Federica Pascucci, Department di Ingegneria, Università degli Studi Roma Tre, Roma, Italy Yong Qin, State Key Laboratory of Rail Traffic Control and Safety, Beijing Jiaotong University, Beijing, China Gan Woon Seng, School of Electrical and Electronic Engineering, Nanyang Technological University, Singapore, Singapore Joachim Speidel, Institute of Telecommunications, University of Stuttgart, Stuttgart, Germany Germano Veiga, FEUP Campus, INESC Porto, Porto, Portugal Haitao Wu, Academy of Opto-electronics, Chinese Academy of Sciences, Haidian District Beijing, China Walter Zamboni, Department of Computer Engineering, Electrical Engineering and Applied Mathematics, DIEM—Università degli studi di Salerno, Fisciano, Salerno, Italy Junjie James Zhang, Charlotte, NC, USA Kay Chen Tan, Department of Computing, Hong Kong Polytechnic University, Kowloon Tong, Hong Kong

The book series *Lecture Notes in Electrical Engineering* (LNEE) publishes the latest developments in Electrical Engineering—quickly, informally and in high quality. While original research reported in proceedings and monographs has traditionally formed the core of LNEE, we also encourage authors to submit books devoted to supporting student education and professional training in the various fields and applications areas of electrical engineering. The series cover classical and emerging topics concerning:

- Communication Engineering, Information Theory and Networks
- Electronics Engineering and Microelectronics
- Signal, Image and Speech Processing
- Wireless and Mobile Communication
- Circuits and Systems
- Energy Systems, Power Electronics and Electrical Machines
- Electro-optical Engineering
- Instrumentation Engineering
- Avionics Engineering
- Control Systems
- Internet-of-Things and Cybersecurity
- Biomedical Devices, MEMS and NEMS

For general information about this book series, comments or suggestions, please contact [leontina.dicecco@springer.com.](mailto:leontina.dicecco@springer.com)

To submit a proposal or request further information, please contact the Publishing Editor in your country:

#### **China**

Jasmine Dou, Editor [\(jasmine.dou@springer.com](mailto:jasmine.dou@springer.com))

#### **India, Japan, Rest of Asia**

Swati Meherishi, Editorial Director [\(Swati.Meherishi@springer.com\)](mailto:Swati.Meherishi@springer.com)

#### **Southeast Asia, Australia, New Zealand**

Ramesh Nath Premnath, Editor ([ramesh.premnath@springernature.com](mailto:ramesh.premnath@springernature.com))

#### **USA, Canada**

Michael Luby, Senior Editor [\(michael.luby@springer.com\)](mailto:michael.luby@springer.com)

#### **All other Countries**

Leontina Di Cecco, Senior Editor [\(leontina.dicecco@springer.com\)](mailto:leontina.dicecco@springer.com)

**\*\* This series is indexed by EI Compendex and Scopus databases. \*\***

N. R. Shetty · N. H. Prasad · H. C. Nagaraj Editors

# Advances in Communication and Applications

Proceedings of ERCICA 2023, Volume 2



*Editors*  N. R. Shetty Central University of Karnataka Kalaburagi, Karnataka, India

H. C. Nagaraj Nitte Meenakshi Institute of Technology Bengaluru, Karnataka, India

N. H. Prasad Nitte Meenakshi Institute of Technology Bengaluru, Karnataka, India

ISSN 1876-1100 ISSN 1876-1119 (electronic) Lecture Notes in Electrical Engineering<br>ISBN 978-981-99-7632-4 ISB ISBN 978-981-99-7633-1 (eBook) [https://doi.org/10.1007/978-981](https://doi.org/10.1007/978-981-99-7633-1)-99-7633-1

© The Editor(s) (if applicable) and The Author(s), under exclusive license to Springer Nature Singapore Pte Ltd. 2024

This work is subject to copyright. All rights are solely and exclusively licensed by the Publisher, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, reuse of illustrations, recitation, broadcasting, reproduction on microfilms or in any other physical way, and transmission or information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed.

The use of general descriptive names, registered names, trademarks, service marks, etc. in this publication does not imply, even in the absence of a specific statement, that such names are exempt from the relevant protective laws and regulations and therefore free for general use.

The publisher, the authors, and the editors are safe to assume that the advice and information in this book are believed to be true and accurate at the date of publication. Neither the publisher nor the authors or the editors give a warranty, expressed or implied, with respect to the material contained herein or for any errors or omissions that may have been made. The publisher remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

This Springer imprint is published by the registered company Springer Nature Singapore Pte Ltd. The registered company address is: 152 Beach Road, #21-01/04 Gateway East, Singapore 189721, Singapore

Paper in this product is recyclable.

# **Preface**

The Eight International Conference on "Emerging Research in Computing, Information, Communication and Applications," ERCICA 2023 is an annual event organized at the Nitte Meenakshi Institute of Technology (NMIT), Yelahanka, Bengaluru, India, in association with Laghu Udyog Bharati (LUB—Karnataka) and technology partner National Research Development Corporation, Ministry of Science and Technology, Government of India.

ERCICA aims to provide an interdisciplinary forum for discussion among Researchers, Engineers, and Scientists to promote research and exchange of knowledge in computing, information, communications, and related applications. This conference will provide a platform for networking of Academicians, Engineers, and Scientists and also will encourage the participants to undertake high-end research in the above thrust areas.

ERCICA 2023 received more than 400+ papers from all over the world, viz. from China, UK, Africa, Saudi Arabia, and India. The ERCICA Technical Review Committee has followed all necessary steps to screen more than 400 papers by going through six rounds of quality checks on each paper before selection for Presentation/Publication in Springer, Lecture Notes in Electrical Engineering (LNEE) proceedings, is SCOPUS indexed.

The acceptance ratio is 1:4

Kalaburagi, India Bengaluru, India Bengaluru, India February 2023

N. R. Shetty N. H. Prasad H. C. Nagaraj

# **Contents**





Contents ix





Contents xi



# **About the Editors**

**N. R. Shetty** is the Chancellor of the Central University of Karnataka, Kalaburagi, and Chairman of the Review Commission for the State Private University Karnataka. He is currently serving as Advisor to the Nitte Meenakshi Institute of Technology (NMIT), Bengaluru. He is also the Founder and Vice-President of the International Federation of Engineering Education Societies (IFEES), USA. He served as Vice Chancellor of Bangalore University for two terms and President of the ISTE, New Delhi, for three terms. He was also a Member of the Executive Committee of the AICTE and Chairman of its South West Region Committee.

**N. H. Prasad** is currently working as Professor and Head of the Department of Master of Computer Applications at Nitte Meenakshi Institute of Technology, Bengaluru. He completed his Ph.D. at Jawaharlal Nehru University, India. He has more than 18 years of experience in different roles in both public and private sector enterprises, including the Ministry of Human Resource and Development, Government of India. He has received the prestigious "Dr. Abdul Kalam Life Time Achievement Award" and also received a "Young Faculty" Award at the 2nd Academic Brilliance Awards.

**H. C. Nagaraj** obtained his B.E. Degree in Electronics Communication Engineering securing first class with distinction from the University of Mysore in 1981. He obtained his M.E. in Communication Systems from P. S. G. College of Technology, Bharathiar University in 1984 and secured first rank. He received his doctoral degree in the area of Biomedical Signal Processing and Instrumentation from the Indian Institute of Technology (IIT) Madras in 2000. He assumed charge as Principal of Nitte Meenakshi Institute of Technology, Bengaluru, in September 2003, and to date, he is serving as Principal. He has about 38 years of experience in teaching, research, and administration. He has published a number of papers in national and international journals, and conferences and delivered invited talks in the field of biomedical signal processing, image processing, mobile communication, etc. He has guided several students in their Ph.D. programs.

# **Prediction of Airfoil Efficiency by Artificial Neural Network**



**Chinmayi Siddamsetty, D. Jyothika, Tabindah Saleem, P. Manvitha, H. V. Srikanth, and S. Vijay Kumar** 

#### **1 Introduction**

It is essential and critical to validate the aerodynamic properties of an airfoil in designing the fluid flow application and developing the optimal characteristics in this regard. The aerodynamic properties of fluid flow around an airfoil are accurately predicted by using the Reynolds-averaged Navier–Stokes (RANS) equations. However, this method has very elevated computational costs and very long progression intervals. Several researchers from the aviation industry have validated machine learning techniques for solving fluid flow problems that are less time-consuming and cost-effective. Although recent advances in computational power and efficiency have greatly reduced these costs, performing numerical simulations remains a timeconsuming and computationally intensive task for many practical applications. As a result, it was necessary to shorten the computational time and cost for solving problems related to fluid flow.

Several studies, namely incompressible, steady-state flows, predict flow fields, and aerodynamic force coefficients of airfoils, were used to determine the characteristics and performance of the airfoil.

These diversified classes of neural networks have been consistently used to ascertain the visual imagery that these techniques incorporate deep learning techniques, and training can be done by extracting the unique features of an employed convolution layer. For explicit problems, an ANN model is adopted. When this model is used

Department of Aeronautical Engineering, Nitte Meenakshi Institute of Technology, Bangalore, India

e-mail: [schinmayi72@gmail.com](mailto:schinmayi72@gmail.com) 

S. Vijay Kumar

C. Siddamsetty (B) · D. Jyothika · T. Saleem · P. Manvitha · H. V. Srikanth

Department of Mechanical Engineering, Nitte Meenakshi Institute of Technology, Bangalore, India

<sup>©</sup> The Author(s), under exclusive license to Springer Nature Singapore Pte Ltd. 2024 N. R. Shetty et al. (eds.), *Advances in Communication and Applications*, Lecture Notes in Electrical Engineering 1105, [https://doi.org/10.1007/978-981-99-7633-1\\_1](https://doi.org/10.1007/978-981-99-7633-1_1)

for the same purpose, it assists in identifying solutions that can be easily validated (Narendra and Parthasarathy 1990; Hunt et al. 1992).

Ahmed and Kamal (2022) proposed that the ability of a BPNN model to predict the significant aerodynamic features Cl and Cd of airfoils was evaluated. The training was carried out for the BPNN model, validated, and tested using aerodynamic data obtained through numerical simulations of 440 cases. In summary, the BPNN produced promising results for predicting the aerodynamic coefficients of airfoils that were contemplated for distinct conditions. Moin and Khan (2021) cited the best geometric coordinates which were determined by training and comparing the network architecture performance of airfoil. In contrast to CFD analysis, the neural network was found to be proficient in capturing aerodynamic properties with sparse geometric information.

Sekar and Khoo (2019) carried out investigations without directly solving the Navier–Stokes equations, where CNNs were used to estimate the flow field over an airfoil as a role of airfoil geometry, Re, and more. Chen et al. (2020) created a dataset of CAI to determine the CL and CD using flow condition convolution. Bhatnagar and Afshar (2019) used CNNs to validate velocity and pressure fields. There are reports that CNN is used to explain the pressure distribution pattern around the airfoils and to predict the nonuniform study laminar flow in the 2D or 3D domain (Hui et al. 2020; Guo et al. 2016). However, simple ANN architectures have been extensively adapted for addressing the problems associated with designing of an inverse airfoil. Rai and Madavan designed turbomachinery airfoils utilizing pressure distribution (Rai and Madavan 2001) and other design variables (Rai and MAdavan 2000) as input to ANNs. Huang et al. (1994) used ANNs to design and evaluate the Eppler method, which explains the velocity distribution of the airfoil.

The authors claimed that the lift coefficients determined by this method are highly accurate in contrast to the claim, and it is observed that there was a deviation between predicted and actual coefficients. Khurana et al. (2008) used an approach with an ANN on PARSEC (a common method for airfoil parameterization) airfoils as a search agent in order to optimize their shapes. Various reports reported the possibility of using supervised machine learning techniques in the field of aerodynamics (Duru et al. 2021). However, in the previous studies, the ANN model was trained for lesser cases with less range of AoA and needs further investigations to prove its adaptability.

In this study, the test cases were increased along with the range of AoA. The numerical simulation was performed in CFD. This resulted in the model being more accurate in predicting the Cl and Cd for different airfoils. The ANN model was trained in MATLAB using a dataset with different operating conditions such as Re and AoA as input data and the corresponding CL and CD as output data. The primary goal of this research was to develop an ANN architecture capable of predicting the most important aerodynamic characteristics Cd and Cl, which were determined for different airfoils under various aerodynamic conditions.

#### **2 Methodology**

#### *2.1 Numerical Simulation*

The numerical simulation was performed in the CFD software package Ansys Fluent 16.0. The numerical simulations were performed on different airfoil geometries under various flow conditions to obtain the coefficient of lift and drag which then could be used as a training data set to train and validate the ANN model. The CFD analysis on four different NACA series airfoils, i.e., NACA 0012, NACA 0015, NACA 2412, and NACA 4415 was carried out. NACA 0012 and NACA 0015 are symmetrical airfoils and NACA 2412 and NACA 4415 are asymmetric airfoils that have various applications in the field of aeronautics. The simulation was performed for 20 different AoAs on each airfoil varying from  $-10^{\circ}$  to 10°. The Re varied from 0.5  $\times$  10<sup>6</sup> to 5  $\times$  10<sup>6</sup>, i.e., the Re used in the simulation was  $0.5 \times 10^6$ ,  $1 \times 10^6$ ,  $1.5 \times 10^6$ ,  $2 \times 10^6$ ,  $2.5 \times 10^6$ ,  $3 \times 10^6$ ,  $3.5 \times 10^6$ ,  $4 \times 10^6$ ,  $4.5 \times 10^6$ , and  $5 \times 10^6$ . Each airfoil was simulated with each Re at the AoA varying from  $-10^{\circ}$  to  $10^{\circ}$  with a 1° increment between the cases. The meshing details of selected airfoils are shown in Figs. 1a–d.

Altogether, the CFD analysis of 850 such cases was performed. The K-epsilon turbulence model was used which is a general description of turbulence by means of PDE. The standard k-epsilon model was used for a much more practical approach which helps in minimizing the unknowns and presents a set of equations that could be applied to various turbulent applications (Li et al. 2020). The C-type domain was used with the boundary conditions given as velocity inlet and pressure outlet at the inlet and outlet, respectively. The velocity specification was selected as magnitude and direction where magnitude was changed according to the Re. The velocity components x and y are changed with respect to the AoA as cosα and sinα.

When an airfoil is subjected to flow, its streamlined shape enables the flow to split between the airfoil's upper and lower surfaces. The pressure in the upper surface of the airfoil decreases as the flow stretches over the curved upper surface, whereas in the flat lower section, the flow speed and pressure are constant. At the leading edge of the airfoil, the pressure distribution is maximum, whereas at the trailing edge, flow separation occurs. The static pressure distribution is predicted using CFD, and the contour plots are shown in Figs. 1e–h. The conditions for numerical simulations for airfoil flow analysis are mentioned in Table 1.

#### *2.2 Feedforward Backpropagation Neural Network*

A feedforward backpropagation neural network (ANN) is a form of ANN that has three layers: the input layer, the hidden layer, and the output layer. The substantial number of hidden layers is determined by the nature of the challenge. The number of neurons or nodes in the input layer is determined by the quality of the input characteristics, and the number of nodes or neurons in the layer that produces output



**Fig. 1 a** Meshed airfoil NACA 0012, **b** meshed airfoil NACA 0015, **c** meshed airfoil NACA 2412, **d** meshed airfoil NACA 4415, **e** static pressure plot of NACA 0012, **f** static pressure plot of NACA 0015, **g** static pressure plot of NACA 2412, **h** static pressure plot of NACA 4415



**Fig. 1** (continued)

is determined by the number of outputs. Weighted connections transmit all processing items to the next layer, such as neurons or nodes. The weights of the corresponding neurons have been multiplied through the hidden layer's inputs and aggregated by the hidden layer to generate a summed output. The output is then processed using the sigmoid, tan-sigmoid, or threshold activation functions (Yuan et al. 2018). This type of neural network is used because of its speed of functioning, accuracy, and due its ease of implementation. The general architecture of the model used is shown in Fig. 2.

The delta rule is known as the WIDROW-HOFF learning rule using a supervised learning technique. Our model was trained by the adaption learning function called gradient descent (LEARNGDM) which was adopted by the following procedure.

- 1. By giving all the random values each weight  $w_{ij}$  and  $b_j$  where  $i = 1$  to *n* and  $j =$ 1 to *m.*
- 2. Input and output datasets are fed into the BPNN model, and the output of each layer is calculated by the following equation:

$$
y_{jp}^{[lc1]} = f\left(\sum_{i=1}^{N1} w_{ij}^{[l+1]} y_{ip}^{[l]} + b_j^{[l+1]}\right).
$$

3. Error at the output layer is computed by the below formula:

$$
\mathrm{err}_{jp}^{[L]} = f\prime\left(\mathrm{y}_{jp}^{[L]}\right)\left(d_p - \mathrm{y}_{jp}^{[L]}\right),\,
$$

in the  $i_{th}$  hidden layer ( $i = L − 1, L − 2, ... 1$ ).

4. The following equations are used to calculate the bias between the input and output layers and changes in weights

$$
b_{ij}^{[l]}(n+1) = b_i^{[l]}(n) + \text{NG.err}_{jp}^{[l]},
$$
  

$$
w_{ij}^{[l]}(n+1) = w_i^{[l]}(n) + \text{NG.err}_{jp}^{[l]}, y_{jp}^{[i-1]}.
$$

Error terms are back propagated into the neurons of the previous layer while calculating the changes in weights and biases.







**Fig. 2** General block diagram of BPNN

- 5. Steps 2–5 are repeated till the errors are lesser than the minimum specified error.
- 6. The present study involves the usage of the sigmoid activation function and is given by the following equation:

$$
F(x) = 1/(1 + e^{-x}).
$$

#### *2.3 Prediction of Aerodynamic Coefficients*

The block diagram (Fig. 3) depicts the methodology used in this neural network which is used as a regression analysis tool to determine airfoil aerodynamic coefficients such as coefficient of lift and drag (Li et al. 2019). The dataset used in our model consists of 850 cases obtained through CFD analysis in the ANSYS fluent software on four different NACA airfoils: NACA 0015, NACA 0012, NACA 2412, and NACA 4415. Each of these NACA series was analyzed with ten different Re ranging from  $5 * 10<sup>5</sup>$ to  $5 * 10^6$  for various AoA ranges.

The dataset contained two input parameters, velocity and AoA, as well as output parameters, Cl and Cd 70% of the data in the dataset was used for training the network, while 30% was used for testing and validation (Michos et al. 1983). Later, a neural network was trained using a backpropagation algorithm such as the Levenberg– Marquardt algorithm, and training continued until it reached a stopping criterion, which was based on the validation error, i.e., the error should reach a minimum value (Yildiz et al. 2415).

The architecture of the BPNN used consists of two inputs with ten neurons in the hidden layer and two outputs as shown in Fig. 4.



**Fig. 3** Flowchart of the steps followed



**Fig. 4** Architecture of BPNN model used

#### *2.4 Performance Evaluation*

The following parameters are used to evaluate the performance of the BPNN model.

1. RMSE: Lower the value of RMSE, higher the accuracy of the regression of the model, and it is calculated by the following formula:

$$
RMSE = \sqrt{\frac{1}{n}} \sum_{i=0}^{n} |Pi - Mi|^2.
$$

2. Pearson correlation coefficient (*R*): *R*-value varies from − 1 to 1; the accuracy of the regression model is said to be high if it has *R*-value near to 1. *R* I calculated by the following formula:

$$
R = \sqrt{1 - \frac{\Sigma (Mi - Pi)^2}{\Sigma (Mi - M\overline{i}^{\,-})^2}}.
$$

- *n* number of data points in the testing subset.
- *Pi* predicted values for the *i*th aerodynamic coefficient.
- $M_i$  mean of all measured values for the aerodynamic coefficients.

#### **3 Results and Discussions**

The multiple numbers of neurons or nodes that are in the hidden layer are used to train the ANN model to get the best RMSE value. The RMSE values associated with number of neurons in the hidden layer are summarized in Table 2. Ten number of neurons in the hidden layer gave the best RMSE value, i.e., 0.0076318 at 27 epochs. It was discovered that the correlation  $(R)$  value was close to one for all training, validation, and testing cases indicating high accuracy of the predicted value. From the table, it may be inferred that changes in the number of neurons affect the RMSE value in zig-zag fashion indicating that RMSE value is sensitive to several neurons.

Figure 5 describes the relationship between the RMSE and neurons in the hidden layer. A minimum value of 0.0076318of RMSE with accurate prediction was achieved, but there was no continuous trend. As the number of neurons increases, RMSE value for neuron 10 has increased, and then, it decreased for neuron 14;

No. of neurons	Epochs	$RMSE*$ $10^{-3}$	Corr-coeff. for training	Corr-coeff. for validation	Corr-coeff. for testing	Corr-coeff. overall
10 <sup>2</sup>	27	7.6318	0.97557	0.98447	0.98303	0.97812
14	24	6.5816	0.98402	0.98656	0.93697	0.97815
18	12	9.553	0.97581	0.97877	0.98238	0.97716
22	9	5.9927	0.97708	0.98695	0.97691	0.97839
26	6	9.5672	0.9747	0.98147	0.98265	0.97691
30	13	9.3398	0.98386	0.98061	0.94836	0.97769
34	13	10.746	0.98359	0.97696	0.95456	0.97792
36	5	11.265	0.97838	0.97377	0.99939	0.97757
40	7	8.5035	0.9727	0.98105	0.97739	0.97503
44	8	8.4694	0.9768	0.98165	0.9791	0.97809

**Table 2** Correlation table for different neurons



**Fig. 5** Neurons in hidden layer versus RMSE

later for neurons 18 and 22, RMSE value has increased and decreased respectively. RMSE value for the networks with neurons  $26-36$  was seen to increase, whereas RMSE value has again decreased with an increase in neurons to 44.

Figure 6 depicts the relationship between the RMSE value and the network used for the training, validation, testing, and prediction. The graph shows that it was proportionately high at the beginning of training and moderately decreased as training progressed. The RMSE value remained constant after 27 epochs at 0.0076318, and it did not decrease further. This performance graph only shows the best-case scenario. Compared to testing and validation data, RMSE value in the present study is large which may be due to the limited number of training data points in 850 instances.

From Fig. 7, we can conclude that the regression value for training, validation, and testing was near one which indicates high accuracy in the predicted values. BPNN model was trained and validated using the data which was obtained from the historical data. As each of the data points falls on the regressions line, the graphs demonstrate an excellent correlation between the target and projected values. In this work, the trained BPNN model indicates aerodynamic parameters with excellent accuracy and a relatively small number of inaccurate predictions when compared to other current models. Because machine learning techniques require a high number of data sets, model performance is directly related to data size. Only 850 simulated datasets were used to train the BPNN model in this investigation. Because 850 is such a small figure, it could indicate a constraint of the model's performance. To improve the model's dependability, more data from CFD simulations of various airfoils under various conditions must be collected. This will allow us to use this model to estimate aerodynamic coefficients of lift and drag for undiscovered airfoils under varied conditions.



**Fig. 6** Performance plot for the best RMSE case

#### **4 Conclusions**

Validation of the BPNN model was done on basis of its efficiency to predict aerodynamic parameters. It is evident in Fig. 7 that there is a correlation between predicted values and the dataset as R is near to one. This research has contributed to the development of a model that can be used to determine the aerodynamic coefficients (CL and CD) of any airfoil and evaluate its performance. About 850 instances in the dataset obtained from numerical simulations are used to train, test, and validate the developed ANN model. Regression plots showed a nearly perfect fit between the actual and predicted values. At epoch 27, with ten neurons in the hidden layer, the RMSE for the best validation performance obtained was 0.0076318. The model supports any Mach number between 0 and 0.7 and any Re between  $0.5 \times 10^6$  and  $5 \times 10^6$ . To summarize, the developed ANN model produced promising results in efficiently predicting the aerodynamic coefficients of various airfoils.



**Fig. 7** Regression plots for the best RMSE value

#### **Nomenclature**



#### **References**

- Ahmed S, Kamal K (2022) Aerodynamic analyses of airfoils using machine learning as an alternative to RANS simulation. National University of Sciences and Technology, Islamabad 44000, Pakistan. <https://doi.org/10.3390/app12105194>
- Bhatnagar S, Afshar Y (2019) Prediction of aerodynamic flow fields using convolutional neural networks. Comput Mech 64:525–545. <https://doi.org/10.1007/s00466-019-01740-0>
- Chen H, He L, Qian W, Wang S (2020) Multiple aerodynamic coefficient prediction of airfoils using a convolution neural network. Computational Aerodynamics Research Institute, China Aerodynamics Research and Development Center, Mianyang 621000, China. [https://doi.org/](https://doi.org/10.3390/sym12040544) [10.3390/sym12040544](https://doi.org/10.3390/sym12040544)
- Duru C, Alemdar H, Baran U (2021) CNNFOIL: convolutional encoder decoder modeling for pressure fields around airfoils. Neural Comput Appl. [https://doi.org/10.1007/s00521-020-054](https://doi.org/10.1007/s00521-020-05461-x) [61-x](https://doi.org/10.1007/s00521-020-05461-x)
- Guo X, Li W, Iorio F (2016) Convolutional neural networks for steady flow approximation. In: Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining. <https://doi.org/10.1145/2939672.2939738>
- Huang S, Miller L, Steck J (1994) An exploratory application of neural networks to airfoil design. In: 32nd aerospace sciences meeting and exhibit, p 501
- Hui X, Bai J, Wang H, Zhang Y (2020) Fast pressure distribution prediction of airfoils using deep learning. School of Aeronautics, Northwestern Polytechnical University, 127 Youyixi Road, Xi'an, 710072, China.<https://doi.org/10.1016/j.ast.2020.105949>
- Hunt K, Sbarbaro D, Zbikowski R, Gawthrop P (1992) Neural networks for control system
- Khurana M, Winarto H, Sinha A (2008) Application of swarm approach and artificial neural networks for airfoil shape optimization. In: 12th AIAA/ISSMO multidisciplinary analysis and optimization conference
- Li K, Kou J, Zhang W (2019) Deep neural network for unsteady aerodynamic and aeroelastic modeling across multiple Mach numbers. Nonlinear Dyn 96:2157–2177. [https://doi.org/10.](https://doi.org/10.1007/s11071-019-04915-9) [1007/s11071-019-04915-9](https://doi.org/10.1007/s11071-019-04915-9)
- Li J, Zhang M, Martins JRRA, Shu C (2020) Efficient aerodynamic shape optimization with deeplearning-based geometric filtering. AIAA J 58(10):4243–4259. [https://doi.org/10.2514/1.J05](https://doi.org/10.2514/1.J059254) [9254](https://doi.org/10.2514/1.J059254)
- Michos A, Bergeles G, Athanassiadis N (1983) Aerodynamic characteristics of NACA 0012 airfoil in relation to wind generators. Wind Eng 7:247–262. <https://www.jstor.org/stable/43749000>
- Moin H, Khan HZI (2021) Airfoils aerodynamic coefficients prediction using artificial neural network. Department of Aeronautics & Astronautics, Institute of Space Technology, Islamabad, 44000, Pakistan. <https://doi.org/10.48550/arXiv.2109.12149>
- Narendra KS, Parthasarathy KK (1990) Identification and control of dynamical systems using neural networks. IEEE Trans Neural Netw
- Rai MM, Madavan NK (2000) Aerodynamic design using neural networks. AIAA J 38(1):173–182
- Rai MM, Madavan NK (2001) Application of artificial neural networks to the design of turbomachinery airfoils. J Propul Power 17(1):176–183
- Sekar V, Khoo BC (2019) Fast flow field prediction over airfoils using deep learning approach. Phys Fluids 31:057103. <https://doi.org/10.1063/1.5094943>
- Sun G, Sun Y, Wang S (2015) Artificial neural network based inverse design: airfoils and wings. Aerosp Sci Technol 42:415–428
- Yildiz F, Turkmen AC, Celik C, Sarac HI (2015) Pitch angle analysis of NACA 2415 airfoil. In: Proceedings of the world congress on engineering, London, UK, 1–3 July 2015, p 5
- Yuan Z, Wang Y, Qiu Y, Bai J, Chen G (2018) Aerodynamic coefficient prediction of airfoils with convolutional neural network. In: Zhang X (ed) Proceedings of the 2018 Asia-Pacific international symposium on aerospace technology (APISAT 2018), vol 459, Chengdu, China, 16–18 Oct 2018. Springer, Singapore, pp 34–46. [https://doi.org/10.1007/978-981-13-3305-7\\_3](https://doi.org/10.1007/978-981-13-3305-7_3)

# **Predicting Holding Days for Equity Gain Using Wavelets**



**Mala Sundaram, Gitapremnath Raja, and Vimal Pant** 

#### **1 Introduction**

The stock price movements and prediction of future stock values are widely studied in various fields including finance, machine learning, and the trading market. This research attempts to establish that stock can be bought and sold by finding an improved equity gain model at profitable positions. Stock price prediction and indices' movements have been previously investigated by several traders, professionals, and researchers. Many prediction methods for the stock price have been proposed in literature based on various factors such as news and sentiment analysis. Since the stock price movements are volatile and non-stationary, i.e., non-stationary stock prices do not remain constant over time. Therefore, stock market prediction becomes a challenging and difficult task. The stock investor's interest is the motivation for this research work. This work signifies stock price movements using national stock exchange data in the Indian capital market. Further, this work finds the trading interval days using wavelet analysis, which can lead to equity gain in the future.

#### *1.1 Mathematical Preliminaries on Wavelets*

The proposed work utilizes wavelets for the interval-based stock price and indices' movements. Thus, the mathematical preliminaries on wavelets with their related work are presented. This work examines the theoretical foundations of wavelet analysis and various stock market researches based on wavelets.

Nehru Memorial College, Tiruchirappalli, India e-mail: [ursmala@gmail.com](mailto:ursmala@gmail.com)

G. Raja · V. Pant NIFTEM, Sonipat, India

© The Author(s), under exclusive license to Springer Nature Singapore Pte Ltd. 2024 N. R. Shetty et al. (eds.), *Advances in Communication and Applications*, Lecture Notes in Electrical Engineering 1105, [https://doi.org/10.1007/978-981-99-7633-1\\_2](https://doi.org/10.1007/978-981-99-7633-1_2)

M. Sundaram  $(\boxtimes)$ 

#### *1.2 Wavelets*

"A wavelet transform is a tool that cuts up data, functions/operators into different frequencies, and then studies each frequency component with a resolution matched to its scale" (Daubechies 1990). Wavelet refers to a small oscillation with zero mean. Wavelet has frequency- and time-localized functions to analyze the signals identifying the abrupt changes accurately. Wavelets exist for a defined duration and come in different sizes and shapes. Wavelength analysis is strengthened by the availability of a wide range of wavelets. The two main concepts in wavelets are: scaling and shifting. The mathematical representation of equivalent frequency is defined in Eq. 1.

$$
F_{\text{eq}} = \frac{C_{\text{f}}}{S\delta t},\tag{1}
$$

where

*C*f Center frequency.

*S* Scale factor.

δ*t* Sampling interval.

A significant-scale factor results in a stretched wavelet corresponding to low frequency. In contrast, a shorter scale factor results in shrinking/compressed wavelets correspond to high frequency (use narrow window for better frequency resolution). A stretched wavelet helps in capturing slowly varying signals, whereas a compressed wavelet captures abrupt changes. Shifting of a wavelet means delaying (or) advancing the wavelet's onset along the length of the signal. The given signal features are identified by shifting and scaling the wavelets used for the specified application. The scaling and shifting of wavelets are represented in Fig. 1.

#### *1.3 Discrete Wavelet Transform*

Continuous and discrete wavelet transform differs by how the wavelet is shifted and scaled. DWT is easy to implement when compared with CWT. The critical application of discrete wavelets is denoising and compression of signals. The idea in denoising is to keep the most significant coefficients. The DWT requires the signal's length to be dyadic (power of 2) and highly dependent on the origin of the signal analyzed. Any signal  $(S(t))$  can be decomposed by a sequence of projections onto a wavelet basis, shown in Fig. 2.



**Fig. 1** Wavelet at various scales and translations



**Fig. 2** Wavelet decomposition and reconstruction sample

#### *1.4 Haar Wavelet*

Haar Wavelet is the oldest and simplest of wavelets and captures fluctuations between adjacent observations (Huang and Wu 2008; Lahmiri 2013). It resembles a square form. The wavelet function, the scaling function of the Haar Wavelet, is given in Eq. 2.

$$
\phi(t) \longrightarrow \longrightarrow \longrightarrow \longrightarrow \Longrightarrow \left\{ \begin{aligned} &1 \quad \text{for} \quad 0 < t < \frac{1}{2} \\ -1 \quad \text{for} \quad \frac{1}{2} < t < 1 \\ &0 \quad \text{otherwise} \end{aligned} \right\},\tag{2}
$$

#### **2 Literature Review**

This part of the work has focused on studies that have examined the wavelets, wavelets applications, data mining techniques, machine learning, and deep learning implementation in various stock market analyses. Multiple studies show the importance of wavelets and their applications in varieties of fields. This work mainly focuses on wavelets and their applications in stock price and indices' movements.

Wavelets were proposed for various applications (Graps 1995; Gencay et al. 2002; Lee and Yamamoto 1994; Fama 1991). The wavelets to the analysis of financial data and economical data (Ramsey 1999) and wavelets for finding trading interval days are also presented (Mala and Saravanan 2018). The wavelet transform (Daubechies 1990) successfully applied to both time-series financial (Li et al. 2006; Huang and Wu 2008; Lai and Huang 2007; Hsieh et al. 2011; Wang et al. 2019, 2011; Huang 2011; Wang et al. 2011; Kao et al. 2013; Lahmiri et al. 2013; Shah and Debnath 2017) and engineering problems (De and Sil 2012; Rikli 2012) because of its simultaneous analysis in frequency and time domains. Wavelet decomposes given stock price into high- and low-frequency components (Crowley 2005). The wavelets can capture stock price discontinuities in high frequency. In low frequency, the wavelet characterizes the stock data's coarse structure to identify the long-term trends (Lahmiri 2014). Wavelet analysis can extract the hidden temporal features of the stock price. Various factors in the stock market cause stock market instability. The stock market is a complex system that takes much information from news to investors, essential information to socio-political events, and its behavior produces an output (Novak and Veluscek 2015). "Though most of the wavelet applications are in time-series analysis, only very few focuses on stock market data analysis. Deployed various wavelet methods were deployed in stock series with multi-resolution analysis, denoising stock price series, characterizing abrupt changes in the stock prices, and detecting stock series's self-similarity" (Lai and Huang 2007). The discrete wavelet transform