

Lecture Notes in Civil Engineering

Nawawi Chouw  
Chunwei Zhang *Editors*

# Proceedings of the 26th Australasian Conference on the Mechanics of Structures and Materials

ACMSM26, 3–6 December 2023,  
Auckland, New Zealand

 Springer

# Lecture Notes in Civil Engineering

Volume 513

## Series Editors

Marco di Prisco, Politecnico di Milano, Milano, Italy

Sheng-Hong Chen, School of Water Resources and Hydropower Engineering,  
Wuhan University, Wuhan, China

Ioannis Vayas, Institute of Steel Structures, National Technical University of  
Athens, Athens, Greece

Sanjay Kumar Shukla, School of Engineering, Edith Cowan University, Joondalup,  
WA, Australia

Anuj Sharma, Iowa State University, Ames, IA, USA

Nagesh Kumar, Department of Civil Engineering, Indian Institute of Science  
Bangalore, Bengaluru, Karnataka, India

Chien Ming Wang, School of Civil Engineering, The University of Queensland,  
Brisbane, QLD, Australia

Zhen-Dong Cui, China University of Mining and Technology, Xuzhou, China

**Lecture Notes in Civil Engineering (LNCE)** publishes the latest developments in Civil Engineering—quickly, informally and in top quality. Though original research reported in proceedings and post-proceedings represents the core of LNCE, edited volumes of exceptionally high quality and interest may also be considered for publication. Volumes published in LNCE embrace all aspects and subfields of, as well as new challenges in, Civil Engineering. Topics in the series include:

- Construction and Structural Mechanics
- Building Materials
- Concrete, Steel and Timber Structures
- Geotechnical Engineering
- Earthquake Engineering
- Coastal Engineering
- Ocean and Offshore Engineering; Ships and Floating Structures
- Hydraulics, Hydrology and Water Resources Engineering
- Environmental Engineering and Sustainability
- Structural Health and Monitoring
- Surveying and Geographical Information Systems
- Indoor Environments
- Transportation and Traffic
- Risk Analysis
- Safety and Security

To submit a proposal or request further information, please contact the appropriate Springer Editor:

- Pierpaolo Riva at [pierpaolo.riva@springer.com](mailto:pierpaolo.riva@springer.com) (Europe and Americas);
- Swati Meherishi at [swati.meherishi@springer.com](mailto:swati.meherishi@springer.com) (Asia—except China, Australia, and New Zealand);
- Wayne Hu at [wayne.hu@springer.com](mailto:wayne.hu@springer.com) (China).

**All books in the series now indexed by Scopus and EI Compendex database!**

Nawawi Chouw · Chunwei Zhang  
Editors

# Proceedings of the 26th Australasian Conference on the Mechanics of Structures and Materials

ACMSM26, 3–6 December 2023, Auckland,  
New Zealand

 Springer

*Editors*

Nawawi Chowd  
Department of Civil and Environmental  
Engineering  
University of Auckland  
Auckland, New Zealand

Chunwei Zhang  
School of Marine Science and Engineering  
South China University of Technology  
Guangzhou, China

ISSN 2366-2557

ISSN 2366-2565 (electronic)

Lecture Notes in Civil Engineering

ISBN 978-981-97-3396-5

ISBN 978-981-97-3397-2 (eBook)

<https://doi.org/10.1007/978-981-97-3397-2>

© The Editor(s) (if applicable) and The Author(s), under exclusive license to Springer Nature Singapore Pte Ltd. 2024

This work is subject to copyright. All rights are solely and exclusively licensed by the Publisher, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, reuse of illustrations, recitation, broadcasting, reproduction on microfilms or in any other physical way, and transmission or information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed.

The use of general descriptive names, registered names, trademarks, service marks, etc. in this publication does not imply, even in the absence of a specific statement, that such names are exempt from the relevant protective laws and regulations and therefore free for general use.

The publisher, the authors and the editors are safe to assume that the advice and information in this book are believed to be true and accurate at the date of publication. Neither the publisher nor the authors or the editors give a warranty, expressed or implied, with respect to the material contained herein or for any errors or omissions that may have been made. The publisher remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

This Springer imprint is published by the registered company Springer Nature Singapore Pte Ltd. The registered company address is: 152 Beach Road, #21-01/04 Gateway East, Singapore 189721, Singapore

If disposing of this product, please recycle the paper.

# Members of ACMSM Scientific Committee

Prof. Faris Albermani, Central University of Queensland, Australia  
Prof. Daniel Ambrosini, National University of Cuyo, Argentina  
Prof. Thiru Aravinthan, University of Southern Queensland, Australia  
Prof. Charles E. Bakis, Pennsylvania State University, USA  
Prof. Debes Bhattacharyya, The University of Auckland, NZ  
Prof. Tommy Chan, Queensland University of Technology, Australia  
Prof. Nawawi Chouw, The University of Auckland, NZ  
Prof. Rajesh Dhakal, The University of Canterbury, NZ  
Prof. Wenhui Duan, Monash University, Australia  
Prof. Qin Fang, PLA University of Technology, China  
Prof. Sam Fragomeni, Victoria University, Australia  
Prof. Norbert Gebbeken, University of the Bundeswehr Munich, Germany  
Prof. Raymond Gilbert, The University of New South Wales, Australia  
Prof. Michael Griffith, The University of Adelaide, Australia  
Prof. Hong Guan, Griffith University, Australia  
Prof. Muhammad Hadi, University of Wollongong, Australia  
Prof. Hong Hao, Curtin University, Australia  
Prof. Sohichi Hirose, Tokyo Institute of Technology, Japan  
Prof. Sritawat Kitipornchai, The University of Queensland, Australia  
Prof. Tribikram Kundu, University of Arizona, USA  
Prof. Nelson Lam, University of Melbourne, Australia  
Prof. David Lau, Carleton University, Canada  
Dr. Tam Larkin, The University of Auckland, NZ  
Prof. Jianchun Li, RMIT University, Australia  
Prof. Qingming Li, The University of Manchester, GB  
Prof. Guoxing Lu, Swinburne University of Technology, Australia  
Prof. Yew-Chaye Loo, Griffith University, Australia  
Prof. Guowei Ma, University of Western Australia, Australia  
Prof. Xing Ma, University of South Australia, Australia  
Prof. Mahen Mahendran, Queensland University of Technology, Australia  
Prof. Priyan Mendis, The University of Melbourne, Australia

Prof. Rob Melchers, The University of Newcastle, Australia  
Prof. Tomoya Nishiwaki, Tohoku University, Japan  
Prof. Rolando Orense, The University of Auckland, NZ  
Dr. Miguel Ormeno, Airey Consultants, NZ  
Dr. Xiaoyang Qin, ARUP Limited, NZ  
Prof. Gianluca Ranzi, The University of Sydney, Australia  
Prof. Kim Rasmussen, The University of Sydney, Australia  
Prof. Wei Xin Ren, Shenzhen University, China  
Prof. Ilias Dimitrakopoulos, The Hong Kong University of Science and Technology, China  
Prof. Bijan Samali, Western Sydney University, Australia  
Prof. Chongmin Song, The University of New South Wales, Australia  
Prof. Jay Sanjayan, Swinburne University of Technology, Australia  
Prof. Caijun Shi, Hunan University, China  
Prof. Scott T. Smith, University of Adelaide, Australia  
Prof. Mark Stewart, University of Technology Sydney, Australia  
Prof. Izuru Takewaki, Kyoto Arts and Crafts University, Japan  
Prof. Zhong Tao, University of Western Sydney, Australia  
Prof. David Thambiratnam, Queensland University of Technology, Australia  
Prof. Brian Uy, The University of New South Wales, Australia  
Prof. Chien Ming Wang, The University of Queensland, Australia  
Prof. Hao Wang, University of Southern Queensland, Australia  
Prof. Ying Wang, University of Surrey, GB  
Prof. Douglas Wilson, The University of Auckland, NZ  
Prof. Yong Xia, The Hong Kong Polytechnic University, China  
Prof. Yang Xiang, Swinburne University of Technology, Australia  
Prof. Chung Bang Yun, Zhejiang University, China  
Prof. Ben Young, The Hong Kong Polytechnic University, China  
Prof. Chunwei Zhang, South China University of Technology, China  
Prof. Xinqun Zhu, University of Technology Sydney, Australia  
Prof. Yan Zhuge, University of South Australia, Australia

# Local Organising Committee

## Chairperson

Nawawi Chouw

## Members

Rolando Orense  
Tam Larkin  
Douglas Wilson  
Xiaoyang Qin  
Miguel Ormeño  
Wei Loo  
Chin-Long Lee

## Team

Anastasios Giouvanidis  
Fengze Li  
Sujith Padiyara  
Yuanyuan Wei  
Ruisong Xue  
Ziqi Yang  
Zhanxi Ye  
Mengya You  
Kun Zhang



# Preface

The series of ACMSM conferences was first held in Sydney in 1967. It is one of the longest running and reputable conferences in the field, taking place every 2–3 years either in Australia or New Zealand. The ACMSM26 has been postponed three times due to the COVID-19 pandemic. But finally, after more than 35 years, the conference returns to Auckland. Over these decades, the topics of the conference have expanded to include much broader research areas, beyond structural and material mechanics, as this year’s conference demonstrates. The conference is no longer a premier forum largely for participants from Australia and New Zealand, but also an essential gathering of emerging and established researchers, as well as practicing engineers, from many countries. The conference presents an ideal platform for participants to extensively exchange knowledge and experiences as well as the development of new friendships and collaborations. Despite the reverberation of the pandemic, the ACMSM26 has attracted over 120 participants from four continents.

These ACMSM26 e-proceedings contain a selected set of 83 papers that cover a range of topics in the mechanics of structures and materials. We hope that the papers will ignite new ideas and trigger new collaborations in your research.

We would like to express our sincere gratitude to all authors, reviewers of the papers, and sponsors, i.e., the University of Auckland, Faculty of Engineering Transportation Research Centre, Asian Concrete Federation, Shenyang University of Technology, HIWAY Group, South China University of Technology, Downer, and Road Science for making this conference possible.

Auckland, New Zealand

Nawawi Chouw  
Chunwei Zhang

# Contents

<b>Composite Structures, Concrete, and Pavements</b>	
<b>Spatial Correlation of Flexural Tensile Bond Strength in Unreinforced Masonry Walls</b> .....	3
L. J. Gooch, M. J. Masia, M. G. Stewart, and C. Collard	
<b>Seismic Assessment and Upgrade of Concrete Wharf Structure</b> .....	13
F. Yu, X. Qin, and C. Wicaksana	
<b>Modelling Compressive Strength of Concrete Incorporating Supplementary Cementitious Materials Using Machine Learning Technologies</b> .....	25
Yang Yu, Ailar Hajimohammadi, Ali Nezhad, David Hocking, Farzad Moghaddam, and Stephen Foster	
<b>Towards the Development of a Low-Carbon Emission Sandwich Panel—A State-of-the-Art Review</b> .....	35
Ashiqul Islam, Wahid Ferdous, Polly Burey, Kamrun Nahar, and Allan Manalo	
<b>Toxic Leaching and Engineering Properties of Copper Contaminated Soil Cured by Magnesium Phosphate Cement</b> .....	45
Shiwei Hou, Zhanwen Lai, Hao Zhang, and Junyan Han	
<b>Impact of Concrete Properties on the Carbon Footprint of a Structure When Using Green Concrete</b> .....	55
T. Khaoted and S. Al-Deen	
<b>Impact of Corroded Galvanised Wall Ties on the Structural Integrity of Masonry Veneer Walls</b> .....	65
L. Terry, G. Gillogly, I. A. Chaves, M. Masia, and R. Petersen	

**Mesoscale Analysis of Rubber Particle Effect on Tensile Strength of Crumb Rubber Concrete** ..... 77  
 Huailiang Chen, Danda Li, Xing Ma, Zheng Zhong, and El-Sayed Abd-Elaal

**Meso-Scale Numerical Creep Analysis of Steel Fibre Reinforced Concrete—Effect of Aggregate and Fibre Content** ..... 89  
 S. Zhang, E. Hamed, I. Gilbert, and A. Amin

**Effect of Cracks Along the Rebars on the Bond Deterioration Under Tensile Stress in Reinforced Concrete** ..... 99  
 M. Kojima, N. Chijiwa, and R. Kurihara

**Interface Bonding Behavior of Ordinary Concrete Reinforced with Lightweight High-Strength Engineered Cementitious Composite** ..... 111  
 H. Gou, M. Sofi, R. Zhang, and P. Mendis

**Stability Assessment of Masonry Domes Using Thrust Network Analysis in Earth and Lunar Environments** ..... 123  
 S. Lee, T. Bennett, and S. T. Smith

**Use of Innovative Materials as Ground Improvement Technique to Mitigate Soil Liquefaction** ..... 135  
 Shaswat and R. P. Orense

**Flexural Behaviour of Pultruded GFRP Profiles Filled with Layered Composite Panels for Railway Sleepers** ..... 145  
 Mamun Abdullah, Wahid Ferdous, Sourish Banerjee, and Allan Manalo

**Analysis of Bond Performance of Timber Beam and CFRP RODS Bonded with Different End Conditions** ..... 153  
 Hafedh Al-Mashgari, Xuemei Liu, Tuan Ngyuen, and Tuan Ngo

**Application of Non-destructive Testing Techniques for Condition Assessment of Wall Ties in Masonry Construction** ..... 165  
 C. Y. Lam, M. J. Masia, and I. A. Chaves

**The Effect of Single and Bimodulus Material Behavior on Longitudinal Compression Failure of Bamboo Culms Under Flexure** ..... 175  
 Nahid Khodabakhshi, Theodora Mouka, and Elias G. Dimitrakopoulos

**Maximum Spanning Capacity of a Catenary Arch Under Selfweight Against Buckling** ..... 185  
 C. M. Wang and J. M. Zhang

**Correlation Between Cold Recycled Mixture Triaxial Parameters and Conventional Mechanical and Volumetric Properties** ..... 199  
 Pablo Orosa, Ignacio Pérez, Ana R. Pasandín, and John E. Haddock

**Characterizing Reduction of Variability in Bamboo Axial Members Through Use of Multiple Culms and Grading** ..... 211  
 Nischal P. N. Pradhan, Nahid Khodabakhshi, and Elias G. Dimitrakopoulos

**A Framework for Estimating Structural Stability Decay of Multistorey Cavity Brick and Brick Veneer Masonry Walls** ..... 225  
 I. A. Chaves, M. J. Masia, R. E. Melchers, S. de Prazer, and W. Chen

**Flexural and Shear Response of One-Part Alkali-Activated Reinforced Concrete Beams** ..... 237  
 A. Tambusay, B. Suryanto, and P. Suprobo

**Failure Mechanisms of Multiple External Column Removals in RC Flat Plate Structures** ..... 249  
 Z. Q. Zhao, H. Guan, H. Z. Xue, Y. Li, and B. P. Gilbert

**Extended Abstract: Drying Shrinkage, Water Absorption and Electrical Behaviour of Mortar Reinforced with Polymer Fibres** ... 261  
 Y. Tao and S. A. Hadigheh

**Experimental Investigation and Numerical Analysis on the Flexural Response of the GFRP-Reinforced Concrete Pontoon Deck** ..... 267  
 Shahrad Ebrahimzadeh, Allan Manalo, Omar Alajarmeh, Xian Yang, Charles-Dean Sorbello, Senarath Weerakoon, and Choman Salih

**Connection, Steel, Timber, and Fire Engineering**

**Experimental Study on Screw Connections of Aluminium Roof-Purlin Systems** ..... 285  
 Y. Su, X. Ma, Y. Zhuge, E. Abdelaal, A. Singh, H. Habib, and M. Aburas

**Experimental Analysis of Hybrid Timber-Steel Connections Under Quasi-Static Loading** ..... 297  
 B. E. Thevarajah, Alex M. Remennikov, Tuan D. Ngo, Hong Guan, and Benoit P. Gilbert

**A Simplified Finite Element Model of Grouted Duct Connections in Precast Reinforced Concrete Walls** ..... 311  
 X. Weng, E. Lumantarna, R. D. Hoult, and N. T. K. Lam

**Significance of End Connection Rigidity on the Economic Design of Long-Span Timber Beams** ..... 323  
 M. Z. Patowary, S. Al-Deen, and M. Ashraf

**Behaviour of Redundant Fasteners under Tension Load with Crack Cycling** ..... 333  
 C. C. Neupane, J. Lee, T. Pokharel, H. H. Tsang, and E. Gad

**Effects of External Architectural Features on the Performance of Buildings Under Wildfire Exposure Conditions** ..... 343  
 S. Hendawitharana, L. Plumpton, A. Ariyanayagam, and M. Mahendran

**Performance of External Light Steel Walls Lined with Steel Cladding Under Wildfire Exposure Conditions** ..... 353  
 S. Hendawitharana, A. Ariyanayagam, and M. Mahendran

**Fire Behavior of Ultra-High Strength Concrete Filled Steel Tubular Columns Under Non-uniform Heating** ..... 363  
 L. Lama, T. Gernay, and H. T. Thai

**Corrosion Characteristics of Q370 qENH Weathering Bridge Steel** ..... 375  
 Zhihui Zhu and Qianshuo Feng

**Evaluating the Performance of Category D Timber Connections** ..... 387  
 A. Amirsardari, L. Pham, J. Lee, and Emad Gad

**Behaviour of Cold-Formed Steel Batten Screw Connections Under Wind Loading at Sub-Zero Temperatures** ..... 397  
 G. Athmarajah and M. Mahendran

**Time-History Identification of Physical Properties of a Single-Storey Steel Frame Subjected to a Seismic Excitation** ..... 409  
 R. Enokida and K. Kajiwara

**Cold-formed Steel for Mid-rise Construction—Conceptual Design** ..... 421  
 K. Watson, A. Amirsardari, and L. Pham

**Effect of Corrosion Pit Growth on the Ultimate Strength of Weld Joints** ..... 431  
 H. Humphrey and R. E. Melchers

**Damping and Mechanics of Structures**

**Seismic Vibration Control of Fluid Storage Tanks Using Magnetorheological Dampers** ..... 445  
 Seyed Ehsan Aghakouchaki Hosseini and Sherif Beskhyroun

**Numerical Simulation and Shake Table Test on the Seismic Performance of the Combined Viscous-Steel Damping System** ..... 457  
 Shangtao Hu, Menggang Yang, Dongliang Meng, and Nawawi Chow

**How to Implement Bell-Shaped Damping Model?** ..... 471  
 C.-L. Lee

**Effect of Water Pressure Increase Speeds in Mortar on Mechanical Behavior Under High Water Pressure** ..... 481  
 R. Fujikawa, H. Iwamoto, K. Nakayama, and M. Iwanami

**Comparison of Damping Ratio Identification Methods for Buildings Using Seismic Responses** ..... 491  
 Y. Zheng, C.-L. Lee, and R. Shen

**The Mechanics of Reliability Performance Evaluation** ..... 501  
 L. Pham, E. Gad, A. Amirsardari, J. Lee, and J. Wilson

**Data-Driven Modeling of General Damping Systems by *k*-Means Clustering and Two-Stage Regression** ..... 513  
 J. Guo and K. Ikago

**Comparison Between the Cyclic Response of Viscoelastic Dampers Made of Natural and Silicon Rubber** ..... 523  
 A. Alhasan, S. C. Alih, and M. Vafaei

**Numerical Methods and Health Monitoring**

**Toward Resilience-Based Design (RBD): Lessons Learned from Past Earthquakes in Japan** ..... 535  
 I. Takewaki and K. Shintani

**A More Realistic Load for Prediction of the Structural Integrity** ..... 563  
 R. Xue and H. M. Osinga

**Study on the Delamination Damage Prediction of Wind Turbine Blade Spar Cap Based on Morphology Feature Recognition** ..... 577  
 H. Li, X. L. Lu, B. Zhou, W. Xin, and X. Y. Zhang

**Machine-Learning Based Prediction Model for Identifying Torsion-Induced Seismic Response Amplification in Plan-Asymmetric Buildings** ..... 593  
 Yao Hu, Elisa Lumantarna, Nelson Lam, and Hing-Ho Tsang

**Comparative Analysis of Random Forest and Support Vector Machine for a Bridge Damage Detection** ..... 605  
 A. Yaghoobzadefard, M. Sofi, E. Lumantarna, and N. Herath

**Simulative Investigation of Wave Propagation in a Thin Plate Using Abaqus for the Application of Coda Wave Interferometry in Order to Detect Progressive Material Damage** ..... 617  
 Paul G. Bolz

**Earthquake Response of SDOF Bilinear Hysteretic System Under Forward-Directivity Input Modeled by Triple Impulse** ..... 629  
 K. Kojima and I. Takewaki

**Development of New Seismic Testing Program for Suspended Ceilings** ..... 641  
 C. Flude, D. Lau, and J. Erochko

**Uplift-Restraint All-Cover Conical Friction Isolation System: Numerical Study** ..... 653  
W. Xiong

**Navigating the Complexity of Off-River Gravity Dam Monitoring: Insights from Finite Element Modelling** ..... 663  
B. Cuning, I. Chaves, L. Pilgrim, and R. Petersen

**Nonlinear Numerical Simulation Method for Combined Supporting Structures of Steel Sets and Shotcrete in Tunnels** ..... 675  
C. Kong and M. Xiao

**Seismic-Induced Damage Localization Through Neural Networks and Clustering Method** ..... 687  
M. Vafaei, S. C Alih, and S. Umar

**Rocking Structures and Soil-Structure Interaction**

**Influence of Frequency Ratio and Support Flexibility on the Seismic Response of Two-Segment Rockable Bridges** ..... 699  
Z. Yang, M. You, K. Zhang, and N. Chow

**Consequence of Slenderness for the Seismic Response of Rockable Bridges** ..... 709  
Z. Yang, R. Xue, M. You, K. Zhang, and N. Chow

**The Interrelation Between the Dynamic Properties of Rockable Bridges and Excitations** ..... 719  
R. Xue, Z. Yang, D. Meng, K. Zhang, M. You, and N. Chow

**Influence of Excitation Angle and Soil-Structure Interaction on the Seismic Response of Bridges** ..... 731  
K. Zhang, R. Xue, M. You, Z. Yang, and N. Chow

**The Effect of Soil Properties on the Dynamic Response of Closely Adjacent Structures** ..... 739  
M. You, G. Barrios, R. Xue, K. Zhang, Z. Yang, and N. Chow

**Rocking Amplification and Vector-Valued Intensity Measures** ..... 751  
A. I. Giouvanidis and E. G. Dimitrakopoulos

**Seismic Rocking Response Classification Through the Lens of a Machine Learning Methodology** ..... 763  
S. K. W. Chu, A. I. Giouvanidis, C. N. Loong, and E. G. Dimitrakopoulos

**Experimental Investigation into Seismic Response of Superelastic Tendon Restrained Rocking Structures** ..... 773  
Sheng Li, Hing-Ho Tsang, and Nelson Lam

<b>Exploring Advanced Soil Constitutive Models for Simulation of Flexible Barrier Piles Under Vehicle Impact</b> .....	783
F. Safari Honar, N. Yousefpour, N. T. K. Lam, and J. S. Perera	
<b>Structural Dynamics and Blast Loading</b>	
<b>Analytical Study of Seismic Demand and Fragility of Piping Systems in the Reticulated Shell Structures</b> .....	797
Fengze Li, Xudong Zhi, Enchun Zhu, Duozhi Wang, and Rong Zhang	
<b>Shake Table Experiment on Girder-Abutment Pounding Effect and Its Numerical Simulation</b> .....	809
M. Amin and Y. Kajita	
<b>Numerical Simulation of Impact Effect for Damage Assessment of Highway Bridge Abutments</b> .....	821
M. Amin and Y. Kajita	
<b>Static and Dynamic Field Testing of 40 m I-girder Bridge in Teluk Lamong Area</b> .....	835
B. Piscesa, I. Komara, M. Irmawan, W. Sutrisno, A. N. Refani, and H. Alrasyid	
<b>The Dynamic Behaviour of Precast Socket Bridge Piers Under Impact at the Pier Top</b> .....	845
Dongliang Meng, Renkang Hu, Menggang Yang, Shangtao Hu, Xuhui He, and Nawawi Chow	
<b>A Study on Different Structural Systems Using Response Spectrum Analysis</b> .....	859
M. Z. Patowary, M. Ivtekar, M. S. A. Zafar, I. T. Hossain, and M. R. Raju	
<b>Crack Intensification on Brittle Materials Under Impact Loading Based on Peridynamics</b> .....	869
Songbo Li, Miao Li, Zhiliang Wang, and Linfang Shen	
<b>Response of Structure with Air-Backed and Water-Backed Medium Subjected to Underwater Shock Pulse</b> .....	883
A. Deivanayagam and A. Ponnalagu	
<b>A Simulation Method for Offshore Inclined Cylinder Under the Coupling Loads of Wind, Wave and Earthquake</b> .....	893
H. Lin, H. Luan, H. Karampour, S. Zhang, L. Yang, P. Han, H. Xu, and L. Wei	
<b>Investigation on the Influence of Structural Measures on Seismic Resilience of Multi-storey Masonry Structures</b> .....	907
H. Zhang, Y. X. Huang, and H. N. Li	



**Blast-Induced Response of Closed Cellular Rigid Polyurethane Foam** ..... 919  
K. Kaviarasu and P. Alagappan

**Prediction of the Nonlinear Capacities of RC Buildings Including the Effect of Interactions Between Structural Elements** ..... 929  
P. Khatiwada, E. Lumantarna, and N. Lam

**Dynamic Impact Performance of Solid Aluminium Cladding Panels Subjected to the Impact of Timber Projectile** ..... 939  
Iqrar Hussain, Sanam Aghdamy, and Shanmuganathan Gunalan

**A Review of Advances in Research on the Seismic Vulnerability of Bridge Structures** ..... 949  
L. M. Yu, B. Yan, X. R. L. Lou, H. X. Fu, and J. H. Tian

**Influence of Different Structural Systems on Rail-Suspension Bridge Interaction** ..... 961  
X. R. L. Lou, B. Yan, R. Gan, and L. M. Yu

# **Composite Structures, Concrete, and Pavements**

# Spatial Correlation of Flexural Tensile Bond Strength in Unreinforced Masonry Walls



L. J. Gooch, M. J. Masia, M. G. Stewart, and C. Collard

**Abstract** The flexural tensile bond strength of the unit-mortar interface is an important material property in defining the load-carrying capacity of unreinforced masonry (URM) walls. This property often governs the response of URM walls subject to in-plane and out-of-plane flexure. Masonry is an inherently variability building material, with properties such as the flexural tensile bond strength having been observed to vary considerably when comparing adjacent mortar joints. This spatial variability influences the performance of URM structures and is an important consideration when performing stochastic assessments of masonry behaviour. This study describes an experimental investigation in which an URM wall was sequentially deconstructed utilising a bond wrench, and the bending stress to failure of each individual mortar joint was recorded. The bending capacity of each of these joints allows for an assessment of the spatial correlation of joint strengths within a masonry wall. Furthermore, 15 additional mortar joints, constructed in piers under identical conditions, and using the same unit type and the same mortar batch, as the examined wall, have been tested using a bond wrench. These supplemental tests are a standard form of estimating the strength of mortar joints within an URM structure. Examination of these specimens, therefore, provides insight into how accurately such tests estimate the true strength of joints within a wall.

**Keywords** Unreinforced masonry · Spatial variability · Correlation · Flexural tensile strength · Statistics · Materials

---

L. J. Gooch (✉) · M. J. Masia  
Centre for Infrastructure Performance and Reliability, The University of Newcastle,  
Callaghan 2308, Australia  
e-mail: [lewis.gooch@newcastle.edu.au](mailto:lewis.gooch@newcastle.edu.au)

M. J. Masia  
e-mail: [mark.masia@newcastle.edu.au](mailto:mark.masia@newcastle.edu.au)

L. J. Gooch · M. G. Stewart  
Centre for Built Infrastructure Resilience, University of Technology Sydney, Ultimo 2007,  
Australia  
e-mail: [mark.stewart@uts.edu.au](mailto:mark.stewart@uts.edu.au)

C. Collard  
Civil Engineering, ADW Johnson, Warners Bay 2282, Australia  
e-mail: [corben.collard@uon.edu.au](mailto:corben.collard@uon.edu.au)

© The Author(s), under exclusive license to Springer Nature Singapore Pte Ltd. 2024  
N. Chow and C. Zhang (eds.), *Proceedings of the 26th Australasian Conference  
on the Mechanics of Structures and Materials*, Lecture Notes in Civil Engineering 513,  
[https://doi.org/10.1007/978-981-97-3397-2\\_1](https://doi.org/10.1007/978-981-97-3397-2_1)

# 1 Introduction

Recent studies into the variability and structural reliability of unreinforced masonry (URM) walls have utilised computational methods of estimating load–displacement behaviour [5, 9]. A key component of these methods is the accurate representation of material properties within a modelled masonry structure. These values are commonly sourced from experimental testing, standardised or recommended values such as those in AS 3700 [12] and NZSEE [10], or from extensive published databases [6, 8]. However, in order to produce a more accurate computational representation of an URM wall, consideration of how these properties varying throughout a structure should be made.

Previous studies by Heffler et al. [4] and Corrêa et al. [1] address the spatial variability of masonry flexural bond strength through the quantification of a correlation coefficient,  $\rho_k$ . This descriptor quantifies the degree of dependence that the flexural bond strength of any given mortar joint has from other joints within a course of a masonry wall. For example, a correlation coefficient equal to 1.0 for the bond strength of adjacent mortar joints implies that a full correlation between these distinct interfaces is present, and the determination of the strength of any one joint informs the strengths of all adjacent joints. In contrast, a coefficient equal to 0 implies that no correlation is present, and that no information is gained about adjacent elements within a wall. Finally, a value of -1.0 indicates that a full negative correlation exists. This results in alternating joint strengths of above then below average (or vice versa), with the changes in strength maintaining a constant value. This concept is presented in Fig. 1.




Fig. 1 Indicative flexural bond strengths for various correlation coefficients

The current study begins to expand upon the results of these previous investigations. A wall specimen constructed after those by Gooch et al. [3] was sequentially deconstructed using the standardised bond wrench test presented in AS 3700 [12]. Furthermore, as in the investigation by Corrêa et al. [1], several supplemental masonry piers were tested in the same manner. These additional tests, constructed using the same masonry units, mortar batch and bricklayer, facilitate research into the reliability of material characterisation tests.

## 2 Description of Experimental Testing

This initial study focuses on the results associated with a single URM wall specimen. This wall was constructed in a running bond pattern, with eight standard Australian masonry units ( $230 \text{ mm} \times 110 \text{ mm} \times 76 \text{ mm}$ ) per course and a total of fourteen courses. Mortar joint widths of approximately 10 mm were adopted, and a single wythe of units was used. The overall geometry of this wall specimen, as well as the supplemental prisms discussed in Sect. 3.2, are presented in Fig. 2.

Both the wall specimen and supplemental masonry prisms were constructed by the same individual bricklayer on the same day. A standard 1:1:6 (cement: lime: sand by volume) mortar mix was adopted, as specified in AS 3700 [12], and the same batch was utilised in the construction of all specimens. Finally, all specimens were aged for an extensive period of 222 days. This protracted age time is significantly longer than the 7 days required by AS 3700 [12], or the 28 days common to masonry research. However, the longer curing period effectively eliminates the potential for variability induced from inconsistent curing, both throughout the wall specimen, and between the wall and prisms.



**Fig. 2** Wall specimen and prism geometries (all dimensions are presented in mm)

## 2.1 Bond Wrench Test Method

The estimation of the flexural tensile bond strength of each mortar joint was achieved through the application of the bond wrench test. This test involves attaching a clamp to an individual masonry unit and applying a bending moment to its bed joint through the steady application of force. While the testing of masonry prisms can be readily undertaken as per the arrangement shown in Fig. 3, in order to test bed joints within the wall specimen, the vertical perpend joints were first removed. This was achieved using a sharp handsaw. A manual saw was utilised rather to minimise the vibrations of and potential damage to adjacent joints that could arise through the use of power tools.

The omission of perpend joints from this study was a result of two considerations. Firstly, flexural tensile testing of perpend joints is difficult, and their strengths are typically less critical to the overall strength of a given URM wall (see [7, 10, 12]). Secondly, it may be expected that some correlation exists between adjacent bed joints within an URM wall. These joints are typically laid in a sequence, with a bricklayer first placing a run of mortar capable of seating several masonry units. Perpend joints, however, are placed sequentially. Mortar is applied individually to one header face of a masonry unit before it is placed onto the mortar bed and tapped into position. As such, it is expected that a much weaker relationship between adjacent perpend joints exists. Hence no consideration of perpend joint strengths have been made in this study, nor that of Heffler et al. [4] and Corrêa et al. [1].

The flexural tensile bond strength  $f_{sp}$  of a given joint can be estimated from Eq. (1). In this study a bond wrench with a mass  $m_1$  of 8.2 kg, an arm length  $d_2$  of 1300 mm, and a distance to the centre-of-mass  $d_1$  of 389 mm. The mass of each unit  $m_3$  was found to be approximately 2.9 kg, or 1.5 kg in the case of the half bricks at each end of every alternate course.

$$f_{sp} = \left( \frac{M_{sp}}{Z_d} \right) - \left( \frac{F_{sp}}{A_d} \right) \quad (1)$$




Fig. 3 Schematic and test set-up of the bond wrench test [12]

where  $M_{sp}$  is the applied bending moment about the centroid of the bedded area of the examined joint, estimated as per Eq. (2), and  $Z_d$  is the section modulus of the bedded area about the axis about which the bending moment is applied. Similarly,  $F_{sp}$  is the applied compressive force, calculated via Eq. (3), and  $A_d$  is the total bedded area.

$$M_{sp} = 9.81m_2 \cdot \left( d_2 - \frac{t_u}{2} \right) + 9.81m_1 \cdot \left( d_1 - \frac{t_u}{2} \right) \quad (2)$$

$$F_{sp} = 9.81 \cdot (m_1 + m_2 + m_3) \quad (3)$$

Load applied to the specimen  $m_2$  is applied by the individual performing the test either through their own body mass or through the application of weights. This force must be applied at an even rate to avoid dynamic load effects until failure of the joint is achieved. A constant unit thickness  $t_u$  of 110 mm was present in all specimens tested in this study.


### 3 Experimental Results

The estimated flexural tensile bond strengths of each bed joint within the wall specimen are presented in Fig. 4. An average strength of 0.48 MPa with a coefficient of variation (COV) of 0.30 was estimated. These values are consistent with the expected bond strengths of URM walls, such as those presented in McNeilly et al. [8]. In addition, the average strengths of each course within the wall are presented in Fig. 5. These values, ranging from 0.33 MPa to 0.63 MPa, are important to the determination of the spatial correlation coefficient (see Eq. 4). The observed spread of 0.30 MPa between these mean values may be significant (approximately 63% of the overall mean) but is not unexpected in the highly variable masonry unit-mortar interface.

In Fig. 4 it may be observed that two values have been omitted (the final tested units in courses 4 and 5). In this case, during the testing of the final unit of course 5, both of these bed joints, as well as the final perpend joint of course 4, failed. The subsequently recorded force at failure was disregarded, as this test result was deemed invalid. In addition, it may be observed that no flexural bond strength values are presented for the bottom course of units in Fig. 4. As these units were bonded to a reinforced concrete beam, rather than to another course of units, the resultant values of bond strength are expected to be inconsistent with the others presented in this study. As such, these values were also disregarded.

0.28	0.31	0.30	0.34	0.24	0.29	0.33	0.52	
0.56	0.35	0.28	0.46	0.39	0.40	0.36	0.36	0.48
0.38	0.32	0.61	0.69	0.53	0.31	0.36	0.35	
0.41	0.43	0.36	0.40	0.38	0.34	0.20	0.32	0.46
0.50	0.51	0.36	0.72	0.26	0.42	0.55	0.41	
0.35	0.56	0.58	0.42	0.58	0.33	0.43	0.60	0.56
0.54	0.45	0.64	0.84	0.55	0.27	0.36	0.53	
0.62	0.64	0.65	0.38	0.64	0.54	0.38	0.45	0.66
0.41	0.39	0.45	0.44	0.68	0.37	0.50	N/A	
0.63	0.68	0.43	0.56	0.53	0.47	0.47	0.21	N/A
0.59	0.45	0.65	0.58	0.60	0.48	0.62	0.64	
0.95	0.52	0.62	0.53	0.55	0.56	0.53	0.45	0.97
0.72	0.28	0.39	0.45	0.55	0.48	0.56	0.73	
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

**Fig. 4** Flexural tensile bond strengths estimated from wall specimen bed joints (all values are in MPa)



**Fig. 5** Average flexural tensile bond strength of each course within wall specimen

### 3.1 Spatial Correlation of Adjacent Joint Strengths

The spatial correlation of flexural bond strengths was quantified using the autocorrelation function,  $\rho_k$ . This function is calculated for a “lag”  $k$  representing the space




between data points (in this case the bed joints within a course). There are a number of estimates for the autocorrelation function, however, the bias estimate adopted in this study, is the most popular variance estimator and produces a smaller error than an unbiased case ([4] after, [2, 11]).

For a sample size  $N$ , the  $k^{\text{th}}$  autocorrelation function may be estimated from Eq. (4). Where  $z_i$  refers to the flexural tensile bond strength of the  $i^{\text{th}}$  joint within a course, and  $\mu_z$  is the mean bond strength of that course.

$$\rho_k = \frac{\sum_{i=1}^{N-k} (z_i - \mu_z)(z_{i+k} - \mu_z)}{\sqrt{\sum_{i=1}^{N-k} (z_i - \mu_z)^2 \sum_{i=1}^{N-k} (z_{i+k} - \mu_z)^2}} \tag{4}$$

In addition to Eq. (4), Priestley [11] and Fenton [2] suggest that values of  $\rho_k$  that fall within the bounds of  $\pm 2\sqrt{1/N}$  are not significantly distinct from statistically independent variables (i.e.:  $\rho_k = 0$ ). In the case of the current study, this limit is equal to between 0.67 and 0.76 depending on the number of data points in the course under consideration. This range is quite large due to the relatively small number of units in each course, however, conclusions regarding the strength of the observed correlations may still be drawn despite this limitation.

The resultant autocorrelation function values, presented in Fig. 6, indicate that a weak correlation exists between adjacent bed joints ( $k = 1$ ). The autocorrelation function value at this point is highly variable, with values of  $\rho_{k=1}$  ranging from 0.70 to -0.61. While this result is not inconsistent with the findings of Heffler et al. [4] who observed values of  $\rho_{k=1}$  between approximately 0.9 and -0.6, it reinforces the conclusion of a weak and variable degree of correlation between adjacent bed joint strengths presented in this previous investigation.



**Fig. 6** Autocorrelation function values for each course in the wall specimen

As may be expected, the strength of this correlation diminishes at higher lag values. Despite this general trend, seen in the results of this study and that of Heffler et al. [4], there are significant fluctuations in the estimated values of  $\rho_k$ . Several large spikes or dips in  $\rho_k$  may be observed in Fig. 6, indicative of a very strong or positive or negative correlation. There are two likely causes of this variability. Firstly, despite the standard construction practice of placing units sequentially within a course, the first or last units of a course are often placed first. This is done to ensure that the wall remains flush at each end. As a result, it may be expected that a higher degree of correlation exists between joint strengths at the highest values of  $k$ . In addition, it was observed upon the completion of construction that the overall quality of workmanship of this wall specimen was low. This may be seen in part from the partially filled joints shown in Fig. 3. This characteristic does not explicitly relate to the spatial correlation of joint strength but would act to exacerbate the inherent variability of these relationships.

### 3.2 Relationship Between Wall and Prism Joint Strengths

In addition to the assessment of the spatial correlation of adjacent joint strengths, the suitability of the supplemental prism joint tests to represent the average strength of joints within the wall specimen was examined. This was achieved through the application of a t-Test, as described by Corrêa et al. [1]. This test found that, at a 5% significance level, the null hypothesis was rejected, i.e.: the tested prism joints do not accurately represent the statistical properties of the wall joint bond strengths.

This result, presented in Table 1, is consistent with the findings of Corrêa et al. [1] who found that the majority of URM prisms tested were not suitably accurate representations of their corresponding wall specimens.

In addition to the t-Test results, a comparison of the estimated mean strengths provides insight into the suitability of the prism joint strengths to reflect the properties of the wall specimen. In the case of this study, the prism joints underestimate the wall strength by approximately 14%. These values are conformant to the strength compliance requirements of AS 3700 [12] and are on the conservative side of those results presented by Corrêa et al. [1], who observed differences between wall and prisms mean strengths ranging from 3 to 270%.

**Table 1** Summary of sample means, COVs and t-Test results

Wall			Prism			t-Test result (same population)
n	Mean (MPa)	COV	n	Mean (MPa)	COV	
108	0.48	0.30	15	0.41	0.25	No

## 4 Conclusions

The experimental results presented in this study indicate that a weak, but highly variable, correlation exists between the flexural tensile bond strengths of adjacent bed joints within an URM wall. The observed mean strength of 0.48 MPa with a COV of 0.30 are consistent with values observed in literature, and the determined values of an autocorrelation function are similar to those presented in previous, similar investigations. Further testing of larger, repeat wall specimens are planned in a future study, in order to refine the conclusions presented in this paper. The inclusion of a larger number of tested joints per course is expected to produce a more reliable estimate of the correlation coefficient presented in this study.

In addition to these findings, it was concluded through the application of a t-Test that the accompanying supplemental prism specimens constructed in concert with the tested URM wall did not accurately reflect the statistical properties of the wall. While a suitable estimation of the mean strength and COV was determined, as defined by the current Australian standard for masonry design, this observation suggests that care should be taken in the interpretation of similar characterisation tests.

## References

1. Corrêa MRS, Masia MJ, Stewart MG, Heffler LM (2012) An experimental and statistical analysis of the flexural bond strength of masonry walls. *Aust J Struct Eng* 13(2):139–148
2. Fenton GA (1999) Estimation for stochastic soil models. *J Geotech Geoenviron Eng* 470–485
3. Gooch LJ, Masia MJ, Stewart MG, Hossain MA (2023) A laboratory investigation into the variability of unreinforced masonry shear wall capacities. In: Omaha, Proceedings in the 14th North American Masonry conference
4. Heffler LM, Stewart MG, Masia MJ, Corrêa MRS (2008) Statistical analysis and spatial correlation of flexural bond strength for masonry. *Masonry Int* 21(2):59–70
5. Isfeld AC, Stewart MG, Masia MJ (2023) Structural reliability and partial safety factor assessment of unreinforced masonry in vertical bending. *Aust J Struct Eng*
6. Lawrence SJ (1983) Behaviour of brick masonry walls under lateral loading. University of New South Wales, Sydney
7. Magenes G, Calvi GM (1997) In-plane seismic response of brick masonry walls. *Earthq Eng Struct Dynam* 26:1091–1112
8. McNeilly TN, Scrivener CJ, Lawrence S, Zsembery S (1996) A site survey of masonry bond strength. In: Australian Civil/Structural Engineering Transactions, CE38(2,3&4), pp 103–109
9. Muhit IB, Masia MJ, Stewart MG, Isfeld AC (2022) Spatial variability and stochastic finite element model of unreinforced masonry veneer wall system under out-of-plane loading. *Eng Struct* 267
10. NZSEE (2017) The seismic assessment of existing buildings. Wellington: New Zealand Society for Earthquake Engineering, Structural Engineering Society, and NZ Geotechnical Society
11. Priestley MB (1981) Spectral analysis and time series. Academic Press, London
12. Standards Australia (2018) AS3700: Masonry structures. Standards Australia, Sydney

# Seismic Assessment and Upgrade of Concrete Wharf Structure



F. Yu, X. Qin, and C. Wicaksana

**Abstract** The KiwiRail's Inter-island Resilient Connection (iReX) program aims to increase the capacity and efficiency of ferry between the north island and the south island of New Zealand. It introduces two new ferries and terminals at Kaiwharawhara in Wellington and Waitohi Picton. The terminal upgrade for the Picton port involving the construction of a new wharf and the upgrade of the existing wharfs. This paper presents the upgrade work for the largest wharf at the current Picton terminal. The upgrade involves partial demolition and replacement of the wharf deck. New pile supports will also be constructed for the new decks. A mechanical hinge bridge and automatic mooring unit will be installed on these new decks, enabling the operation of new ferries with various sizes. A seismic analysis was conducted to evaluate the seismic performance of the wharf before and after the upgrade work. It was acknowledged that the existing pile might fail in tension or compression due to the additional seismic force. Therefore, the design of the new members allowed the potential uplift movement of the existing piles such that all tension demand will be resisted by the new piles. A finite element model was constructed. Tensionless springs were used during the modelling of the existing piles. The seismic behaviour of the wharf and the evaluation of the wharf performance will be presented.

**Keywords** Seismic assessment · Wharf structures · Pile uplift

---

F. Yu · X. Qin (✉) · C. Wicaksana  
Arup Limited, 1010 Auckland, New Zealand  
e-mail: [Gary.qin@arup.com](mailto:Gary.qin@arup.com)

© The Author(s), under exclusive license to Springer Nature Singapore Pte Ltd. 2024  
N. Chow and C. Zhang (eds.), *Proceedings of the 26th Australasian Conference on the Mechanics of Structures and Materials*, Lecture Notes in Civil Engineering 513, [https://doi.org/10.1007/978-981-97-3397-2\\_2](https://doi.org/10.1007/978-981-97-3397-2_2)

# 1 Introduction

## 1.1 Background

Picton Interislander ferry terminal consist of 2 berths, Berth no 1 and Berth no 2. Currently Berth No 2 can only be used by Aratere, while the other three Interislander ferries, Kaitaki, Kaiarahi and Valentine are using Berth no 1. To facilitate the construction of the new berthing and terminal facilities, current berth No 1 needs to be demolished. To maintain ferry operations during the construction of the new berth, existing Berth No 2 required to be modified to enable all four ferries to use Berth no 2. Picton Enabling Work focused on the design of temporary structure and modifications of the existing structures to enable the existing Berth No 2 to be used for berthing for all four Interislander ferries.

There are several new structures proposed to be constructed as part of the Berth 2 upgrade, which includes a new Hinge Bridge, new foundation structures to support the new Automated Mooring Units (AMU), and a new foundation structure to support the existing short-arm end fender. Figure 1 shows a plan view of those proposed structures and their relative position to the long wharf. To allow these new structures to be constructed, some part of the existing structures required to be demolished.

The Hinge Bridge is a bascule bridge structure that enables vehicle loading and unloading of the K-class vessels (Kaiarahi and Kaitaki) and the Valentine onto the existing rail linkspan at Berth No 2. The bridge will be lifted in a stowed position when the Aratere is berthing and allow the vessel to access the existing rail linkspan within the nest, as in the original berthing configuration. The foundation of the hinge bridge is a portal frame structure with a concrete deck supported on 12 bore piles. The deck spans over two bays of the long arm wharf. The existing deck within the bays will be removed while the existing piles, kerbs and capping beams remain unchanged.




Fig. 1 Plan view of the new structures proposed (hinge bridge, AMUs and short arm fender)

Based on mooring analysis, two new AMUs are required to be installed at the end of the wharf. A new foundation structure at each location to seat the AMUs required. To facilitate the construction of the mooring unit foundations, the existing precast prestressed deck panel are to be removed and replaced with a new structure joining into the existing structure on either side.

A number of finite element analysis software, including SAP 2000, have been used to carry out static analysis of the structure based on the loadings applied and the non-linear geotechnical springs defined. However, the modelling process requires a certain degree of knowledge in the integration of structural and geotechnical engineering field, as well as careful calibration of multiple parameters to obtain a more realistic results. This paper discussed how a more accurate estimate of the actual wharf structure behaviour and demands were obtained. Details methodology employed in the analysis were shared including the findings which may be referenced for any similar future projects.

## ***1.2 Geotechnical Analysis***

Prior to the structural analysis and design being undertaken, site-specific geotechnical investigations were carried out by external parties including borehole/CPT tests, lab analysis and geophysical investigation using Multi-channel Analysis of Surface Waves (MASW).

The majority of boreholes were drilled at the neighbouring wharves' locations. The ground conditions were inferred from those boreholes. The marine sediments were mostly comprised of soft silts and loose sands. Below the sediments were medium dense gravels and sandy gravels of alluvial outwash embedded in a clay/silt matrix. These materials generally become denser with the depth. The bedrock is anticipated at approximately  $-30.0$  m RL at the coastline and indicatively dips down towards the northeast.

## **2 Methodology**

### ***2.1 Modelling***

During the optioneering stage, an Oasys GSA model was established to allow an exploration of the structural geometry and adaption to the client demand. Later in the review stage, SAP2000 was used for nonlinear seismic analysis.

The structural members (such as beams, pile caps and piles) are modelled using beam elements. A grillage model was constructed for the concrete deck of the wharf. Reinforced concrete members are modelled with linear elastic material properties