

IoT SIGNAL DETECTION



RUI HAN • JINGJING WANG
LIN BAI • JIANWEI LIU

 **IEEE Press**

WILEY

IoT Signal Detection

IEEE Press
445 Hoes Lane
Piscataway, NJ 08854

IEEE Press Editorial Board
Sarah Spurgeon, *Editor-in-Chief*

Moeness Amin
Jón Atli Benediktsson
Adam Drobot
James Duncan

Ekram Hossain
Brian Johnson
Hai Li
James Lyke
Joydeep Mitra

Desineni Subbaram Naidu
Tony Q. S. Quek
Behzad Razavi
Thomas Robertazzi
Diomidis Spinellis

IoT Signal Detection

Rui Han

Beihang University

Jingjing Wang

Beihang University

Lin Bai

Beihang University

Jianwei Liu

Beihang University

 **IEEE Press**

WILEY

Copyright © 2024 by The Institute of Electrical and Electronics Engineers, Inc. All rights reserved.

Published by John Wiley & Sons, Inc., Hoboken, New Jersey.

Published simultaneously in Canada.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, scanning, or otherwise, except as permitted under Section 107 or 108 of the 1976 United States Copyright Act, without either the prior written permission of the Publisher, or authorization through payment of the appropriate per-copy fee to the Copyright Clearance Center, Inc., 222 Rosewood Drive, Danvers, MA 01923, (978) 750-8400, fax (978) 750-4470, or on the web at www.copyright.com. Requests to the Publisher for permission should be addressed to the Permissions Department, John Wiley & Sons, Inc., 111 River Street, Hoboken, NJ 07030, (201) 748-6011, fax (201) 748-6008, or online at <http://www.wiley.com/go/permission>.

Trademarks: Wiley and the Wiley logo are trademarks or registered trademarks of John Wiley & Sons, Inc. and/or its affiliates in the United States and other countries and may not be used without written permission. All other trademarks are the property of their respective owners. John Wiley & Sons, Inc. is not associated with any product or vendor mentioned in this book.

Limit of Liability/Disclaimer of Warranty: While the publisher and author have used their best efforts in preparing this book, they make no representations or warranties with respect to the accuracy or completeness of the contents of this book and specifically disclaim any implied warranties of merchantability or fitness for a particular purpose. No warranty may be created or extended by sales representatives or written sales materials. The advice and strategies contained herein may not be suitable for your situation. You should consult with a professional where appropriate. Further, readers should be aware that websites listed in this work may have changed or disappeared between when this work was written and when it is read. Neither the publisher nor authors shall be liable for any loss of profit or any other commercial damages, including but not limited to special, incidental, consequential, or other damages.

For general information on our other products and services or for technical support, please contact our Customer Care Department within the United States at (800) 762-2974, outside the United States at (317) 572-3993 or fax (317) 572-4002.

Wiley also publishes its books in a variety of electronic formats. Some content that appears in print may not be available in electronic formats. For more information about Wiley products, visit our web site at www.wiley.com.

Library of Congress Cataloging-in-Publication Data applied for:

Hardback ISBN: 9781394183081

Cover Design: Wiley

Cover Image: © Yuichiro Chino/Getty Images

Set in 9.5/12.5pt STIXTwoText by Straive, Chennai, India

To our families and friends

Contents

| | |
|---------------------------|--------------|
| List of Figures | <i>xi</i> |
| List of Algorithms | <i>xvii</i> |
| About the Authors | <i>xix</i> |
| Foreword | <i>xxi</i> |
| Preface | <i>xxiii</i> |
| Acknowledgements | <i>xxv</i> |
| Acronyms | <i>xxvii</i> |

| | | |
|----------|---|-----------|
| 1 | Introduction | <i>1</i> |
| 1.1 | IoT in 5G | <i>1</i> |
| 1.1.1 | What Is IoT | <i>1</i> |
| 1.1.2 | Applications of IoT | <i>2</i> |
| 1.1.3 | Future of IoT | <i>3</i> |
| 1.2 | IoT Networks | <i>4</i> |
| 1.3 | Characteristics of IoT Signals | <i>6</i> |
| 1.4 | Outline | <i>8</i> |
| 2 | Background of IoT Signal Detection | <i>11</i> |
| 2.1 | Random Access | <i>11</i> |
| 2.1.1 | Grant-based Random Access | <i>11</i> |
| 2.1.2 | Grant-free Random Access | <i>14</i> |
| 2.2 | Signal Detection Methods | <i>16</i> |
| 2.2.1 | System Model | <i>17</i> |
| 2.2.2 | ML Detection | <i>18</i> |
| 2.2.3 | ZF Detection | <i>22</i> |
| 2.2.4 | MMSE Detection | <i>25</i> |
| 2.2.5 | MCMC Detection | <i>28</i> |

| | | |
|----------|---|------------|
| 2.2.6 | VI Detection | 31 |
| 2.2.7 | CS Detection | 34 |
| 2.3 | Conclusion and Remarks | 38 |
| 3 | Sparse Signal Detection for Multiple Access | 39 |
| 3.1 | System Model | 39 |
| 3.2 | Sparse Signal Detection | 41 |
| 3.2.1 | Tree Search-based Approach | 41 |
| 3.2.2 | VI Detection Algorithm | 44 |
| 3.3 | Performance Analysis | 48 |
| 3.3.1 | Complexity Analysis | 48 |
| 3.3.2 | VI Detection Performance Analysis | 49 |
| 3.4 | Simulation Results | 55 |
| 3.5 | Conclusion and Remarks | 61 |
| 4 | Collided Signal Detection for Multiple Access | 63 |
| 4.1 | System Model | 63 |
| 4.2 | Automatic Modulation Classification-based Detection | 66 |
| 4.2.1 | Preamble Sequence Detection | 66 |
| 4.2.2 | HOCs-based AMC Approach for Collision Recognition | 68 |
| 4.2.3 | Data Decoding with SIC | 69 |
| 4.3 | Performance Analysis | 71 |
| 4.4 | Simulation Results | 78 |
| 4.5 | Conclusion and Remarks | 86 |
| 5 | Multiple Delay Estimation for Collided Signals | 89 |
| 5.1 | System Model | 89 |
| 5.2 | Multiple Delay Estimation | 92 |
| 5.2.1 | ML Detection Algorithm | 92 |
| 5.2.2 | CAVI Detection Algorithm | 95 |
| 5.2.3 | MCMC Detection Algorithm | 99 |
| 5.3 | Signal Number Estimation and Channel Estimation | 100 |
| 5.4 | Simulation Results | 102 |
| 5.4.1 | CAVI Simulation Results | 102 |
| 5.4.2 | MCMC Simulation Results | 109 |
| 5.5 | Conclusion and Remarks | 115 |
| 6 | Detection and Division for Backscatter Signals | 117 |
| 6.1 | System Model | 117 |
| 6.2 | Central Limit Theorem-based Signal Detection | 122 |
| 6.2.1 | Activity Detection Algorithm | 123 |

| | | |
|----------|--|------------|
| 6.2.2 | Signal Detection Algorithm | 126 |
| 6.2.3 | Performance Analysis | 127 |
| 6.3 | Simulation Results | 128 |
| 6.4 | Conclusion and Remarks | 134 |
| 7 | Analysis and Optimization for NOMA Signals | 137 |
| 7.1 | System Model | 137 |
| 7.2 | Throughput and Power Consumption Analysis | 139 |
| 7.2.1 | Throughput Analysis | 139 |
| 7.2.2 | Power Consumption Analysis | 140 |
| 7.3 | Energy Efficiency Performance Optimization | 141 |
| 7.4 | Simulation Results | 145 |
| 7.5 | Conclusion and Remarks | 148 |
| 8 | Signal Design for Multicluster Coordination | 149 |
| 8.1 | Multi-cluster Coordination in IoT | 149 |
| 8.2 | Multi-cluster Coordination with NOMA | 152 |
| 8.2.1 | Multi-cluster Coordination NOMA Design | 152 |
| 8.2.2 | Multi-cluster Coordinated NOMA Resource Allocation | 153 |
| 8.3 | CI-aided Multi-cluster Coordination with Interference Management | 156 |
| 8.3.1 | CI Signal Design | 156 |
| 8.3.2 | CI Design for Multi-cluster Coordination | 158 |
| 8.4 | Future Works | 161 |
| 8.5 | Conclusion and Remarks | 162 |
| 9 | Conclusion of the Book | 163 |
| | References | 165 |
| | Index | 175 |

List of Figures

- Figure 1.1** Architecture of IoT 5
- Figure 2.1** The contention-based RA 12
- Figure 2.2** The contention-free RA 12
- Figure 2.3** The grant-free RA 14
- Figure 2.4** The compressed sensing 15
- Figure 2.5** A $M \times N$ MIMO system 17
- Figure 2.6** The constellation of 64-QAM system with ML 21
- Figure 2.7** BER of ML detector in 4-QAM 2×2 MIMO system 22
- Figure 2.8** The constellation of 64-QAM system with ZF 24
- Figure 2.9** BER of ZF detector in 4-QAM 2×2 MIMO system 25
- Figure 2.10** The process of MMSE detection 25
- Figure 2.11** The constellation of 64-QAM system with MMSE 27
- Figure 2.12** BER of MMSE detector in 4-QAM system 28
- Figure 2.13** Comparison between ZF detector and MCMC detector when SNR = 5 dB 31
- Figure 2.14** BER of MCMC detector in 4-QAM 2×2 MIMO system 32
- Figure 2.15** BER of VI detection in 2×2 MIMO system 35
- Figure 2.16** The process of compressive sensing 35
- Figure 2.17** The reconstruction residual with different observation vector sizes 38
- Figure 3.1** Structure of NGMA systems 41
- Figure 3.2** The tree search for the presence of (sparse) signals in a block 42
- Figure 3.3** Complexity ratio: (a) as a function of D with $p = 0.04$; (b) as a function of p with $D = 8$ 49

- Figure 3.4** J -divergence and its approximation in Eq. (3.59) when $N = 128$, $M = 512$, and $\frac{E_s}{N_0} = 20$ dB: (a) as a function of D with $p = 0.04$; (b) as a function of p with $D = 8$ 55
- Figure 3.5** Performance of Stage 1 for various SNRs with $M = 512$, $(K, D) = (128, 4)$, $N = 128$, $p = 0.02$, and $p_\tau \in (\Pr(x_k = 1), 0.5)$: (a) the probabilities of FA and MD of the CAVI algorithm as functions of SNR; (b) J -divergence as a function of SNR 56
- Figure 3.6** Performance of Stage 1 for various values of p with $M = 512$, $(K, D) = (128, 4)$, $N = 128$, SNR = 16 dB, and $p_\tau \in (\Pr(x_k = 1), 0.5)$: (a) the probabilities of FA and MD of the CAVI algorithm as functions of p ; (b) J -divergence as a function of p 57
- Figure 3.7** Performance of Stage 1 for various values of D with $M = 512$, $N = 128$, $p = 0.02$, SNR = 16 dB, and $p_\tau \in (\Pr(x_k = 1), 0.5)$: (a) the probabilities of FA and MD of the CAVI algorithm as functions of D ; (b) J -divergence as a function of D 58
- Figure 3.8** Performance of Stage 1 for various values of N with $M = 512$, $(K, D) = (128, 4)$, $p = 0.02$, SNR = 16 dB, and $p_\tau \in (\Pr(x_k = 1), 0.5)$: (a) the probabilities of FA and MD of the CAVI algorithm as functions of N ; (b) J -divergence as a function of N 59
- Figure 3.9** Performance of TS approach and SS approach for various values of SNR with $M = 512$, $(K, D) = (128, 4)$, $N = 128$, $p = 0.02$, and $p_\tau = 0.5$ 59
- Figure 3.10** Performance of TS approach and SS approach for various values of p with $M = 512$, $(K, D) = (128, 4)$, $N = 128$, SNR = 16 dB, and $p_\tau = 0.5$ 60
- Figure 3.11** Performance of TS and SS approach for various values of N with $M = 512$, $(K, D) = (128, 4)$, SNR = 16 dB, $p = 0.02$, and $p_\tau = 0.5$ 61
- Figure 4.1** A typical uplink massive MIMO System 64
- Figure 4.2** Flowchart for classifying Cases 1–3 67
- Figure 4.3** Feature f versus OSNR with $M = 400$ and $\epsilon = 0.7$ 80
- Figure 4.4** Probability of correct estimation of $|\zeta_1|$ versus OSNR with $M = 400$ and $\epsilon = 0.7$ 80
- Figure 4.5** Probability $P_{\text{rc,CB}}(1)$ of resolving a two-UE collision versus OSNR with CB, various M , $\gamma_{\text{Th}} = 0$ dB, $\epsilon = 0.7$, and $K = 10$ 81
- Figure 4.6** Success probability $P_{2,\text{resolved}}$ versus the total number of UEs in the cell with CB, $\gamma_{\text{Th}} = 0$ dB, OSNR = 30 dB, and $\epsilon = 0.7$ 82

- Figure 4.7** Probability $P_{\text{rc,CB}}(1)$ of resolving a two-UE collision versus ϵ with CB, $M = 400$, OSNR = 80 dB, and $\gamma_{\text{Th}} = 0$ dB 83
- Figure 4.8** Probability $P_{\text{rc,ZF}}(1)$ of resolving a two-UE collision versus OSNR with ZFB, various M , $\gamma_{\text{Th}} = 0$ dB, $\epsilon = 0.7$, and $K = 10$ 84
- Figure 4.9** Success probability $P_{2,\text{resolved}}$ versus the total number of UEs in the cell with ZFB, $\gamma_{\text{Th}} = 0$ dB, OSNR = 30 dB, and $\epsilon = 0.7$ 84
- Figure 4.10** Probability of correctly estimating $|\mathcal{B}|$ via SORTE versus OSNR with ZFB, $M = 400$, $\epsilon = 0.7$, $K = 10$, and $D = 60$ 85
- Figure 4.11** Achievable probability of resolving a three-UE collision versus OSNR with $\epsilon = 0.7$ and $K = 10$ 86
- Figure 5.1** System model of two active devices with different RTDs 91
- Figure 5.2** Normalized frequencies of \hat{d}_k of the CAVI algorithm and the correlator-based detector when $K = 2$ ($d_1 = 5, d_2 = 8$), $L = 64$, $P = 16$, $Q = 3$, $M = 2$, SNR = 10 dB, and $(\mu, N_{\text{iter}}) = (1, 20)$ 103
- Figure 5.3** Performance of the CAVI algorithm to estimate RTDs for different numbers of iterations when $K = 2$, $L = 64$, $P = 16$, $Q = 3$, $M = 2$, SNR = 10 dB, and $\mu = 1$ 105
- Figure 5.4** Performance of the CAVI algorithm to estimate RTDs for different values of step size μ , when $K = 2$, $L = 64$, $P = 16$, $Q = 3$, $M = 2$, SNR = 10 dB, and $N_{\text{iter}} = 20$ 106
- Figure 5.5** Performance of the CAVI algorithm and the ML approach for different values of SNR when $K = 2$, $L = 64$, $P = 16$, $Q = 3$, $M = 2$, and $(\mu, N_{\text{iter}}) = (1, 20)$ 107
- Figure 5.6** Performance of the CAVI algorithm and the ML approach for different numbers of multipaths, Q , when $K = 2$, $L = 64$, $P = 16$, SNR = 10 dB, $M = 2$, and $(\mu, N_{\text{iter}}) = (1, 20)$ 108
- Figure 5.7** Performance of the CAVI algorithm and the ML approach for different numbers of antennas, M , when $K = 2$, $L = 64$, $P = 16$, SNR = 10 dB, $Q = 3$, and $(\mu, N_{\text{iter}}) = (1, 20)$ 109
- Figure 5.8** Conditional normalized MSE of the estimated composite CIR (without CIR overlapping) when $K = 2$, $L = 64$, $P = 16$, and $(\mu, N_{\text{iter}}) = (1, 20)$: (a) as a function of SNR with $Q = 3$ and $M = 2$; (b) as a function of Q with SNR = 10 dB and $M = 2$; (c) as a function of M with SNR = 10 dB and $Q = 3$ 110
- Figure 5.9** Conditional probabilities of correct estimation of K for given $K \in \{0, \dots, 3\}$ as functions of SNR when $L = 64$, $P = 16$, $Q = 3$, $M = 2$, and $(\mu, N_{\text{iter}}) = (1, 20)$ 111

- Figure 5.10** Conditional probabilities of correct estimation of K for given $K \in \{0, \dots, 3\}$ when $L = 64$, SNR = 10 dB, $M = 2$, and $(\mu, N_{\text{iter}}) = (1, 20)$: (a) as functions of the number of multipaths, Q , when $P = 16$; (b) as functions of the length of CP, P , when $Q = 3$ 112
- Figure 5.11** P_c with numbers of samples under $L = 64$, $P = 16$, $Q = 3$, $M = 2$, and SNR = 10 dB 114
- Figure 5.12** P_c with numbers of mutations under $L = 64$, $P = 16$, $Q = 3$, $M = 2$, and SNR = 10 dB 114
- Figure 5.13** P_c with SNR under $K = 2$, $L = 64$, $P = 16$, $Q = 3$, and $M = 2$ 115
- Figure 6.1** Backscatter communication system 118
- Figure 6.2** Ambient backscatter communications for parasite devices 121
- Figure 6.3** P_e versus number of host devices, K , with $M = 200$, SNR = 15 dB, $D = 100$, $L = 64$, $\rho = 0.4$, and $\gamma = 1$ 129
- Figure 6.4** P_e versus SNR, with $M = 200$, $D = 100$, $L = 64$, $\rho = 0.4$, and $\gamma = 1$ 130
- Figure 6.5** P_e versus number of antennas, M , with SNR = 15 dB, $D = 100$, $L = 64$, $\rho = 0.4$, and $\gamma = 1$ 131
- Figure 6.6** P_e versus channel correlation coefficient, ρ , with $M = 200$, SNR = 15 dB, $D = 100$, $L = 64$, and $\gamma = 1$ 131
- Figure 6.7** BER versus number of host devices, K , with $M = 200$, SNR = 15 dB, $D = 100$, $L = 64$, $\rho = 0.4$, and $\gamma = 1$ 132
- Figure 6.8** BER versus SNR, with $M = 200$, $D = 100$, $L = 64$, $\rho = 0.4$, and $\gamma = 1$ 133
- Figure 6.9** BER versus number of antennas, M , with SNR = 15 dB, $D = 100$, $L = 64$, $\rho = 0.4$, and $\gamma = 1$ 133
- Figure 6.10** BER versus channel correlation coefficient, ρ , with SNR = 15 dB, $M = 200$, $D = 100$, $L = 64$, $K = 10$, and $\gamma = 1$ 134
- Figure 7.1** NOMA system with two IoT devices 138
- Figure 7.2** The stylized relationship of EE maximization, power minimization, and throughput maximization problems 145
- Figure 7.3** Impact of the normalized distance between the BS and the SU on the value of EE and throughput, with $p_{3,\text{max}} = 20 \times 10^{-3}$ mW. (a) normalized distance between the BS and the SU and (b) normalized distance between the BS and the SU 146
- Figure 7.4** Impact of the maximum constraint $p_{3,\text{max}}$ at the SU on the SIC's failure probability, where the SU is in the middle of the BS and the WU 147

- Figure 8.1** Low energy consumption, high energy efficiency, and low complexity techniques are preferable to enable an energy-efficient multi-cluster coordinated IIoT system 150
- Figure 8.2** Transmission power consumption and EE performance with 5 MHz bandwidth. (a) transmission power consumption performance and (b) EE performance with different coordination designs 155
- Figure 8.3** (a) An elementary example of CI exploitation with BPSK constellation; (b) A quadrature phase shift keying (QPSK) constellation example with CI precoding exploits interference as a beneficial element; (c) A schematic representation of 16-QAM constellation points 157
- Figure 8.4** The performance gain of the FJT-CI and PBF-CI designs over the conventional coordination techniques 159
- Figure 8.5** The symbol error rate and execution time of different precoders in the FJT scenario. (a) Symbol error rate of different precoders and (b) execution time of different precoders 160

List of Algorithms

- Algorithm 2.1** ML Detection 20
- Algorithm 2.2** ZF Detection 23
- Algorithm 2.3** MMSE Detection 26
- Algorithm 2.4** Gibbs Sampler 30
- Algorithm 2.5** VI Detection 34
- Algorithm 2.6** CS Detection 37
- Algorithm 3.1** VI Detection for Sparse Signal 47
- Algorithm 5.1** The GA-MCMC Gibbs Sampler 101
- Algorithm 7.1** EE Oriented FD Cooperative NOMA Algorithm 143

