

SPRINGER BRIEFS IN APPLIED SCIENCES AND TECHNOLOGY
AUTOMOTIVE ENGINEERING: SIMULATION AND VALIDATION METHODS

Alexander Thaler · Daniel Watzenig
Editors

Automotive Battery Technology

SpringerBriefs in Applied Sciences and Technology

Automotive Engineering: Simulation and Validation Methods

Series editors

Anton Fuchs, Graz, Austria
Hermann Steffan, Graz, Austria
Jost Bernasch, Graz, Austria
Daniel Watzenig, Graz, Austria

For further volumes:
<http://www.springer.com/series/11667>

Alexander Thaler · Daniel Watzenig
Editors

Automotive Battery Technology

Editors

Alexander Thaler
Daniel Watzenig
Virtual Vehicle Research Center
Graz
Austria

ISSN 2191-530X ISSN 2191-5318 (electronic)
ISBN 978-3-319-02522-3 ISBN 978-3-319-02523-0 (eBook)
DOI 10.1007/978-3-319-02523-0
Springer Cham Heidelberg New York Dordrecht London

Library of Congress Control Number: 2013958389

© The Author(s) 2014

This work is subject to copyright. All rights are reserved by the Publisher, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, reuse of illustrations, recitation, broadcasting, reproduction on microfilms or in any other physical way, and transmission or information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed. Exempted from this legal reservation are brief excerpts in connection with reviews or scholarly analysis or material supplied specifically for the purpose of being entered and executed on a computer system, for exclusive use by the purchaser of the work. Duplication of this publication or parts thereof is permitted only under the provisions of the Copyright Law of the Publisher's location, in its current version, and permission for use must always be obtained from Springer. Permissions for use may be obtained through RightsLink at the Copyright Clearance Center. Violations are liable to prosecution under the respective Copyright Law. The use of general descriptive names, registered names, trademarks, service marks, etc. in this publication does not imply, even in the absence of a specific statement, that such names are exempt from the relevant protective laws and regulations and therefore free for general use.

While the advice and information in this book are believed to be true and accurate at the date of publication, neither the authors nor the editors nor the publisher can accept any legal responsibility for any errors or omissions that may be made. The publisher makes no warranty, express or implied, with respect to the material contained herein.

Printed on acid-free paper

Springer is part of Springer Science+Business Media (www.springer.com)

Foreword

Ongoing discussions about climate change and the related fuel economy challenges are moving the automotive industry more and more in the direction of pure electric driving. At this point, it is no longer a question of “if” electromobility will become reality, but rather a question of “when” it will become a reality, and which applications will be first to market. Worldwide legal reductions in carbon dioxide and emissions limits will essentially require the electrification of automobiles. In addition, there is an ongoing shift in consumer attitudes towards electric vehicles, which is evident in two examples: Tesla’s electric Model S has already been very successful, and BMW plans to launch its electric i3 by the end of 2013. Those two models, which feature completely new vehicle technology that has been specifically developed for an electric powertrain, may already herald a new era of individual mobility.

One of the main factors driving this trend is that battery technology, which is at the heart of electromobility, has improved significantly in recent years. Particularly in the field of lithium-ion batteries, which are essential for plug-in vehicles (PHEV) and fully electrified vehicles (BEV) due to their high energy and power density, significant progress has been made in reducing costs and improving safety, performance and reliability. For example, energy density has been increased significantly, without compromising power capability. Today’s 18650 lithium-ion cells, which are already in use in automotive applications, can achieve a capacity of more than 3Ah. Safety has also been increased significantly, such as via new separator technologies and/or improved chemistries (e.g. LiFePO₄). Indeed, many measures have already been implemented in the battery management system to protect the battery from dangerous external events (e.g. overcharge, over-temperature, over-current).

However, from a consumer’s perception point of view in automotive applications and over 20 years of experience in other commercial applications (e.g. mobile phones) have shown that there is still considerable room for improvement if drivers are to fully embrace electric driving and the related battery technology. Costs need to be further reduced, and the reliability, durability and safety of lithium-ion batteries can be enhanced. In terms of safety, for example, more must be learned about system safety and abuse tolerance under vehicle crash conditions. Such advances will require an even deeper understanding of the microscopic processes in batteries under both normal and abnormal conditions (e.g. misuse or

crash situations). Furthermore, new analytical approaches must be developed to provide an enhanced insight into the electrochemical processes within the lithium-ion battery cells, which will in turn improve the accuracy of estimations of the remaining vehicle driving range by enabling a better state-of-charge determination of the cells.

This book contributes to this ongoing development effort by providing insight into the state of the art of lithium-ion battery technology modelling. It is designed to stimulate new ideas for the improved utilization of batteries in real application. From a long-term perspective, we hope that this book will help foster improvements of the technology itself and thereby help usher vehicle technology into the next era. While today's lithium-ion batteries are suitable for application in electric cars, it is clear that many improvements are still to come in terms of both the physics and chemistry of such batteries. Energy and power density, which directly affect driving range and vehicle performance, will be significantly increased; safety and reliability will be further improved; and the total cost of batteries will decrease once production figures reach automotive scale quantities. As a consequence, consumer acceptance will increase significantly, as vehicles driven by "horsepower" from combustion engines will become less attractive than quiet, environmentally friendly electric vehicles propelled by "kiloWatts". When this happens, PHEVs and BEVs will have truly arrived.

Graz, November 2013

Volker Hennige

Preface

During the last 10 years, the modern world has seen at least the second attempt to electrify the powertrains of road traffic vehicles. Beyond the battery, which is a key component in this electrification process, all other parts have been further developed. All power devices have made a huge step forward. The combination of powerful control devices and semiconductor enhancements are providing adequate functionality from a customer point of view.

Much research has been conducted on the electrochemical level, and there has been progress made on energy density and cost as well. However, currently there is no electrochemical energy storage system available that fulfils the energy demand of today's drive trains and the related passenger comfort functions. Of course, it is simple to blame the battery and argue that this technology does not cover the needs. On the other hand, we can see that society is embracing the need to be more efficient when using energy, a need which is particularly strong in the area of mobility. Thus, the trend towards the electrification of drive trains is revealing the essential weakness of today's vehicle concepts. In the past, the availability of fossil fuels, with their high energy density, fostered vehicle evolution. Due to the limitation of on-board installed energy in storage systems, public awareness of the low efficiency of current vehicles has been growing, and the automotive industry has grasped the demand for more efficiency.

Two developments are anticipated:

- An increase in efficiency on the drive-train level, comfort (HVAC, etc.) and safety functions within a vehicle
- An increase in energy density in terms of energy storage:
 - Energy density will increase on the chemical level
 - Technology integration aspects (e.g. ageing, safety) will become better understood and development processes will be implemented in the automotive industry.

This book provides a comprehensive overview of the current research work in the latter area (i.e. integration). The two main topics of this book, safety and ageing, both directly influence the size and utilization of the applied storage system.

Articles Related to Safety

In [Chap. 1](#), Martin et al. offer an overview of today state-of-the-art safety standard. Although this standard is well defined in ISO 26262, from an overall system-safety perspective, important processes and methods are still missing. Since safety aspects influence cost, it is essential to understand how different safety measures reduce risk for a new product (e.g. a battery system) that is integrated into the vehicle environment.

In [Chap. 2](#), Trattning and Leitgeb provide an overview of the challenge of mechanical battery modelling in crash/crush battery simulations. The current challenge in this area is to bridge the gap between the battery's micro structures and the need to keep simulation effort manageable. The question is, how simple can a model be made while still preserving its ability to provide all of the necessary information at the vehicle level to enable crash-relevant optimizations.

In [Chap. 3](#), Golubkov and Fuchs focus on the thermal runaway process. Their team is currently working to develop a basic, application-related understanding of this process. The knowledge of this process will enable the creation of a battery system simulation framework that can predict the propagation of thermal runaway within the whole battery and the vehicle as a whole.

Articles Related to Ageing

In [Chap. 4](#), Pichler and Cifrain describe an approach for modelling the electro-chemical battery cell with all of the necessary details. The major challenge here is to devise a model that covers the physical properties of the cell in nanometre scale (e.g. anode/cathode porosity) while still providing simulation output in a reasonable amount of time and with an acceptable level of quality. The final step is the optimization of the cell design and technology in front of the application (e.g. driving cycle), while also covering major ageing aspects. A detailed model of physical processes always requires real parameters derived directly from physical measurements. In [Chap. 5](#), Weber et al. provide an overview of analytical methods for quantifying the ageing of lithium-ion batteries. Such laboratory work is a necessary input for the models mentioned above. Since a complex model uses parameters that are not directly measurable, in [Chap. 6](#), Scharrer et al. present a mathematical method for parameter optimization. To demonstrate this method, they present the results of a synthetic fitting problem solved by a parallel-adaptive Markov chain Monte Carlo method.

In [Chap. 7](#), Hametner and Jakubek present a data-based, chemistry-independent approach to nonlinear observer design for the state-of-charge (SoC) estimation. In order to operate the energy storage system throughout the required lifetime, knowledge of the SoC is essential, and one of the key factors related to ageing.

One significant challenge for all of these individual approaches towards improved safety and life time of battery systems is the complexity this component adds to the car. Standards in the automotive industry are particularly high, especially in terms of quality and durability, and all research conducted in these fields must be measured against these standards. In the field of applied research, the key to meeting these high standards is the combination of knowledge from different specialist domains.

Such collaboration can produce high quality, highly useful development environments (modelling, simulation tools, accompanying tests and standards). In this context, the coordination of the efforts of specialists from different industries and from research institutes is the way forward.

Graz, November 2013

Alexander Thaler
Daniel Watzenig

Contents

1	Holistic Safety Considerations for Automotive Battery Systems . . .	1
	Helmut Martin, Andrea Leitner and Bernhard Winkler	
2	Battery Modelling for Crash Safety Simulation	19
	Gernot Trattnig and Werner Leitgeb	
3	Thermal Runaway: Causes and Consequences on Cell Level	37
	Andrey W. Golubkov and David Fuchs	
4	Application-Related Battery Modelling: From Empirical to Mechanistic Approaches.	53
	Franz Pichler and Martin Cifrain	
5	Analytical Methods for Investigation of Lithium-Ion Battery Ageing.	71
	Sascha Weber, Sascha Nowak and Falko Schappacher	
6	Bayesian Inference for Lithium-Ion Cell Parameter Estimation . . .	89
	Matthias K. Scharrer, Heikki Haario and Daniel Watzenig	
7	Data-Driven Methodologies for Battery State-of-Charge Observer Design.	111
	Christoph Hametner and Stefan Jakubek	
	Erratum to: Application-Related Battery Modelling: From Empirical to Mechanistic Approaches.	E1
	Franz Pichler and Martin Cifrain	
	About the Editors and Authors	127

Contributors

Martin Cifrain Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: martin.cifrain@v2c2.at

David Fuchs Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: david.fuchs@v2c2.at

Andrey W. Golubkov Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: andrej.golubkov@v2c2.at

Heikki Haario Lappeenranta University of Technology, Lappeenranta, Finland, e-mail: heikki.haario@lut.fi

Christoph Hametner Christian Doppler Laboratory for Model Based Calibration Methodologies, Vienna University of Technology, Wiedner Hauptstr. 8-10, 1040 Vienna, Austria, e-mail: christoph.hametner@tuwien.ac.at

Stefan Jakubek Institute of Mechanics and Mechatronics, Vienna University of Technology, Wiedner Hauptstr. 8-10, 1040 Vienna, Austria, e-mail: stefan.jakubek@tuwien.ac.at

Werner Leitgeb Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: werner.leitgeb@v2c2.at

Andrea Leitner Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: andrea.leitner@v2c2.at

Helmut Martin Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: helmut.martin@v2c2.at

Sascha Nowak MEET Battery Research Center, Westfälische Wilhelms-Universität Münster, Corrensstr. 46, 48149 Münster, Germany, e-mail: sascha.nowak@uni-muenster.de

Franz Pichler Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: franz.pichler@v2c2.at

Falko Schappacher MEET Battery Research Center, Westfälische Wilhelms-Universität Münster, Corrensstr. 46, 48149 Münster, Germany, e-mail: falko.schappacher@uni-muenster.de

Matthias K. Scharrer Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: matthias.scharrer@v2c2.at

Alexander Thaler Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: alex.thaler@v2c2.at

Gernot Trattnig Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: gernot.trattnig@v2c2.at

Daniel Watzenig Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: daniel.watzenig@v2c2.at

Sascha Weber MEET Battery Research Center, Westfälische Wilhelms-Universität Münster, Corrensstr. 46, 48149 Münster, Germany, e-mail: sascha.weber@uni-muenster.de

Bernhard Winkler Virtual Vehicle Research Center, Inffeldgasse 21a, 8010 Graz, Austria, e-mail: bernhard.winkler@v2c2.at

Chapter 1

Holistic Safety Considerations for Automotive Battery Systems

Helmut Martin, Andrea Leitner and Bernhard Winkler

Abstract The objective of system safety engineering is to develop a system with no unreasonable risk. To this end, risks caused by the electrical and/or electronic (E/E) system that could potentially harm persons must be analyzed, and appropriate risk reduction measures have to be considered in an early phase of development. This requires a close collaboration between different engineering disciplines in order to specify a comprehensive description of risk reduction and mitigation measures—the safety concept. The international functional safety standard ISO 26262 has to be considered for the development of E/E systems within road vehicles up to 3.5 tons. This standard focuses on E/E measures and considers other non-E/E measures only after the specification of the safety concept. In contrast, this chapter proposes a workflow for the elaboration of an integrated safety concept including safety measures from different engineering disciplines. Two main lessons learned were that the consideration of all kinds of risk reduction measures in the concept phase improves the understanding of the safety of the overall system, and involving various fields of expertise enables the development of a clear safety concept. This approach will improve the development of the overall system, while complying with the requirements of ISO 26262 for the development of E/E systems. The applicability of the introduced approach is demonstrated on an automotive battery case study, where the influence of various safety measures on the Automotive Safety Integrity Level (ASIL) determination has been taken into account in order to reduce the costs of E/E system development.

H. Martin (✉) · A. Leitner · B. Winkler
Virtual Vehicle Research Center, Graz, Austria
e-mail: helmut.martin@v2c2.at

A. Leitner
e-mail: andrea.leitner@v2c2.at

B. Winkler
e-mail: bernhard.winkler@v2c2.at

1.1 Motivation

Hazardous voltage (HV) battery systems are a central part of battery-powered Electric Vehicles (EVs) or Hybrid Electric Vehicles (HEVs) [8], which are becoming more and more important. One reason is the high energy efficiency of E/E systems and the zero (local) environmental pollution of EVs. Their main disadvantage is the relatively short operation range, which is far less competitive compared to conventional vehicles with internal combustion engines. Conventional vehicles provide good performance and long operating ranges by utilizing the high energy-density advantages of petroleum fuels. HEVs combine the advantages of both technologies. Some of the main targets for batteries to be used in HEVs are low costs, high power density (e.g. 1,200 W/kg), very high cycle life time (e.g. 200,000 cycles of charge/discharge), long life time (e.g. 9 years), and safety. With the growing importance of e-mobility, automotive battery systems are becoming more important as well. High power (e.g. HEV up to 250 kW to provide more dynamic driving torques) and high energy application (e.g. EVs such as Nissan Leaf 36 kWh to allow longer driving distances) are already being applied in series-production vehicles. Increasing power and energy while decreasing the battery geometries leads to an increase of potential critical effects in the case of malfunctions.

This chapter focuses on safety aspects in the context of safety-critical automotive batteries for EVs or HEVs. Regarding functional safety (safety of the E/E system), the IEC 61508¹ [3] is the basic international functional safety standard applicable to all industries. The ISO 26262 [4] is an adaptation of this standard that is applicable to the development of safety-related electrical and/or electronic (E/E) systems in the automotive domain. One important aspect of functional safety is the potential risk of electronic malfunction, e.g. malfunction of the battery control unit caused by incorrect inputs or software errors. These malfunctions could lead to hazardous events for passengers, other traffic participants, and uninvolved parties (e.g. fire due to overcharge). The potential of malfunctions has to be lowered by gaining of possible faults, as well as their causes and effects, and by providing solutions for fault mitigation.

In particular, e-mobility is highly interdisciplinary, whereby risk reduction also results from different technical disciplines (e.g. mechanics, chemistry). This means that system safety has to consist of different safety disciplines as well (i.e. functional, electrical, mechanical, and chemical safety). One example for electrical safety could be the prevention of hazardous voltage through the use of galvanic disconnections or isolation. Mechanical safety aims to prevent the deformation of the battery in the case of an accident through the use of cell housings or the installation location for example. Chemical safety can prevent explosions or fire by using a mechanical venting outlet for toxic gases. All of these measures are applicable for the development of a safe system.

¹ IEC 61508—Functional safety of electrical/electronic/programmable electronic safety-related systems.