

Khaled Khalaf
Vojkan Vidojkovic
Piet Wambacq
John R. Long

Data Transmission at Millimeter Waves

Exploiting the 60 GHz Band on Silicon

Lecture Notes in Electrical Engineering

Volume 346

Board of Series editors

Leopoldo Angrisani, Napoli, Italy
Marco Arteaga, Coyoacán, México
Samarjit Chakraborty, München, Germany
Jiming Chen, Hangzhou, P.R. China
Tan Kay Chen, Singapore, Singapore
Rüdiger Dillmann, Karlsruhe, Germany
Haibin Duan, Beijing, China
Gianluigi Ferrari, Parma, Italy
Manuel Ferre, Madrid, Spain
Sandra Hirche, München, Germany
Faryar Jabbari, Irvine, USA
Janusz Kacprzyk, Warsaw, Poland
Alaa Khamis, New Cairo City, Egypt
Torsten Kroeger, Stanford, USA
Tan Cher Ming, Singapore, Singapore
Wolfgang Minker, Ulm, Germany
Pradeep Misra, Dayton, USA
Sebastian Möller, Berlin, Germany
Subhas Mukhopadhyay, Palmerston, New Zealand
Cun-Zheng Ning, Tempe, USA
Toyoaki Nishida, Sakyo-ku, Japan
Bijaya Ketan Panigrahi, New Delhi, India
Federica Pascucci, Roma, Italy
Tariq Samad, Minneapolis, USA
Gan Woon Seng, Nanyang Avenue, Singapore
Germano Veiga, Porto, Portugal
Haitao Wu, Beijing, China
Junjie James Zhang, Charlotte, USA

About this Series

“Lecture Notes in Electrical Engineering (LNEE)” is a book series which reports the latest research and developments in Electrical Engineering, namely:

- Communication, Networks, and Information Theory
- Computer Engineering
- Signal, Image, Speech and Information Processing
- Circuits and Systems
- Bioengineering

LNEE publishes authored monographs and contributed volumes which present cutting edge research information as well as new perspectives on classical fields, while maintaining Springer’s high standards of academic excellence. Also considered for publication are lecture materials, proceedings, and other related materials of exceptionally high quality and interest. The subject matter should be original and timely, reporting the latest research and developments in all areas of electrical engineering.

The audience for the books in LNEE consists of advanced level students, researchers, and industry professionals working at the forefront of their fields. Much like Springer’s other Lecture Notes series, LNEE will be distributed through Springer’s print and electronic publishing channels.

More information about this series at <http://www.springer.com/series/7818>

Khaled Khalaf · Vojkan Vidojkovic
Piet Wambacq · John R. Long

Data Transmission at Millimeter Waves

Exploiting the 60 GHz Band on Silicon

 Springer

Khaled Khalaf
SSET-CSI
IMEC
Leuven
Belgium

Piet Wambacq
SSET-CSI
IMEC
Leuven
Belgium

Vojkan Vidojkovic
SSET-CSI
IMEC
Leuven
Belgium

John R. Long
Faculty of EEMCS
Delft University of Technology
CD Delft
The Netherlands

ISSN 1876-1100 ISSN 1876-1119 (electronic)
Lecture Notes in Electrical Engineering
ISBN 978-3-662-46937-8 ISBN 978-3-662-46938-5 (eBook)
DOI 10.1007/978-3-662-46938-5

Library of Congress Control Number: 2015936687

Springer Heidelberg New York Dordrecht London
© Springer-Verlag Berlin Heidelberg 2015

This work is subject to copyright. All rights are reserved by the Publisher, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, reuse of illustrations, recitation, broadcasting, reproduction on microfilms or in any other physical way, and transmission or information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed.

The use of general descriptive names, registered names, trademarks, service marks, etc. in this publication does not imply, even in the absence of a specific statement, that such names are exempt from the relevant protective laws and regulations and therefore free for general use.

The publisher, the authors and the editors are safe to assume that the advice and information in this book are believed to be true and accurate at the date of publication. Neither the publisher nor the authors or the editors give a warranty, express or implied, with respect to the material contained herein or for any errors or omissions that may have been made.

Printed on acid-free paper

Springer-Verlag GmbH Berlin Heidelberg is part of Springer Science+Business Media
(www.springer.com)

Acknowledgments

This work was fulfilled as a result of a cooperative research project between the TU Delft Electronics and IMEC wireless research groups. So, I would like to thank all those who helped me in bringing this work to life. I'd like to thank my advisors, Profs. John Long and Piet Wambacq, for their valuable guidance and discussions, and for making such cooperation possible. Special thanks to my direct supervisor, Vojkan Vidojkovic, for his constant support and continuous technical and un-technical discussions during my period at IMEC. I'd like to thank Bertrand Parvais, Kuba Raczkowski, Kristof Vaesen, Charlotte Soens, Viki Szortyka, Giovanni Mangraviti, Karen Scheir, and Julien Ryckaert for all their help, guidance, and fruitful discussions at IMEC. I'd like also to thank Roeland Vandebriel for the IO ring implementation. Thanks are extended to all who shared their thoughts and helped me in TU Delft including Yanyu Jin, Mina Danesh, Hakan Cetinkaya, and Antoon Frehe. I'd like to acknowledge all my professors at TU Delft including Leo de Vreede and Klaas Bult for their encouraging and valuable course contents, and all my classmates and friends in Delft who made it easier for me staying in that period just studying! I appreciate the efforts of all my friends in Leuven that were continuously supporting me in the good and bad times. I've to express deep thanks to my friends in Germany who actually encouraged me in continuing my post-graduate studies regardless of all the difficulties that I was facing. I'd like also to send deep regards to my bachelor staff members in Ain Shams University who guided me through such an interesting research and career path. I'd like to thank Alaa Medra for helping me finishing this book. No words can express acknowledging my family who did all what they can to help me achieving my goals, especially my wife and little kids for giving me a lot of "their" time to use in this book.

Contents

1	Introduction	1
1.1	Motivation	1
1.2	60 GHz Area Background	2
1.2.1	Standards and Frequency Plan	2
1.2.2	Beamforming and System Architecture	3
1.2.3	Enabling Technology	5
1.2.4	Applications	6
1.3	Book Objectives	7
1.4	Organization of the Following Chapters	7
	References	7
2	Background	9
2.1	QVCO	9
2.1.1	VCO Basics	9
2.1.2	Main Parameters	11
2.1.3	Phase Noise Origins	15
2.1.4	Quadrature VCO	18
2.2	LO Buffer	20
2.3	Frequency Divider	24
2.3.1	ILFD	25
2.3.2	Static Divider	28
2.4	LNA	30
2.4.1	NF and IIP3	31
2.4.2	LNA Topology	33
2.5	Mixer	34
2.5.1	Main Parameters	35
2.5.2	Mixer Topology	36
	References	38

3	Design and Simulation Results	41
3.1	f_T of the 90 Nm NMOS Transistor	41
3.2	Passive Elements	42
3.2.1	Varactors	42
3.2.2	Transmission Lines	43
3.2.3	Inductors	44
3.2.4	Transformers	44
3.3	QVCO and LO Buffer	46
3.3.1	Circuit Schematic	46
3.3.2	Circuit Operation	48
3.3.3	Design Guidelines	52
3.3.4	Design Values	57
3.3.5	Simulation Results of P-QVCO	57
3.3.6	Simulation Results of BS-QVCO	63
3.3.7	Performance Summary	63
3.4	Divider Chain	64
3.4.1	Circuit Schematic	65
3.4.2	ILFD Locking Range	65
3.4.3	Design Guidelines	68
3.4.4	Design Values	70
3.4.5	Simulation Results	70
3.4.6	Performance Summary	74
3.5	LNA and Mixer	75
3.5.1	Circuit Schematic	75
3.5.2	Design Guidelines	76
3.5.3	Design Values	76
3.5.4	Simulation Results	76
3.5.5	Performance Summary	81
	References	82
4	Top-Level Design	83
4.1	Complete Top-Level Circuit	83
4.1.1	Circuit Schematic	83
4.1.2	Design Choices	83
4.1.3	Design Values	85
4.1.4	Simulation Results	85
4.2	QVCO and Divider Sub-system	87
4.2.1	Circuit Schematic	87
4.2.2	Design Choices	87
4.2.3	Design Values	89
4.2.4	Simulation Results	89
	Reference	93

- 5 Layout and Post-layout Simulations 95**
 - 5.1 Physical Layout 95
 - 5.2 Nominal Simulation Result 95
 - 5.2.1 Divider 97
 - 5.2.2 QVCO and LO Buffer 98
 - 5.3 PVT Simulations 100

- 6 Conclusions 103**
 - 6.1 Summary 103
 - 6.2 Future Work 104
 - Reference 105

- Transformer-Coupled Buffer 107**

Figures

Fig. 1.1	Atmospheric propagation attenuation versus frequency	2
Fig. 1.2	57–66 GHz band divided into 4 channels	3
Fig. 1.3	Radiation pattern of a beamformer	4
Fig. 1.4	Beamforming system with antenna arrays and transceivers	4
Fig. 1.5	60 GHz receiver architecture	5
Fig. 1.6	60 GHz potential indoor applications	6
Fig. 2.1	Cross-coupled LC VCO	10
Fig. 2.2	Small-signal analysis of the active part	10
Fig. 2.3	Oscillator negative resistor model	11
Fig. 2.4	VCO main defining parameters	11
Fig. 2.5	Conversion from square wave current to sinusoidal output voltage through filtering by the resonator	13
Fig. 2.6	Oscillator output differential amplitude based on the operation of the tail current transistor	13
Fig. 2.7	Sidebands can be seen as AM and/or PM signals	14
Fig. 2.8	Down conversion of unwanted frequency bands due to oscillator spectral impurity	14
Fig. 2.9	Phase noise spectrum in dBc/Hz	15
Fig. 2.10	Noise folding due to cross-coupled pair	17
Fig. 2.11	Tail noise mixing with the cross-coupled pair	17
Fig. 2.12	Orthogonal signal out of the QVCO	18
Fig. 2.13	Parallel QVCO (P-QVCO) topology	19
Fig. 2.14	P-QVCO with gate decoupling and external bias	19
Fig. 2.15	Half-sections of series-QVCO in a top (TS-QVCO) and b bottom (BS-QVCO) configurations	20
Fig. 2.16	Gate-modulated QVCO (GM-QVCO) architecture	21
Fig. 2.17	Source follower buffer	21
Fig. 2.18	Inductively-tuned CS differential amplifier as a buffer	22
Fig. 2.19	Model of the active buffer	23
Fig. 2.20	Active buffer with transformer load a voltage output b current output	23

Fig. 2.21	Harmonic injection (injection-locked) frequency divider model	25
Fig. 2.22	Conventional ILFD	26
Fig. 2.23	Direct ILFD a circuit schematic and b equivalent model.	27
Fig. 2.24	Block diagram of the differential direct ILFD	27
Fig. 2.25	Voltage and current waveforms a at $\varphi = \pi/2$ and b $\varphi = \pi/4$	28
Fig. 2.26	Dual-mixing direct ILFD circuit schematic	29
Fig. 2.27	Conventional CML latches in a master-slave configuration.	29
Fig. 2.28	High frequency CML divider (by two)	30
Fig. 2.29	Two-tone excitation resulting tones (to the third-order)	32
Fig. 2.30	Definition of important linearity parameters.	32
Fig. 2.31	a Inductively degenerated CS transistor and b small-signal model	33
Fig. 2.32	Single-ended cascode LNA using inductive degeneration	34
Fig. 2.33	Definition of a SSB versus b DSB NF.	35
Fig. 2.34	Active implementation of double-balanced mixer.	36
Fig. 2.35	Passive implementation of double-balanced mixer	37
Fig. 3.1	a Transit frequency of the used 90 nm transistor, and b drain current density versus gate voltage	42
Fig. 3.2	a Capacitance and b quality factor for a varactor with $W = 1 \mu\text{m}$ and $M = 20$	43
Fig. 3.3	Transmission line a cross-section and b RLCG model	43
Fig. 3.4	Single-ended TL characteristic impedance versus frequency	44
Fig. 3.5	a Inductance and b quality factor of the 300 pH differential inductor	45
Fig. 3.6	Differential inductor lumped component model	45
Fig. 3.7	Transformer implemented with 83 pH primary (=secondary) inductance in 90 nm process	45
Fig. 3.8	Testbench used for the prediction of transformer parameters	46
Fig. 3.9	a Inductance, b quality factor and c coupling coefficient of the 83 pH transformer.	47
Fig. 3.10	Transformer lumped component model.	47
Fig. 3.11	Circuit schematic of the used P-QVCO.	49
Fig. 3.12	Circuit schematic of the transformer-coupled LO buffer with output load	50

Fig. 3.13	QVCO a without b with external gate bias, and c higher swing possibility without taking the cross-coupled transistors out of saturation	50
Fig. 3.14	Impedance points of the QVCO two oscillation modes	51
Fig. 3.15	Current and voltage-limited regimes with the bias current as a variable	54
Fig. 3.16	a Average capacitance value and b effective capacitance curve for a varactor in a VCO	55
Fig. 3.17	Less tuning frequency with higher current due to different effective capacitance values at different amplitudes	55
Fig. 3.18	P-QVCO and LO buffer amplitudes versus oscillation frequency.	59
Fig. 3.19	Phase noise at 1 MHz offset versus oscillation frequency	59
Fig. 3.20	a A at max. and min. oscillation freq. b Max. and min. oscillation frequency variations with QVCO bias current.	60
Fig. 3.21	Phase noise variations at max. and min. oscillation frequencies with QVCO bias current	60
Fig. 3.22	a Amplitude and b phase noise variations with external gate bias at maximum oscillation frequency	61
Fig. 3.23	a Amplitude and b phase noise variations with supply voltage at maximum oscillation frequency	61
Fig. 3.24	a Amplitude and b phase noise variations with external gate bias at 1.2 V supply and maximum oscillation frequency	62
Fig. 3.25	P-QVCO and LO buffer amplitudes versus oscillation frequency at a reduced load transistor width of 24 μm	62
Fig. 3.26	BS-QVCO and LO buffer a amplitudes and b phase noise over the whole tuning range	63
Fig. 3.27	BS-QVCO and LO buffer amplitudes versus oscillation frequency at a reduced load transistor width of 24 μm	64
Fig. 3.28	Divider chain block diagram	65
Fig. 3.29	Differential to single-ended stage with output buffers	66
Fig. 3.30	Locking range behavior with inductor quality factor.	67
Fig. 3.31	Divider output spectrum with quality factor curves assuming equal output amplitude	68
Fig. 3.32	60 GHz divider input sensitivity curve	71
Fig. 3.33	60 GHz divider output power at 4 dBm input signal	71
Fig. 3.34	30 GHz divider input sensitivity curve	71
Fig. 3.35	30 GHz divider output power at 4 dBm input signal	72
Fig. 3.36	First static divider input sensitivity curve	72