



Waste Management

in the Chemical and Petroleum Industries

ALIREZA BAHADORI



WILEY

**Waste Management in
the Chemical and
Petroleum Industries**

Waste Management in the Chemical and Petroleum Industries

Alireza Bahadori

*School of Environment, Science and Engineering,
Southern Cross University, Australia*

WILEY

This edition first published 2014
© 2014 John Wiley & Sons, Ltd

Registered office

John Wiley & Sons Ltd, The Atrium, Southern Gate, Chichester, West Sussex, PO19 8SQ, United Kingdom

For details of our global editorial offices, for customer services and for information about how to apply for permission to reuse the copyright material in this book please see our website at www.wiley.com.

The right of the author to be identified as the author of this work has been asserted in accordance with the Copyright, Designs and Patents Act 1988.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, except as permitted by the UK Copyright, Designs and Patents Act 1988, without the prior permission of the publisher.

Wiley also publishes its books in a variety of electronic formats. Some content that appears in print may not be available in electronic books.

Designations used by companies to distinguish their products are often claimed as trademarks. All brand names and product names used in this book are trade names, service marks, trademarks or registered trademarks of their respective owners. The publisher is not associated with any product or vendor mentioned in this book. This publication is designed to provide accurate and authoritative information in regard to the subject matter covered. It is sold on the understanding that the publisher is not engaged in rendering professional services. If professional advice or other expert assistance is required, the services of a competent professional should be sought.

The publisher and the author make no representations or warranties with respect to the accuracy or completeness of the contents of this work and specifically disclaim all warranties, including without limitation any implied warranties of fitness for a particular purpose. This work is sold with the understanding that the publisher is not engaged in rendering professional services. The advice and strategies contained herein may not be suitable for every situation. In view of ongoing research, equipment modifications, changes in governmental regulations, and the constant flow of information relating to the use of experimental reagents, equipment, and devices, the reader is urged to review and evaluate the information provided in the package insert or instructions for each chemical, piece of equipment, reagent, or device for, among other things, any changes in the instructions or indication of usage and for added warnings and precautions. The fact that an organization or Website is referred to in this work as a citation and/or a potential source of further information does not mean that the author or the publisher endorses the information the organization or Website may provide or recommendations it may make. Further, readers should be aware that Internet Websites listed in this work may have changed or disappeared between when this work was written and when it is read. No warranty may be created or extended by any promotional statements for this work. Neither the publisher nor the author shall be liable for any damages arising herefrom.

Library of Congress Cataloging-in-Publication Data

Bahadori, Alireza.

Waste management in the chemical and petroleum industries / Alireza Bahadori.

1 online resource.

Includes index.

Description based on print version record and CIP data provided by publisher; resource not viewed.

ISBN 978-1-118-73171-0 (MobiPocket) – ISBN 978-1-118-73172-7 (Adobe PDF) – ISBN 978-1-118-73173-4 (ePub) – ISBN 978-1-118-73175-8 (cloth) (print) 1. Petroleum industry and trade–Waste disposal. 2. Chemical industry–Waste disposal. 3. Petroleum refineries–Waste disposal. I. Title.

TD899.P4

628.5'1–dc23

2013021840

A catalogue record for this book is available from the British Library.

ISBN: 9781118731758 (13 digits)

Set in 10/12pt Times by Aptara Inc., New Delhi, India.

Dedicated to the loving memory of my Parents, grandparents, and to all
who contributed so much to my work over the years.

Contents

<i>Preface</i>	xv
<i>Acknowledgments</i>	xix
<i>Biography</i>	xxi
1 Wastewater Treatment	1
1.1 Characteristics of Wastewaters	1
1.1.1 Suspended Solids	2
1.1.2 Heavy Metals	2
1.1.3 Dissolved Inorganic Solids	4
1.1.4 Toxic Organic Compounds	4
1.1.5 Surfactants	6
1.1.6 Priority Pollutants	6
1.1.7 Volatile Organic Compounds	6
1.2 Treatment Stages	7
1.2.1 Sources of Wastewater	8
1.2.2 Discharge Options and Quality Requirements	8
1.2.3 Preliminary Wastewater Treatment	9
1.2.4 Primary Wastewater Treatment	9
1.2.5 Conventional Secondary Wastewater Treatment	9
1.2.6 Nutrient Removal or Control	9
1.2.7 Advanced Wastewater Treatment/Wastewater Reclamation	10
1.2.8 Toxic Waste Treatment/Specific Contaminant Removal	10
1.2.9 Sludge Processing	10
1.3 Treatment Processes	11
1.3.1 Selection of Treatment Processes	14
1.4 Chemical Oxygen Demand (COD) in Wastewater Systems	22
1.4.1 Determination of the COD	23
1.4.2 Calculation of Theoretical Oxygen Demand	23
2 Physical Unit Operations	25
2.1 Flow Measurement	25
2.2 Screening	25
2.3 Comminution	28
2.4 Grit Removal	28
2.5 Gravity Separation	29
2.5.1 General	29

2.5.2	Application	30
2.5.3	Oil–Water Separator General Design Considerations	30
2.5.4	Conventional Rectangular Channel (API) Separators	31
2.5.5	Parallel-Plate Separators	43
2.5.6	Oil Traps	45
2.5.7	Oil Holding Basins	46
2.6	Flow Equalization	46
2.6.1	Application and Location	46
2.6.2	Volume Requirements	48
2.7	Mixing	48
2.7.1	Description and Type	48
2.7.2	Application	48
2.8	Sedimentation	49
2.8.1	Sedimentation Theory	49
2.8.2	Application and Type	51
2.8.3	Design Considerations	53
2.8.4	Number of Basins	53
2.8.5	Inlet Arrangements	54
2.8.6	Short-Circuiting	54
2.8.7	Outlet Arrangements	54
2.8.8	Detention Time	54
2.8.9	Surface Loading Rate	54
2.8.10	Factors Affecting Sedimentation	55
2.9	Dissolved Air Flotation (DAF)	56
2.9.1	General	56
2.9.2	System Configuration	57
2.9.3	Variables Affecting DAF Efficiency	58
2.9.4	Treatability Testing	59
2.9.5	Design Considerations	59
2.9.6	Instruments and Control	64
2.9.7	Piping	65
2.9.8	Chemical Facilities	65
2.9.9	Material	65
2.9.10	Estimation of Air Concentration in Dissolved Air Flotation (DAF) Systems	66
2.10	Granular-Media Filters	71
2.10.1	General	71
2.10.2	Filter Types and Applications	72
2.10.3	System Design Parameters	74
2.10.4	Cycle Time	76
2.10.5	Vessels and Appurtenances	77
2.10.6	Instrumentation and Controls	78
3	Chemical Treatment	81
3.1	Introduction	81
3.1.1	Chemical Precipitation	81
3.1.2	Chemical Coagulation	81

3.1.3	Chemical Oxidation and Advanced Oxidation	82
3.1.4	Ion Exchange	82
3.1.5	Chemical Stabilization	84
3.2	Definition and Application	84
3.2.1	Activated Carbon Adsorption	85
3.3	Chemical Precipitation	87
3.4	Chemical Flocculation	87
3.4.1	Definition and Applications	88
3.4.2	Design Considerations	90
3.4.3	Clarifier	90
3.4.4	Chemical Addition Systems	93
3.5	Disinfection	94
3.5.1	Chemical Agents	95
3.5.2	Mechanical Means	95
3.6	Chlorination	95
3.6.1	Application	96
3.6.2	Chlorine Dosages	96
3.6.3	Design Considerations	96
4	Biological Treatment	99
4.1	Theory	99
4.1.1	Biological Activated Carbon Process	101
4.1.2	Biokinetic Theoretical Model	102
4.2	Biological Treatment Processes	104
4.2.1	Major Differences in Aerobic and Anaerobic Treatment	106
4.2.2	Aerobic Processes	107
4.2.3	Anaerobic Waste Treatment	112
4.2.4	Aerobic, Anaerobic (Facultative) Waste Treatment	112
4.3	Activated-Sludge Units	112
4.3.1	Applications	113
4.3.2	Effects of Activated-Sludge	114
4.3.3	Feed Composition	115
4.3.4	Process Design	120
4.3.5	Design Considerations	120
4.4	Trickling-Filters	123
4.4.1	Trickling-Filter Process Design	124
4.5	Rotating Biological Contactor System	126
4.6	Sewage Oxidation Ponds	126
5	Wastewater Treatment in Unconventional Oil and Gas Industries	129
5.1	Background	129
5.1.1	Dissolved and Dispersed Hydrocarbon Components	131
5.1.2	Dissolved Mineral	131
5.1.3	Production Chemicals	131
5.1.4	Produced Solids	132
5.1.5	Dissolved Gases	132

5.2	Toxicity Limitations of Coal Bed Water	132
5.3	Shale Gas and Coal Seam Gas Produced Water, Treatment and Disposal	135
5.3.1	Evaporation Pond	136
5.3.2	Surface Stream Disposal	136
5.3.3	Ion Exchange	138
5.3.4	Membrane Filtration Technology	138
5.3.5	Freeze–Thaw Evaporation	140
5.3.6	Adsorption	140
5.3.7	Chemical Oxidation	140
5.3.8	Filtration	141
5.3.9	Constructed Wetlands	141
5.3.10	Electrodialysis/Electrodialysis Reversal	141
5.3.11	Deep Well Injection at Dedicated Onshore Sites	141
5.3.12	Biological Aerated Filters	142
5.3.13	Macro-Porous Polymer Extraction Technology	143
5.3.14	Thermal Technologies	143
5.4	Re-Thinking Technologies for Safer Facing	147
5.5	Water Treatment for Oil Sands Mining	153
5.5.1	Recycling and Water Treatment Options	153
5.5.2	Oily Water Treatment in Oil Sands Mining	155
6	Wastewater Sewer Systems	161
6.1	Stormwater Sewer System	162
6.2	Oily Water Sewer System	162
6.3	Non-Oily Water Sewer System	163
6.4	Chemical Sewer System(s)	164
6.4.1	Disposal of Chemical Sewers	164
6.4.2	Neutralization Systems	164
6.4.3	Type of Chemical Wastes	164
6.5	Sanitary Sewer System	165
6.6	Special Sewer Systems	165
6.7	Effluent Sources and Disposals	165
6.8	Particular Effluents in Refinery and Petrochemical Plants	167
6.8.1	Caustic Scrubs (Heavy Oils)	167
6.8.2	Desalter Wastewater	168
6.8.3	Foul or Sour Waters	168
6.8.4	Spent Caustic Solutions	168
6.8.5	MTBE or Leaded Contaminated Streams	170
6.8.6	Benzene Contaminated Streams	171
6.8.7	Spent Sulfuric Acid Products	171
6.8.8	Nitrogen Base Components	172
6.8.9	Cyanides	172
6.8.10	Aluminum Chloride	173
6.8.11	Polyelectrolyte	173
6.8.12	Ferric Chloride	173
6.8.13	Phosphoric Acid	173

6.8.14	Hydrofluoric Acid	173
6.8.15	Other Spent Catalysts	173
6.8.16	Chemical Cleaning Wastes	174
6.8.17	Sulfur Solidification and Crushing Facilities and Loading Systems Drainage	174
6.8.18	Water Containing Solids, Emulsifying Agents, etc.	174
6.8.19	Heavy Viscous Oils Drainage	174
6.8.20	Toxic Metal Contaminated Streams	174
6.8.21	Solvent Processes Drainage	174
6.8.22	Treating Processes Drainage	175
6.9	Petrochemical Plants' Special Effluents	175
6.9.1	Summary of Disposal/Treatment Methods	175
6.10	NGL, LNG, and LPG Area Effluents	178
6.10.1	Liquefied Gas Spill	178
6.11	Gas Treatment Facilities' Effluents	178
6.12	Effluents from Terminals, Depots, and Product Handling Areas	178
6.13	General Considerations and Conditions for Release of Wastes	178
6.13.1	Characteristics and Composition of Waste	179
6.13.2	Characteristics of the Discharge Site and Receiving Environment	179
6.13.3	Availability of Waste Technologies	180
6.14	Effluent Wastewater Characteristics	180
6.14.1	Flow	180
6.14.2	Temperature	181
6.14.3	pH	181
6.14.4	Oxygen Demand	181
6.14.5	Phenol Content	182
6.14.6	Sulfide Content	182
6.14.7	Oil Content	182
6.14.8	Light Hydrocarbon Solubility in Water	182
6.14.9	Predicting Water-Hydrocarbon System Mutual Solubility	185
6.15	Wastewater Emissions	189
6.15.1	Point Source Discharge	189
6.15.2	Effluent Permissible Concentrations	193
7	Sewage Treatment	195
7.1	Sewage Effluents	196
7.1.1	Receiving Water	196
7.1.2	Final Effluents of Domestic Wastewater Plants	197
7.2	Methods of Sewage Treatment: General	197
7.2.1	Conventional Methods	197
7.3	Choice of System: General	197
7.4	Design of Sewage Treatment Plants: General Guidances	198
7.5	Design of Small Sewage Treatment Plants	198
7.5.1	Collection of Information	198
7.6	Preliminary Treatment	200

7.7	Primary and Secondary Settlement Tanks	200
7.7.1	Capacities of Primary Settlement Tanks	201
7.8	Sludge Digesters	202
7.9	Drying Beds	202
7.9.1	Secondary Settlement Tanks	203
7.10	Biological Filters	204
7.10.1	Distribution	205
7.10.2	Volume of Filter	205
7.10.3	Mineral Filter Media	206
7.11	Activated-Sludge Units	207
7.12	Tertiary Treatment (Polishing) Processes	207
7.13	Disposal of Final Effluent	207
7.14	Advanced Wastewater Treatment	208
7.14.1	Effects of Chemical Constituents in Wastewater	208
7.14.2	Advanced Wastewater Treatment Operations and Processes	209
7.15	Effluent Disposal and Reuse	212
7.15.1	Direct and Indirect Reuse of Wastewater	212
8	Solid Waste Treatment and Disposal	215
8.1	Basic Considerations	215
8.1.1	Classification	215
8.1.2	Methodology	215
8.1.3	Sources	216
8.1.4	Characteristics	219
8.1.5	Quantities	223
8.2	Sludge Handling, Treatment, and Reuse	223
8.2.1	General	223
8.2.2	Sludge and Scum Pumping	223
8.2.3	Sludge Piping	226
8.2.4	Preliminary Operation Facilities	229
8.2.5	Thickening (Concentration)	230
8.3	Stabilization	233
8.3.1	Design Considerations	233
8.3.2	Lime Stabilization	233
8.3.3	Heat Treatment	234
8.3.4	Anaerobic Sludge Digestion	235
8.3.5	Composting	236
8.4	Conditioning	237
8.5	Disinfection	237
8.6	Dewatering	237
8.6.1	Sludge Dewatering Methods	238
8.6.2	Vacuum Filtration	238
8.6.3	Centrifugation	238
8.6.4	Belt Filter Press	238
8.6.5	Sludge Drying Beds	241
8.6.6	Lagoons	241

8.7	Heat Drying	242
8.8	Thermal Reduction	242
8.8.1	Thermal Reduction Process Applications	243
8.9	Land Application of Sludge	243
8.10	Chemical Fixation	245
8.11	Final Sludge and Solids Conveyance, Storage, and Disposal	245
8.11.1	Conveyance Methods	245
8.11.2	Environmental Considerations in Sludge Transportation	246
8.11.3	Sludge Storage	246
8.11.4	Final Disposal	246
8.11.5	Incineration	247
8.11.6	Ash Handling and Disposal	248
8.12	Disposal of Solid Waste	248
8.12.1	Types of Waste	248
8.12.2	Siting of Hazardous Waste Facilities	250
8.12.3	Non-Hazardous Waste	251
8.12.4	Sources, Segregation, Quantities, and Characteristics of Solid Waste in Refineries	251
8.12.5	Source Reduction Methods	253
8.12.6	Resource Recovery and Waste Minimization	255
8.12.7	Hazardous Waste Reduction	258
8.12.8	Treatment Prior to Ultimate Disposal	260
8.12.9	Disposal of Waste Generated in Drilling Wells	266
8.12.10	General Sampling Considerations	267
8.12.11	Air Monitoring of Waste for Employee Protection	272
8.12.12	Procedures	273
8.12.13	Hazards	275
8.12.14	Quality Assurance Consideration	275
	<i>Definitions and Terminology</i>	277
	<i>Bibliography and Further Reading</i>	307
	<i>Index</i>	323

Preface

Oil and gas are major sources of energy and revenue for many countries today – their production has been described as one of the most important industrial activities in the twenty-first century – and obviously waste treatment and disposal assume a greater degree of importance in the petroleum, chemical processing, and unconventional oil and gas industries.

Wastewater quality and the quantity produced determine the means of disposal and the costs of disposal. Suspended solids, total dissolved solids, and oxygen demand of produced waters have the most impact on wastewater treatment.

Wastewater is a complex mixture of organic and inorganic compounds and the largest byproduct by volume generated during chemical processing and both conventional and unconventional oil and gas recovery operations. The potential of oilfield-produced water to be a source of freshwater for water-stressed oil-producing countries and increasing environmental concerns, in addition to stringent legislations on produced water discharge into the environment, have made produced water management a significant part of the oil and gas business.

In marginally economic coal bed projects, the water disposal costs and attendant environmental accounting are critical factors in the investment decision; water disposal costs can economically make or break a marginal project.

Before investing in a coal bed methane (CBM) process, multiple questions need to be answered concerning the water to be produced – questions concerning quantity, flow-rates, chemical content, disposal means, monitoring, and environmental regulations. Perhaps no other factor affects the economics and feasibility of CBM projects as much as water removal and disposal.

In heavy oil production, between 2 to 4.5 volume units of water are used to produce each volume unit of synthetic crude oil in an ex situ mining operation. Despite recycling, almost all of it ends up in tailings ponds. However, in Steam Assisted Gravity Drainage (SAGD) operations, 90–95% of the water is recycled and about 0.2 volume units of water is used per volume unit of bitumen produced.

A major hindrance to the monitoring of oil sands-produced waters has been the lack of identification of individual compounds present. By better understanding the nature of the highly complex mixture of compounds, including naphthenic acids, it may be possible to monitor rivers for leachate and also to remove toxic components. Such identification of individual acids has for many years proved impossible, but a recent breakthrough in analysis has begun to reveal what is in the oil sands-produced waters.

The extraction and use of shale gas can affect the environment through the leaking of extraction chemicals and waste into water supplies, the leaking of greenhouse gasses during extraction, and the pollution caused by the improper processing of natural gas.

A challenge to preventing pollution is that shale gas extractions vary widely in this regard, even between different wells in the same project; the processes that reduce pollution sufficiently in one extraction may not be enough in another.

Chemicals are added to the water to facilitate the underground fracturing process that releases natural gas. Fracturing fluid is primarily water and approximately 0.5% chemical additives (friction reducer, agents countering rust, agents to kill microorganisms). Since (depending on the size of the area) millions of liters of water are used, this means that hundreds of thousands of liters of chemicals are often injected into the soil.

Only about 50 to 70% of the resulting volume of contaminated water is recovered and stored in above-ground ponds to await removal by tanker. The remaining “produced water” is left in the earth where it can lead to contamination of groundwater aquifers, though the industry deems this “highly unlikely.” However, the wastewater from such operations often leads to foul-smelling odors and heavy metals contaminating the local water supply above-ground.

This book unravels the essential requirements for the process design and engineering of the equipment and facilities pertaining to the wastewater treatment units, solid waste disposal, and wastewater sewer systems of oil and gas refineries, chemical plants, oil terminals, petrochemical plants, unconventional oil and gas industries (coal seam gas or coal bed methane, shale gas and oil sands production), and other facilities as required. Included within the scope are:

- Liquid and solid disposal systems.
- Primary oil/solids removal facilities.
- Further oil and suspended solids removal (secondary oil/solids removal), such as dissolved air flotation units.
- Granular media filters and chemical flocculation units.
- Chemical addition systems.
- Biological treatments.
- Filtration and/or other final polishing.
- Sewage systems handling domestic and medical sanitary appliances of buildings.
- Drainage systems carrying surface and rainwater.
- Wastewater gathering systems.
- Clean water drainage, e.g., from buildings and paved areas.
- Evaporation ponds and disposal by natural percolation into the subsoil in permeable ground.
- Sanitary sewage treatment.
- Sludge handling and treatment.

It is obvious that the aim of any drainage/effluent disposal system should be to segregate uncontaminated water from contaminated water or effluents and to segregate different types of effluents in order to reduce the size, complexity, and costs of any treatment units that may be required for handling the contaminated water and effluents before they are discharged from a unit.

All wastewater effluents from industry that are discharged to public and/or natural water sources or directed for recycling purposes inside the industry, and that may contain a wide variety of matters in solution or suspension, should be controlled according to the requirements imposed by the final destination. However, in any case, elimination of the waste or the hazard potential of the waste should be the ultimate goal in the management.

Under no circumstances should effluent water cause oil traces on the surface or embankments of the receiving water, or affect the natural self-purification capacity of the receiving water to such an extent that it would cause hindrance to other users.

Under no conditions should polluted streams be combined with unpolluted streams if the resultant stream will then require purification. In general, the main sewer systems in the industry will be segregated according to the following categories:

- Stormwater sewer systems.
- Oily water sewer systems.
- Non-oily water sewer systems.
- Chemical sewer systems.
- Sanitary sewer systems.
- Special sewer systems.

In all areas, including process, offsite, and utility units, provisions should be made to anticipate any of the above mentioned sewer systems as required.

The treatment of wastewaters involves a sequence of treatment steps. Each wastewater treatment process involves the separation of solids from water in at least some part of the operation and the removal of biochemical oxygen demand (BOD) to some extent.

The end of pipe treatment sequence can be divided into the following elements: primary or pre-treatment, intermediate treatment, secondary treatment and tertiary treatment plus ancillary, sludge dewatering, and disposal operations.

The key to optimizing the treatment sequence for provision of maximum water treatment at minimum cost is to identify the rule of each unit operation and optimize that operation. Optimizing the performance of specific unit operations, such as API separators, dissolved air flotation, biological treatment, etc., can best be achieved if:

1. The properties of influent streams are considered.
2. The chemical principles that are used in solids pre-treatment are understood.
3. The variety of chemicals available for solids treatment is recognized.
4. The properties of effluent water are established based on the local environmental regulations and final disposal.
5. The protocols for quantifying results are identified.

In general, most industries require water for processing or other purposes; much of this water after use is discharged either to public and/or natural water sources or directed for recycling purposes inside the industry.

Such discharge, which may contain a wide variety of matter in solution or suspension, should be controlled according to the requirements imposed by the final destination and/or environmental regulations.

Moreover, according to the type of plant and the method of plant operation, the sources of solids in a wastewater treatment plant can be uncovered. Solids may also be formed by interaction of waste streams in the sewer.

Wastewaters contain metal ions, such as iron, aluminium, copper, magnesium, and so on, from corrosion of the process equipment, chemicals used in treating cooling water, salts in the water intake, and chemicals used in processing.

Insoluble metal hydroxide floc may be formed when alkaline wastes are discharged and raise the pH of wastewater above neutral. The wastes, containing considerable concentrations of phenols, sulfides, emulsifying agents, and alkalines, should be segregated. In general, discharging any material to the oily sewer system or other drainage system should be investigated in line with the final waste treatment and disposal targets.

In view of the above, this book will unravel the fundamental engineering for waste recovery, treatment, and disposal systems in the petroleum, chemical, and unconventional oil and gas processing industries. These new fundamental discoveries will enable the development of practical solutions to these pressing environmental issues.

Dr. Alireza Bahadori

School of Environment, Science & Engineering, Southern Cross University, Lismore, NSW, Australia

25 July 2013

Acknowledgments

I would like to thank the Wiley editorial and production team Rebecca Stubbs, Emma Strickland and Sarah Tilley of John Wiley & Sons for their editorial assistance.

Biography

Alireza Bahadori, PhD is a research staff member in the School of Environment, Science & Engineering at Southern Cross University, Lismore, NSW, Australia. He received his PhD from Curtin University, Western Australia. For the better part of 20 years, Dr Bahadori had held various process engineering positions and involved in many large-scale projects at NIOC, Petroleum Development Oman (PDO), and Clough AMEC PTY LTD.

He is the author of over 200 articles and 6 books. His books have been accepted/published by prestigious publishers such as John Wiley & Sons, Springer, Taylor & Francis and Elsevier. Dr Bahadori is the recipient of highly competitive and prestigious Australian Government's Endeavour International Postgraduate Research award as part of his research in oil and gas area. He also received top-up award from State Government of Western Australia through Western Australia Energy research Alliance (WA:ERA) in 2009. Dr Bahadori Serves as a member of editorial board for a number of journals such as *Journal of Sustainable Energy Engineering* which is published by Wiley-Scrivener.

1

Wastewater Treatment

Wastewater treatment refers to the treatment of sewage and water used by residences, business, and industry to a sufficient level that it can be safely returned to the environment. It is important to treat wastewater to remove bacteria, pathogens, organic matter, and chemical pollutants that can harm human health, deplete natural oxygen levels in receiving waters, and pose risks to animals and wildlife.

1.1 Characteristics of Wastewaters

A number of chemical and physical characteristics are used to describe wastewater. The most common are:

- Biochemical Oxygen Demand (BOD). This is a measure of the amount of unstable organic matter in the water. It measures how much oxygen is required by the available microorganisms to break down the readily available organic matter into simpler forms, such as carbon dioxide, ammonia, and water.
- Total Nitrogen (TN) and Total Phosphorus (TP). These are the sum of all forms of nitrogen and phosphorus in the water, respectively.
- Fecal microbes (which include viruses, bacteria, and protozoans). These are found in wastewater and may cause disease.
- Suspended solids, biodegradable organics, nutrients, refractory organics, heavy metals, dissolved inorganic solids, and pathogens are important contaminants that may be found in the oil, gas, and chemical processing industry's wastewaters. Table 1.1 presents a list of important wastewater contaminants and reasons for their importance.

Suspended solids can be removed by physical treatment to some extent. Removal of biodegradable organics, suspended solids, and pathogens is achieved through the secondary treatment operation units.

Table 1.2 shows typical waste compounds classified as priority pollutants. The more stringent rules deal with the removal of nutrients and priority pollutants. When wastewater

Table 1.1 Contaminant importance in wastewater treatment.

Contaminants	Reason for Importance
Physical suspended solids	Suspended solids are important for esthetical reasons and because they can lead to the development of sludge deposits and anaerobic conditions
Chemical biodegradable organics	Composed principally of proteins, carbohydrates, and fats, biodegradable organics are measured most commonly in terms of BOD (Biochemical Oxygen Demand) and COD (Chemical Oxygen Demand). If discharged untreated to the environment, the biological stabilization of these materials can lead to the depletion of natural oxygen resources and to the development of septic conditions.
Nutrients	Carbon, nitrogen, and phosphorus are essential nutrients for growth. When discharged to the aquatic environment, these nutrients can lead to the growth of undesirable aquatic life. When discharged in excessive amounts on land, they can also lead to the pollution of groundwater.
Refractory organics	These organics tend to resist conventional biological methods of wastewater treatment. Typical examples include surfactants, phenols, and agricultural pesticides
Heavy metals	Due to their toxic nature, certain heavy metals can negatively impact upon biological waste treatment processes and stream life.
Dissolved inorganic solids	Inorganic constituents, such as calcium, sodium, and sulfate, are added to the original domestic water supply as a result of water use and may have to be removed if the wastewater is to be reused.
Biological pathogens	Communicable diseases can be transmitted by the pathogenic organisms in wastewater.

is to be reused, rules normally include requirements for the removal of refractory organics, heavy metals, and in some case dissolved inorganic solids.

1.1.1 Suspended Solids

Typically, suspended solids carry a significant portion of organic material, thus significantly contributing to the organic load of the wastewater (solids can contribute up to 60% of the BOD of a wastewater). Hence, effective solids removal can significantly contribute to wastewater treatment. A widely-accepted means of testing a wastewater for suspended solids is to filter the wastewater through a 0.45 μm porosity filter. Anything left on the filter after drying at about 103 $^{\circ}\text{C}$ is considered a portion of the suspended solids. Table 1.3 provides another classification system for the solids found in wastewater.

1.1.2 Heavy Metals

Any cation having an atomic mass (weight) greater than 23 (atomic mass of sodium) is considered a heavy metal. Motivations for controlling heavy metal concentrations in gas streams are diverse. Some of them are dangerous to health or to the environment (e.g., mercury, cadmium, lead, chromium), some can cause corrosion (e.g., zinc, lead), some are

Table 1.2 Typical waste compounds classified as priority pollutants.

Name (Formula)	Concern
Non-metals	
Arsenic (As)	Carcinogen and mutagen. Long term: sometimes cause fatigue and loss of energy; dermatitis.
Selenium (Se)	Long term: red staining of fingers, teeth, and hair; general weakness; depression; irritation of nose and mouth.
Metals	
Barium (Ba)	Flammable at room temperature in powder form. Long term: increased blood pressure and nerve block.
Cadmium (Cd)	Flammable in powder form. Toxic by inhalation of dust or fume. A carcinogen. Soluble compounds of cadmium are highly toxic. Long term: concentrates in the liver, kidneys, pancreas, and thyroid; hypertension suspected effect.
Chromium (Cr)	Hexavalent chromium compounds are carcinogenic and corrosive on tissue. Long term: skin sensitization and kidney damage
Lead (Pb)	Toxic by ingestion or inhalation of dust or fumes. Long term: brain and kidney damage; birth defects.
Mercury (Hg)	Highly toxic by skin absorption and inhalation of fume or vapor. Long term: toxic to central nervous system; may cause birth defects.
Silver (Ag)	Toxic metal. Long term: permanent gray discoloration of skin, eyes, and mucus membranes.
Organic compounds	
Benzene (C ₆ H ₆)	Carcinogen. Highly toxic. Flammable, dangerous fire risk.
Ethylbenzene (C ₆ H ₅ C ₂ H ₅)	Toxic by ingestion, inhalation, and skin absorption; irritant to skin and eyes. Flammable, dangerous fire risk.
Toluene (C ₆ H ₅ CH ₃)	Flammable, dangerous fire risk, Toxic by ingestion, inhalation, and skin absorption.
Halogenated compounds	
Chlorobenzene (C ₆ H ₅ Cl)	Moderate fire risk. Avoid inhalation and skin contact.
Chloroethene (CH ₂ CHCl)	An extremely toxic and hazardous material by all avenues of exposure. A carcinogen.
Dichloromethane (CH ₂ Cl ₂)	Toxic. A carcinogen, narcotic.
Tetrachloroethene (CCl ₂ CCl ₂)	Irritant to eyes and skin.
Pesticides, herbicides, insecticides (Pesticides, herbicides, and insecticides are listed by trade name. The compounds listed are also halogenated organic compounds.)	
Endrin (C ₁₂ H ₈ OCl ₆)	Toxic by inhalation and skin absorption, carcinogen.
Lindane (C ₆ H ₆ Cl ₆)	Toxic by inhalation, ingestion, skin absorption.
Methoxychlor [Cl ₃ CCH(C ₆ H ₄ OCH ₃) ₂]	Toxic material.
Toxaphene (C ₁₀ H ₁₀ Cl ₈)	Toxic by ingestion, inhalation, skin absorption.
Silvex [Cl ₃ C ₆ H ₂ OCH(CH ₃)COOH]	Toxic material; use has been restricted.

Table 1.3 General classification of wastewater solids.

Particle Classification	Particle Size, mm
Dissolved	Less than 10^{-6}
Colloidal	10^{-6} to 10^{-3}
Suspended	Greater than 10^{-3}
Settleable	Greater than 10^{-1}
Supracolloidal	10^{-3} to 10^{-1}

harmful in other ways (e.g., arsenic may pollute catalysts). Unlike organic pollutants, heavy metals do not decay and thus pose a different kind of challenge for remediation.

Currently, plants or microorganisms are tentatively used to remove some heavy metals such as mercury. Plants that exhibit hyper accumulation can be used to remove heavy metals from soils by concentrating them in their bio-matter. Some treatment of mining tailings has occurred where the vegetation is then incinerated to recover the heavy metals.

1.1.3 Dissolved Inorganic Solids

Total dissolved inorganic solids (TDIS) are a calculated value to assess the actual inorganic salt content of a water or process water.

The following procedure can be used to determine the inorganic dissolved solids in wastewaters. A sample of wastewater is filtered through a $0.45\ \mu\text{m}$ filter, filtrate is collected, the water is vaporized first (at $103\ ^\circ\text{C}$) and then the organic fraction (at $550\ ^\circ\text{C}$) from the filtrate. The amount of material left in the vessel after incineration at $550\ ^\circ\text{C}$ is referred to as the fixed or inorganic dissolved solids level.

1.1.4 Toxic Organic Compounds

Wastewater systems are known to contain toxic metals, organic micro pollutants, and pathogens that may add constraints to their beneficial uses. Environmental risks related to toxic inorganics, dioxins, furans, and pathogens can be controlled by:

1. Selecting a wastewater system with a low content of regulated contaminants that respects the local legislation for land application.
2. Application of a decontamination process to remove toxic metals.
3. The necessary step of sterilization for monocultures that eliminates pathogens.

These toxic organic compounds eventually reach sewage treatment plants and can be concentrated in wastewater systems. Disposal of wastewater systems is one way that these pollutants can be introduced into the environment. The presence of these toxic organic compounds can add constraints to the ultimate disposal of these sludges and/or reduce the possibilities for their beneficial use.

Tables 1.4 and 1.5 provide some organic compounds that are considered toxic and/or carcinogenic.

Table 1.4 Toxic organic compounds; occupational exposure to carcinogenic substances.

Compound	Site	Comment
Organic substances for which there is wide agreement on carcinogenicity		
4-Aminodiphenyl	Bladder	A contaminant in diphenylamine
Benzidine	Bladder	Ingredient of aniline dyes, plastics, and rubber
Beta-naphthylamine (2-NA)	Bladder	Dye and pesticide ingredient; synonym, 2-naphthylamine exposed workers have 30 to 60 times more cases of bladder cancer
Bis (chloromethyl) ether	Lung	Used in making exchange resins; exposed workers have 7 times more cases of lung cancer; synonym, BCME
Vinyl chloride	Liver	Angiosarcoma cases among PVC workers
Additional organic substances on USDA-OSHA cancer-causing substances list		
Alpha-naphthylamine (1-NA)	Bladder	Human case implicated; used in making dyes, herbicides, (1-NA) food colors, color film; an antioxidant
Ethyleneamine	Unknown	Carcinogenic in animals; used in paper and textile processing and manufacture of herbicides, resins, rocket and jet fuels
3,3-Dichlorobenzidine	Unknown	Carcinogenic in animal species; exposure accompanies benzidine and betanaphthylamine
Methyl chloromethyl methyl ether	Unknown	Carcinogenic in animals; synonym, CMME; BCME contaminants CMME; used in resin-making, textile, and drug production.
4,4-Methylene bis (2-chloroaniline)	Unknown	Synonym MOCA. Tumorigenic in rats and mice. Skin absorption may be the hazard. Curing agent for iso-cyanate polymers.

Table 1.5 Industrial substances suspected of carcinogenic potential for humans.

Industrial Substance	Industrial Substance
Antimony trioxide production	Epichlorhydrin
Benzene (skin)	Hexamethyl phosphoramidate (skin)
Benzo(a) pyrene	Hydrazine
Beryllium	4,4-Methylene bis (2-chloroaniline) (skin)
Cadmium oxide production	4,4-Methylene dianiline
Chloroform	Monomethyl hydrazine
Chromates of lead and zinc	Nitrosamines
3,3-Dichlorobenzidine	Propane sulfone
1,1-Dimethyl hydrazine	Beta-propiolactone
Dimethyl sulfate	Vinyl cyclohexene dioxide
Dimethylcarbamyl chloride	

1.1.5 Surfactants

Surfactants, or surface-active agents, are large organic molecules that are slightly soluble in water and cause foaming in wastewater treatment plants and in the surface waters into which the waste effluent is discharged.

The surfactants present in detergent products remain chemically unchanged during the washing process and are discharged down the drain with the dirty wash water. In the vast majority of cases, the drain is connected to a sewer and ultimately to a wastewater treatment plant, where the surfactants present in the sewage can be removed by biological and physical-chemical processes.

During aeration of wastewater, these compounds are collected on the surface of the air bubbles and thus create a very stable foam. The determination of surfactants is accomplished by measuring the color change in a standard solution of methylene blue active substance (MBAS).

1.1.6 Priority Pollutants

Priority pollutants (both inorganic and organic) are selected on the basis of their known or suspected carcinogenicity, mutagenicity, teratogenicity, or high acute toxicity. Many of the organic priority pollutants are also classified as volatile organic compounds (VOCs).

Representative examples of the priority pollutants are shown in Table 1.2. Within a wastewater collection and treatment system, organic priority pollutants may be removed, transformed, generated, or simply transported through the system unchanged. Five primary mechanisms are involved: (1) volatilization (also gas stripping); (2) degradation; (3) adsorption to particles and sludge; (4) transport through the entire system; (5) generation as a result of chlorination or as byproducts of the degradation of precursor compounds.

1.1.7 Volatile Organic Compounds

Wastewaters are collected and treated in a variety of ways, some of which result in the emission of volatile organic compounds (VOCs) from the wastewater to the air. Water may come into direct contact with organic compounds during a variety of different chemical processing steps, thus generating wastewater streams that must be discharged for treatment or disposal. Direct contact wastewater includes:

- Water used to wash impurities from organic compound products or reactants.
- Water used to cool or quench organic compound vapour streams.
- Condensed steam from jet eductor systems pulling vacuum on vessels containing organic compounds.
- Water from raw material and product storage tanks.
- Water used as a carrier for catalysts and neutralizing agents (e.g., caustic solutions).
- Water formed as a byproduct during reaction steps.

Direct contact wastewater is also generated when water is used in equipment washes and spill clean-ups. This wastewater is normally more variable in flow-rate and concentration than the streams listed above and may be collected in a way that is different from process wastewater. Wastewater streams generated by unintentional contact with organic compounds through equipment leaks are defined as “indirect contact” wastewater. Indirect contact wastewater may become contaminated as a result of leaks from heat exchangers, condensers, and pumps.