

---

# PRACTICAL RF SYSTEM DESIGN

---

**WILLIAM F. EGAN, Ph.D.**

Lecturer in Electrical Engineering  
Santa Clara University



The Institute of Electrical and Electronics Engineers, Inc., New York



A JOHN WILEY & SONS, INC., PUBLICATION



# PRACTICAL RF SYSTEM DESIGN



---

# PRACTICAL RF SYSTEM DESIGN

---

**WILLIAM F. EGAN, Ph.D.**

Lecturer in Electrical Engineering  
Santa Clara University



The Institute of Electrical and Electronics Engineers, Inc., New York



A JOHN WILEY & SONS, INC., PUBLICATION

MATLAB is a registered trademark of The Math Works, Inc., 3 Apple Hill Drive, Natick, MA 01760-2098 USA; Tel: 508-647-7000, Fax 508-647-7101; WWW: <http://www.mathworks.com>; email: [info@mathworks.com](mailto:info@mathworks.com).

Figures whose captions indicate they are reprinted from *Frequency Synthesis by Phase Lock*, 2nd ed., by William F. Egan, copyright © 2000, John Wiley and Sons, Inc., are reprinted by permission.

Copyright © 2003 by John Wiley & Sons, Inc. All rights reserved.

Published by John Wiley & Sons, Inc., Hoboken, New Jersey.  
Published simultaneously in Canada.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, scanning, or otherwise, except as permitted under Section 107 or 108 of the 1976 United States Copyright Act, without either the prior written permission of the Publisher, or authorization through payment of the appropriate per-copy fee to the Copyright Clearance Center, Inc., 222 Rosewood Drive, Danvers, MA 01923, 978-750-8400, fax 978-750-4470, or on the web at [www.copyright.com](http://www.copyright.com). Requests to the Publisher for permission should be addressed to the Permissions Department, John Wiley & Sons, Inc., 111 River Street, Hoboken, NJ 07030, (201) 748-6011, fax (201) 748-6008, e-mail: [permreq@wiley.com](mailto:permreq@wiley.com).

**Limit of Liability/Disclaimer of Warranty:** While the publisher and author have used their best efforts in preparing this book, they make no representations or warranties with respect to the accuracy or completeness of the contents of this book and specifically disclaim any implied warranties of merchantability or fitness for a particular purpose. No warranty may be created or extended by sales representatives or written sales materials. The advice and strategies contained herein may not be suitable for your situation. You should consult with a professional where appropriate. Neither the publisher nor author shall be liable for any loss of profit or any other commercial damages, including but not limited to special, incidental, consequential, or other damages.

For general information on our other products and services please contact our Customer Care Department within the U.S. at 877-762-2974, outside the U.S. at 317-572-3993 or fax 317-572-4002.

Wiley also publishes its books in a variety of electronic formats. Some content that appears in print, however, may not be available in electronic format.

***Library of Congress Cataloging-in-Publication Data is available.***

ISBN 0-471-20023-9

Printed in the United States of America

10 9 8 7 6 5 4 3 2 1

To those from whom I have learned:  
Teachers, Colleagues, and Students



# CONTENTS

---

<b>PREFACE</b>	<b>xvii</b>
<b>GETTING FILES FROM THE WILEY ftp AND INTERNET SITES</b>	<b>xix</b>
<b>SYMBOLS LIST AND GLOSSARY</b>	<b>xxi</b>
<b>1 INTRODUCTION</b>	<b>1</b>
1.1 System Design Process / 1	
1.2 Organization of the Book / 2	
1.3 Appendixes / 3	
1.4 Spreadsheets / 3	
1.5 Test and Simulation / 3	
1.6 Practical Skepticism / 4	
1.7 References / 5	
<b>2 GAIN</b>	<b>7</b>
2.1 Simple Cases / 8	
2.2 General Case / 9	
2.2.1 <i>S</i> Parameters / 9	
2.2.2 Normalized Waves / 11	
2.2.3 <i>T</i> Parameters / 12	

- 2.2.4 Relationships Between  $S$  and  $T$  Parameters / 13
- 2.2.5 Restrictions on  $T$  Parameters / 14
- 2.2.6 Cascade Response / 14
- 2.3 Simplification: Unilateral Modules / 15
  - 2.3.1 Module Gain / 15
  - 2.3.2 Transmission Line Interconnections / 16
  - 2.3.3 Overall Response, Standard Cascade / 25
  - 2.3.4 Combined with Bilateral Modules / 28
  - 2.3.5 Lossy Interconnections / 32
  - 2.3.6 Additional Considerations / 38
- 2.4 Nonstandard Impedances / 40
- 2.5 Use of Sensitivities to Find Variations / 40
- 2.6 Summary / 43
  - Endnotes / 45

### 3 NOISE FIGURE

47

- 3.1 Noise Factor and Noise Figure / 47
- 3.2 Modules in Cascade / 49
- 3.3 Applicable Gains and Noise Factors / 54
- 3.4 Noise Figure of an Attenuator / 55
- 3.5 Noise Figure of an Interconnect / 56
- 3.6 Cascade Noise Figure / 56
- 3.7 Expected Value and Variance of Noise Figure / 58
- 3.8 Impedance-Dependent Noise Factors / 59
  - 3.8.1 Representation / 60
  - 3.8.2 Constant-Noise Circles / 61
  - 3.8.3 Relation to Standard Noise Factor / 62
  - 3.8.4 Using the Theoretical Noise Factor / 64
  - 3.8.5 Summary / 65
- 3.9 Image Noise, Mixers / 65
  - 3.9.1 Effective Noise Figure of the Mixer / 66
  - 3.9.2 Verification for Simple Cases / 69
  - 3.9.3 Examples of Image Noise / 69
- 3.10 Extreme Mismatch, Voltage Amplifiers / 74
  - 3.10.1 Module Noise Factor / 76
  - 3.10.2 Cascade Noise Factor / 78
  - 3.10.3 Combined with Unilateral Modules / 79
  - 3.10.4 Equivalent Noise Factor / 79

- 3.11 Using Noise Figure Sensitivities / 79
- 3.12 Mixed Cascade Example / 80
  - 3.12.1 Effects of Some Resistor Changes / 81
  - 3.12.2 Accounting for Other Reflections / 82
  - 3.12.3 Using Sensitivities / 82
- 3.13 Gain Controls / 84
  - 3.13.1 Automatic Gain Control / 84
  - 3.13.2 Level Control / 86
- 3.14 Summary / 88
  - Endnotes / 90

## 4 NONLINEARITY IN THE SIGNAL PATH

91

- 4.1 Representing Nonlinear Responses / 91
- 4.2 Second-Order Terms / 92
  - 4.2.1 Intercept Points / 93
  - 4.2.2 Mathematical Representations / 95
  - 4.2.3 Other Even-Order Terms / 97
- 4.3 Third-Order Terms / 97
  - 4.3.1 Intercept Points / 99
  - 4.3.2 Mathematical Representations / 100
  - 4.3.3 Other Odd-Order Terms / 101
- 4.4 Frequency Dependence and Relationship Between Products / 102
- 4.5 Nonlinear Products in the Cascades / 103
  - 4.5.1 Two-Module Cascade / 104
  - 4.5.2 General Cascade / 105
  - 4.5.3 IMs Adding Coherently / 106
  - 4.5.4 IMs Adding Randomly / 108
  - 4.5.5 IMs That Do Not Add / 109
  - 4.5.6 Effect of Mismatch on IPs / 110
- 4.6 Examples: Spreadsheets for IMs in a Cascade / 111
- 4.7 Anomalous IMs / 115
- 4.8 Measuring IMs / 116
- 4.9 Compression in the Cascade / 119
- 4.10 Other Nonideal Effects / 121
- 4.11 Summary / 121
  - Endnote / 122

**5 NOISE AND NONLINEARITY****123**

- 5.1 Intermodulation of Noise / 123
  - 5.1.1 Preview / 124
  - 5.1.2 Flat Bandpass Noise / 125
  - 5.1.3 Second-Order Products / 125
  - 5.1.4 Third-Order Products / 130
- 5.2 Composite Distortion / 133
  - 5.2.1 Second-Order IMs (CSO) / 134
  - 5.2.2 Third-Order IMs (CTB) / 136
  - 5.2.3 CSO and CTB Example / 136
- 5.3 Dynamic Range / 137
  - 5.3.1 Spurious-Free Dynamic Range / 137
  - 5.3.2 Other Range Limitations / 139
- 5.4 Optimizing Cascades / 139
  - 5.4.1 Combining Parameters on One Spreadsheet / 139
  - 5.4.2 Optimization Example / 143
- 5.5 Spreadsheet Enhancements / 146
  - 5.5.1 Lookup Tables / 146
  - 5.5.2 Using Controls / 147
- 5.6 Summary / 147
  - Endnotes / 147

**6 ARCHITECTURES THAT IMPROVE LINEARITY****149**

- 6.1 Parallel Combining / 149
  - 6.1.1 90° Hybrid / 150
  - 6.1.2 180° Hybrid / 152
  - 6.1.3 Simple Push–Pull / 154
  - 6.1.4 Gain / 155
  - 6.1.5 Noise Figure / 156
  - 6.1.6 Combiner Trees / 156
  - 6.1.7 Cascade Analysis of a Combiner Tree / 157
- 6.2 Feedback / 158
- 6.3 Feedforward / 159
  - 6.3.1 Intermods and Harmonics / 160
  - 6.3.2 Bandwidth / 161
  - 6.3.3 Noise Figure / 161
- 6.4 Nonideal Performance / 162
- 6.5 Summary / 163
  - Endnotes / 163

**7 FREQUENCY CONVERSION 165**

- 7.1 Basics / 165
  - 7.1.1 The Mixer / 165
  - 7.1.2 Conversion in Receivers / 167
  - 7.1.3 Spurs / 168
  - 7.1.4 Conversion in Synthesizers and Exciters / 170
  - 7.1.5 Calculators / 170
  - 7.1.6 Design Methods / 170
  - 7.1.7 Example / 171
- 7.2 Spurious Levels / 171
  - 7.2.1 Dependence on Signal Strength / 171
  - 7.2.2 Estimating Levels / 173
  - 7.2.3 Strategy for Using Levels / 175
- 7.3 Two-Signal IMs / 176
- 7.4 Power Range for Predictable Levels / 177
- 7.5 Spur Plot, LO Reference / 180
  - 7.5.1 Spreadsheet Plot Description / 180
  - 7.5.2 Example of a Band Conversion / 182
  - 7.5.3 Other Information on the Plot / 184
- 7.6 Spur Plot, IF Reference / 186
- 7.7 Shape Factors / 196
  - 7.7.1 Definitions / 197
  - 7.7.2 RF Filter Requirements / 197
  - 7.7.3 IF Filter Requirements / 200
- 7.8 Double Conversion / 202
- 7.9 Operating Regions / 203
  - 7.9.1 Advantageous Regions / 203
  - 7.9.2 Limitation on Downconversion, Two-by-Twos / 206
  - 7.9.3 Higher Values of  $m$  / 209
- 7.10 Examples / 211
- 7.11 Note on Spur Plots Used in This Chapter / 216
- 7.12 Summary / 216
  - Endnotes / 217

**8 CONTAMINATING SIGNALS IN SEVERE NONLINEARITIES 219**

- 8.1 Decomposition / 220
- 8.2 Hard Limiting / 223
- 8.3 Soft Limiting / 223

- 8.4 Mixers, Through the LO Port / 225
  - 8.4.1 AM Suppression / 225
  - 8.4.2 FM Transfer / 226
  - 8.4.3 Single-Sideband Transfer / 226
  - 8.4.4 Mixing Between LO Components / 228
  - 8.4.5 Troublesome Frequency Ranges in the LO / 228
  - 8.4.6 Summary of Ranges / 235
  - 8.4.7 Effect on Noise Figure / 236
- 8.5 Frequency Dividers / 240
  - 8.5.1 Sideband Reduction / 240
  - 8.5.2 Sampling / 241
  - 8.5.3 Internal Noise / 242
- 8.6 Frequency Multipliers / 242
- 8.7 Summary / 243
  - Endnotes / 244

## 9 PHASE NOISE

245

- 9.1 Describing Phase Noise / 245
- 9.2 Adverse Effects of Phase Noise / 247
  - 9.2.1 Data Errors / 247
  - 9.2.2 Jitter / 248
  - 9.2.3 Receiver Desensitization / 249
- 9.3 Sources of Phase Noise / 250
  - 9.3.1 Oscillator Phase Noise Spectrums / 250
  - 9.3.2 Integration Limits / 252
  - 9.3.3 Relationship Between Oscillator  $S_{\phi}$  and  $L_{\phi}$  / 252
- 9.4 Processing Phase Noise in a Cascade / 252
  - 9.4.1 Filtering by Phase-Locked Loops / 253
  - 9.4.2 Filtering by Ordinary Filters / 254
  - 9.4.3 Implication of Noise Figure / 255
  - 9.4.4 Transfer from Local Oscillators / 255
  - 9.4.5 Transfer from Data Clocks / 256
  - 9.4.6 Integration of Phase Noise / 258
- 9.5 Determining the Effect on Data / 258
  - 9.5.1 Error Probability / 258
  - 9.5.2 Computing Phase Variance, Limits of Integration / 259
  - 9.5.3 Effect of the Carrier-Recovery Loop on Phase Noise / 260

9.5.4	Effect of the Loop on Additive Noise / 262	
9.5.5	Contribution of Phase Noise to Data Errors / 263	
9.5.6	Effects of the Low-Frequency Phase Noise / 268	
9.6	Other Measures of Phase Noise / 269	
9.6.1	Jitter / 269	
9.6.2	Allan Variance / 271	
9.7	Summary / 271	
	Endnote / 272	
<b>APPENDIX A</b>	<b>OP AMP NOISE FACTOR CALCULATIONS</b>	<b>273</b>
A.1	Invariance When Input Resistor Is Redistributed / 273	
A.2	Effect of Change in Source Resistances / 274	
A.3	Model / 276	
<b>APPENDIX B</b>	<b>REPRESENTATIONS OF FREQUENCY BANDS, IF NORMALIZATION</b>	<b>279</b>
B.1	Passbands / 279	
B.2	Acceptance Bands / 279	
B.3	Filter Asymmetry / 286	
<b>APPENDIX C</b>	<b>CONVERSION ARITHMETIC</b>	<b>289</b>
C.1	Receiver Calculator / 289	
C.2	Synthesis Calculator / 291	
<b>APPENDIX E</b>	<b>EXAMPLE OF FREQUENCY CONVERSION</b>	<b>293</b>
<b>APPENDIX F</b>	<b>SOME RELEVANT FORMULAS</b>	<b>303</b>
F.1	Decibels / 303	
F.2	Reflection Coefficient and SWR / 304	
F.3	Combining SWRs / 306	
F.3.1	Summary of Results / 306	
F.3.2	Development / 307	
F.3.3	Maximum SWR / 308	
F.3.4	Minimum SWR / 309	
F.3.5	Relaxing Restrictions / 309	
F.4	Impedance Transformations in Cables / 310	
F.5	Smith Chart / 310	

<b>APPENDIX G</b>	<b>TYPES OF POWER GAIN</b>	<b>313</b>
G.1	Available Gain / 313	
G.2	Maximum Available Gain / 313	
G.3	Transducer Gain / 314	
G.4	Insertion Gain / 315	
G.5	Actual Gain / 315	
<b>APPENDIX H</b>	<b>FORMULAS RELATING TO IMs AND HARMONICS</b>	<b>317</b>
H.1	Second Harmonics / 317	
H.2	Second-Order IMs / 318	
H.3	Third Harmonics / 318	
H.4	Third-Order IMs / 319	
H.5	Definitions of Terms / 320	
<b>APPENDIX I</b>	<b>CHANGING THE STANDARD IMPEDANCE</b>	<b>321</b>
I.1	General Case / 321	
I.2	Unilateral Module / 323	
<b>APPENDIX L</b>	<b>POWER DELIVERED TO THE LOAD</b>	<b>325</b>
<b>APPENDIX M</b>	<b>MATRIX MULTIPLICATION</b>	<b>327</b>
<b>APPENDIX N</b>	<b>NOISE FACTORS – STANDARD AND THEORETICAL</b>	<b>329</b>
N.1	Theoretical Noise Factor / 329	
N.2	Standard Noise Factor / 331	
N.3	Standard Modules and Standard Noise Factor / 332	
N.4	Module Noise Factor in a Standard Cascade / 333	
N.5	How Can This Be? / 334	
N.6	Noise Factor of an Interconnect / 334	
N.6.1	Noise Factor with Mismatch / 335	
N.6.2	In More Usable Terms / 336	
N.6.3	Verification / 338	
N.6.4	Comparison with Theoretical Value / 340	
N.7	Effect of Source Impedance / 341	
N.8	Ratio of Power Gains / 342	
	Endnote / 343	

<b>APPENDIX P</b>	<b>IM PRODUCTS IN MIXERS</b>	<b>345</b>
<b>APPENDIX S</b>	<b>COMPOSITE S PARAMETERS</b>	<b>349</b>
<b>APPENDIX T</b>	<b>THIRD-ORDER TERMS AT INPUT FREQUENCY</b>	<b>353</b>
<b>APPENDIX V</b>	<b>SENSITIVITIES AND VARIANCE OF NOISE FIGURE</b>	<b>355</b>
<b>APPENDIX X</b>	<b>CROSSOVER SPURS</b>	<b>359</b>
<b>APPENDIX Z</b>	<b>NONSTANDARD MODULES</b>	<b>363</b>
	Z.1 Gain of Cascade of Modules Relative to Tested Gain /	363
	Z.2 Finding Maximum Available Gain of a Module /	366
	Z.3 Interconnects /	367
	Z.4 Equivalent <i>S</i> Parameters /	367
	Z.5 <i>S</i> Parameters for Cascade of Nonstandard Modules /	368
	Endnote /	369
<b>REFERENCES</b>		<b>371</b>
	Endnote /	377
<b>INDEX</b>		<b>379</b>



# PREFACE

---

This book is about RF system analysis and design at the level that requires an understanding of the interaction between the modules of a system so the ultimate performance can be predicted. It describes concepts that are advanced, that is, beyond those that are more commonly taught, because these are necessary to the understanding of effects encountered in practice. It is about answering questions such as:

- How will the gain of a cascade (a group of modules in series) be affected by the standing-wave ratio (SWR) specifications of its modules?
- How will noise on a local oscillator affect receiver noise figure and desensitization?
- How does the effective noise figure of a mixer depend on the filtering that precedes it?
- How can we determine the linearity of a cascade from specifications on its modules?
- How do we expect intermodulation products (IMs) to change with signal amplitude and why do they sometimes change differently?
- How can modules be combined to reduce certain intermodulation products or to turn bad impedance matches into good matches?
- How can the spurious responses in a conversion scheme be visualized and how can the magnitudes of the spurs be determined? How can this picture be used to ascertain filter requirements?

- How does phase noise affect system performance; what are its sources and how can the effects be predicted?

I will explain methods learned over many years of RF module and system design, with emphasis on those that do not seem to be well understood. Some are available in the literature, some were published in reviewed journals, some have developed with little exposure to peer review, but all have been found to be important in some aspect of RF system engineering.

I would like to thank Eric Unruh and Bill Bearden for reviewing parts of the manuscript. I have also benefited greatly from the opportunity to work with many knowledgeable colleagues during my years at Sylvania-GTE Government Systems and at ESL-TRW in the Santa Clara (Silicon) Valley and would like to thank them, and those excellent companies for which we worked, for that opportunity. I am also grateful for the education that I received at Santa Clara and Stanford Universities, often with the help of those same companies. However, only I bear the blame for errors and imperfections in this work.

WILLIAM F. EGAN

*Cupertino, California*  
*February, 2003*

# GETTING FILES FROM THE WILEY ftp AND INTERNET SITES

---

To download spreadsheets that are the bases for figures in this book, use an ftp program or a Web browser.

## **FTP ACCESS**

If you are using an ftp program, type the following at your ftp prompt:

```
ftp://ftp.wiley.com
```

Some programs may provide the first “ftp” for you, in which case type

```
ftp.wiley.com
```

Log in as anonymous (e.g., User ID: anonymous). Leave password blank. After you have connected to the Wiley ftp site, navigate through the directory path of:

```
/public/sci_tech_med/rf_system
```

## **WEB ACCESS**

If you are using a standard Web browser, type URL address of:

**xx** GETTING FILES FROM THE WILEY ftp AND INTERNET SITES

ftp://ftp.wiley.com

Navigate through the directory path of:

/public/sci\_tech\_med/rf\_system

If you need further information about downloading the files, you can call Wiley's technical support at 201-748-6753.

# SYMBOLS LIST AND GLOSSARY

---

The following is a list of terms and symbols used throughout the book. Special meanings that have been assigned to the symbols are given, although the same symbols sometimes have other meanings, which should be apparent from the context of their usage. (For example, *A* and *B* can be used for amplitudes of sine waves, in addition to the special meanings given below.)

$\equiv$	is identically equal to, rather than being equal only under some particular condition
$\triangleq$	is defined as
$\sim$	(superscript) indicates rms
$X _y$	variable <i>X</i> with the condition <i>y</i> or referring to <i>y</i>
$X _{y1}^{y2}$	variable <i>X</i> with <i>y</i> between <i>y1</i> and <i>y2</i>
$\angle x$	angle or phase of <i>x</i>
$\approx$	low-pass filter
$\approx$	band-pass filter
acceptance band	band of frequencies beyond the passband where rejection is not required; used to indicate the region between the passband and a rejection band
contaminant	undesired RF power
passband	band of frequencies that pass through a filter with minimal attenuation or with less than a specified attenuation

rejection band	band of frequencies that are rejected or receive a specified attenuation (rejection)
sideband	signal in relation to a larger signal

**Generic Symbols (applied to other symbols)**

*	complex conjugate
$ x $	magnitude or absolute value of $x$
$\tilde{x}$	$x$ is an equivalent noise factor or gain that can be used in standard equations to represent cascades with extreme mismatches (see Section 3.10.4)

**Particular Symbols**

$A$	voltage gain in dB. Note that $G$ can as well be used if impedances are the same or the voltage is normalized to $R_0$ .
$a$	voltage transfer ratio.
$ a $	voltage gain (not in dB)
AM	amplitude modulation
$a_n$	$n$ th-order transfer coefficient [see Eq. (4.1)]
$a_{RT}$	round-trip voltage transfer ratio
$B$	noise bandwidth
$B_r$	RF bandwidth
$B_v$	video, or postdetection, bandwidth
BW	bandwidth
$c(n, j)$	$j$ th binomial coefficient for $(a + b)^n$ (Abromowitz and Stegun, 1964, p. 10)
cas	subscript referring to cascade
CATV	cable television
cbl	subscript referring to cable
CSO	composite second-order distortion (Section 5.2)
CTB	composite triple-beat distortion (Section 5.2)
dB	decibels
DBM	doubly balanced mixer
dBm	decibels referenced to 1 mW
dBc	decibels referenced to carrier
dBV	decibels referenced to 1 V
dBW	decibels referenced to 1 W
$e$	voltage from an internal generator
$F$	noise figure, $F = 10 \text{ dB} \log_{10} f$ or fundamental (as opposed to harmonic or IM).
$f$	noise factor (not in dB) or standard noise factor (measured with standard impedances) or frequency
$\hat{f}$	theoretical noise factor (measured with specified driving impedance) (see Sections 3.1, N.1)

FDM	frequency division multiplex
$f_c$	center frequency
$f_{osc}$	oscillator center frequency
$f_I$ or $f_{IF}$	intermediate frequency, frequency at a mixer's output
$f_L$ or $f_{LO}$	local oscillator frequency
FM	frequency modulation
$f_m$	modulation frequency
$f_R$ or $f_{RF}$	radio frequency, the frequency at a mixer's input
$G$	power gain, sometimes gain in general, in dB.
$g_k$	power gain of module $k$ , sometimes gain in general, not in dB.
$g_{pk}$	power gain preceding module $k$
$H$	subscript referring to harmonic
$I, IF$	intermediate frequency, the result of converting RF using a local oscillator
$i$	subscript indicating a signal traveling in the direction of the system input
IF	intermediate frequency, frequency at a mixer's output
IIP	input intercept point (IP referred to input levels)
IM	intermodulation product (intermod)
IM $n$	$n$ th-order intermod or IM for module $n$
in	subscript indicating a signal entering a module (1) at the port of concern or (2) at the input port
int( $x$ )	integer part of $x$
IP	intercept point
IP $n$	intercept point for $n$ th-order nonlinearity or for module $n$
ISFDR	instantaneous spur-free dynamic range (see Section 5.3)
$\bar{k}$	Boltzmann's constant
$\bar{k}T_0$	approximately $4 \times 10^{-21}$ W/Hz
$L$	single-sideband relative power density
$L, LO$	local oscillator, the generally relatively high-powered, controllable, frequency in a frequency conversion or the oscillator that provides it
$L_\varphi$	single-sideband relative power density due to phase noise
<b>M</b>	a matrix (bold format indicates a vector or matrix)
$m$	modulation index (see Section 8.1)
$\tilde{m}$	rms phase deviation in radians
ma	subscript for "maximum available"
MAX{ $a, b$ }	the larger of $a$ or $b$
$m \times n$	$m$ refers to the exponent of the LO voltage and $n$ refers to the exponent of the RF voltage in the expression for a spurious product; if written, for example, $3 \times 4$ , $m$ is 3 and $n$ is 4
$N_0$	noise power spectral density
$N_T$	available thermal noise power spectral density at 290 K, $\bar{k}T_0$
$o$	subscript indicating a signal traveling in the direction of the system output.

OIP	output intercept point (IP referred to output levels)
out	subscript indicating a signal exiting a module (1) at the port of concern or (2) at the output port
$P$	power in dB.
$p$	power (not in dB).
$p_{\text{avail},j}$	available power at interface $j$ (preceding module $j$ )
PM	phase modulation
$p_{\text{out},j}$	output power at interface $j$ (preceding module $j$ )
PPSD	phase power spectral density
PSD	power spectral density
$R, RF$	radio frequency, the frequency at a mixer's input
$R_0$	agreed-upon interface impedance, a standard impedance (e.g., 50 $\Omega$ ); characteristic impedance of a transmission line
RT	subscript for "round trip"
$S$	power spectral density or $S$ parameter (see Section 2.2.1)
$\hat{S}$	sensitivity (see Section 2.5)
$S_{ijk}$	$S$ parameter of row $i$ and column $j$ in the parameter matrix for module (or element) number $k$
SF	shape factor, ratio of bandwidth where an attenuation is specified to passband width
SFDR	spur-free dynamic range (see Section 5.3.1)
$S/N$	signal-to-noise power ratio
SSB	single-sideband; refers to a single signal in relation to a larger signal
SWR	standing wave ratio (see Section F.2)
$T$	absolute temperature or subscript referring to conditions during test
$T_0$	temperature of 290 K (16.85°C)
$T_{ijk}$	$T$ parameter (see Section 2.2.3) of row $i$ and column $j$ in the parameter matrix for module (or element) number $k$
$T_k$	noise temperature of module $k$ (see Section 3.2)
UUT	unit under test
<b>V</b>	a vector (bold format indicates a vector or matrix)
$v$	normalized wave voltage (see Section 2.2.2) or voltage (not in dB.)
$V$	voltage in dB
$\hat{v}$	phasor representing the wave voltage (see Section 2.2.2)
$\tilde{v}$	phasor whose magnitude is the rms value of the voltage $\tilde{v} = \hat{v}/\sqrt{2}$ (see Section 2.2.2)
$v_i, v_{\text{in}}, v_o, v_{\text{out}}$	see Fig. 2.2 and Section 2.2.1
$\Delta_{\pm}$	maximum $\pm$ deviation in dB of cable gain $A_{\text{cbl}}$ , from the mean
$\Delta f$	peak frequency deviation or frequency offset from spectral center
$\rho$	reflection coefficient (see Section F.2)
$\sigma$	standard deviation

- frequency
  - bands in spur plot, Appendix B, 279
  - conversion, 165
    - calculator, 170
    - design method, 170
    - effect on IM addition, 111
    - example of, 171
      - Appendix E, 293
    - higher values of  $m$ , 209
    - in feedback path, 217
    - in receivers, 167
    - in synthesizers and exciters, 170
    - operating regions, 203
  - frequency dividers
    - effect on contaminants, 240
    - internal noise, 242
    - sampling in, 241
  - frequency multipliers, effect on contaminants, 242
  - frequency, functions of, 7
- gain, 7
  - actual, 315
  - available, 313
    - ratio to transducer gain, 64
  - average, 19
  - cable, 18
    - variance, 22
  - cascade of nonstandard modules, 365
  - controls, 84
  - effective, 19
  - insertion, 315
  - maximum available, 313
    - nonstandard module, 366
  - mean cable, 20
  - module, 15
    - nonstandard relative to tested, 363
  - round-trip, 18
  - simple, 8
  - summary of Ch. 2, 43
  - tolerance, 8
  - transducer, 314
    - ratio to available gain, 64
  - types of power, Appendix G, 313
  - variance of a cascade, 25
  - variation due to SWR, 21
    - with parallel combining, 155
- getting files, xix
- glossary, xxi
- hard limiting, 223
- harmonic
  - formulas for, Appendix H, 317
  - second, 93
    - third, 100
      - with feedforward, 160
- heterodyning, 165
- homodyne, 195
- HRC CATV system, 133
- hybrid
  - 180°, 152
  - 90°, 150
- i (direction of propagation), 9
- IF
  - Filter Requirements, 200
    - Example 7.11, 201
  - mixer output, 165
  - range, conversion to, Example 7.6, 192
- IIP, 94
- image
  - frequency, parameters differing at, 72
  - noise, 65, 67
    - standard cascade, 74
  - rejection filter, 66
- impedance
  - match, 8
    - with hybrid, 151
  - nonstandard, 8
  - transformations in cables, 310
- IMs
  - adding
    - coherently, 106
    - randomly, 108
  - anomalous, 115
  - formulas for, Appendix H, 317
  - in cascade, spreadsheet for, 111
  - in mixers, Appendix P, 345
  - measuring, 116
  - relative phases at modules, Table 4.1, 108
  - second order, 93
  - that do not add, 109
  - third-order terms at input frequency, Appendix T, 353
  - two-signal in mixer, 176
    - with feedforward, 160
- in (direction of propagation), 9
- insertion gain, 315
- instantaneous SFDR, 137
- integration of phase noise, 258
  - limits for, 252
- intercept point
  - effect of mismatch on, 110
  - second order, 93
  - third-order, 99
- interconnect
  - in nonstandard cascade, 367
  - noise factor, 56, 334

- with mismatch, 335
  - reflection at, 39
  - transmission line, 16
- intermediate frequency, 165. *See* IF
- intermods. *See* IMs
- intermodulation of noise, 123
- internal spur, 168
- introduction, 1
- IRC CATV system, 133
- isolation, mixer, 167
  
- jitter, 248, 269
- Johnson noise, 48
  
- leakage
  - LO-to-IF on spur plot, 184
  - LO-to-RF on spur plot, 184
- level control, 86
- limiting
  - distortion in, 225
  - hard, 223
  - soft, 223
- limits of integration in computing phase
  - variance, 259
- linearity, architectures that improve, 149
- literature, use of technical, 5
- LO
  - components, mixing between, 228
  - contamination, effect on noise figure, 236
  - filtering, 238
  - mixer input, 165
  - summary of troublesome frequency ranges
    - in, 236
  - transfer from, of
    - AM, 225
    - FM, 226
    - phase noise, 255
    - single sideband, 226
  - troublesome frequency ranges in, 228
- load, power delivered to, 23
  - Appendix L, 325
- local oscillator, 165. *See* LO
- look-up tables, 146
- lossy interconnections, 32
  
- m*, high values in frequency conversion, 209
- matching impedance with hybrid, 151
- matrix multiplication, Appendix M, 327
- maximum available gain, 313
  - finding for a nonstandard module, 366
- maximum SWR from multiple reflections, 306
- mean cable gain, 20
- measurement of
  - IMs, 116
  - NPR, 131
  - S parameter, 10
  - T parameter, 13
- minimum SWR, multiple reflections, 306
- mismatch, effect
  - of, 16
    - Example 2.2, 22
  - on intercept points, 110
  - on interconnect noise factor, 335
- mixer, 165
  - doubly balanced, 166
  - IF output, 165
  - IMs in, Appendix P, 345
  - LO input, 165
  - noise factor
    - due to LO contamination, 236
    - effective, 66
  - parameters, 166
  - RF input, 165
  - singly balanced, 166
  - terminations, 174
  - transfer from LO, 225
- mixing between LO components, 228
- modules
  - bilateral in cascade, 24
  - nonstandard, Appendix Z, 363
  - unilateral, 8
- multiband downconverter, Example 7.15, 212
  
- noise
  - additive, effect of loop on, 262
  - and nonlinearity, 123
    - summary of Ch. 5, 147
  - bandwidth, 48, 49, 246
  - density, 49, 126
  - effect of loop on additive, 262
  - factor, 47. *See* also noise figure
    - attenuator, 55
    - cascade, 50
      - module contribution, 50
    - effect from LO contamination, 236
    - effect of source impedance on, 341
    - equivalent for voltage amplifier, 79
    - impedance dependent, 59
      - representation, 59
    - implication re phase noise, 255
    - mixer, due to LO contamination, 236
    - of interconnect, 56, 334
    - of mixer, effective, 66
    - Op-Amp calculations, Appendix A, 273
    - parallel combining, 156
    - single-sideband, 66
    - standard, 54, 331
      - relation to theoretical, 62

- standard and theoretical, Appendix N, 329
- summary of Ch. 3, 88
- summary of relationships, 53
- theoretical, 54, 329
  - relation to standard, 62
  - using, 64
  - summary, 65
- two-element cascade, 51
- voltage amplifier, 74
  - with unilateral modules, 79
- with extreme mismatch, 74
- figure, 47. *See also* noise factor
  - expected value, 58
  - sensitivity, 79
  - sensitivity, Appendix V, 355
  - spot, 49
  - variance, 58
- variance, Appendix V, 355
- flicker, 48
- image, 65, 67
- intermodulation of, 123
- Johnson, 48
- phase, 245
- power ratio, 131
- products
  - DC term, 126
  - second-order, 125
  - third order, 130
- sidebands, oscillator, 238
- source, isolated, 59
- temperature, 47, 48
  - cascade, 51
  - in operational environment, 52
  - system, 51
  - with operational source, 52
- thermal, 48
- nonideal effects
  - in parallel combining, 162
  - other, 121
- nonlinear products
  - frequency dependence, 102
  - general cascade, 105
  - in cascade, 102, 103
  - relationship between, 102
  - two-module cascade, 104
- nonlinearity
  - and noise, 123
  - in signal path, 91
  - summary of Ch. 4, 121
  - representing, 91
- nonstandard
  - impedances, 40
  - interface impedance, 8
  - modules, Appendix Z, 363
- normalized waves, 11
- notes, end, 5
- NPR, 131
  - Measurement, 131
- o (direction of propagation), 9
- odd-order terms, other, 101
- OIP2, 93
- Op-Amp noise factor, Appendix A, 273
- operating regions, frequency conversion, 203
- optimizing cascades, 139
- organization of the book, 2
- oscillator
  - noise sidebands, 238
  - phase noise representations, 252
- out (direction of propagation), 9
- parallel combining, 149
  - gain with, 155
  - noise factor, 156
  - nonideal performance in, 162
- parameters
  - mixer characterized by, 166
  - range in composite modules, 39
  - S, 9
  - scattering, 9
  - T, 12
  - two-port, 9
- passband in spur plot, 279
- performance, deviations from desired, 4
- phase
  - noise, 245
    - adverse effects, 247
    - effect of carrier recovery loop on, 260
    - effect on data, 258
    - effect on data errors, 263
    - implication of noise figure, 255
    - integration of, 258
    - low frequency, 268
    - measures of, 269
    - oscillator spectrum, 250
    - sources of, 250
    - transfer from LO, 255
  - power spectral density, 246
  - shift of a cascade, 27
  - variance, limits of integration, 259
  - variation, 24
- PLLs, filtering of phase noise by, 253
- plotting filter requirements, Example 7.10, 200
- power
  - delivered to load, 23
  - Appendix L, 325
  - gain, 8
  - ratio for two noise factors, 342

- in a traveling wave, 12
  - spectral density, 125
- PPSD, 246
- predictable spur levels, power range for, 177
- preface, xvii
- processing phase noise in a cascade, 252
- propagation direction subscript, 9
- PSD, 125
- push–pull, simple, 154
  
- random-walk FM, 251
- range of parameters in composite modules, 39
- ratio of power gains, standard and theoretical
  - noise factors, 342
- receiver
  - calculator, 289
  - crystal video, 129
  - desensitization, 249
- references, 5, 371
- reflection coefficient, 8, 304
- reflections
  - at interconnects, 39
  - other, 82
- relative sideband
  - amplitude, 245
  - density, 246
- response, standard cascade, 25
- return loss, 8
- RF mixer input, 165
- round-trip gain, 18
  
- S parameters, 9
  - composite, Appendix S, 349
  - measurement, 10
  - nonstandard
    - cascade, 368
    - module, 367
  - relative to T parameters, 13
- sampling in frequency dividers, 241
- scattering parameters, 9
- second harmonic, Example 4.1, 94
- second-order
  - IMs in CATV, 134
  - products
    - mathematical representation, 95
    - of noise, 125
  - terms, 92
- sensitivity
  - noise figure, 79
    - Appendix V, 355
    - using, 82
  - use of to find variations, 40
- severe nonlinearities, 219
- SFDR, instantaneous, 137
  
- shape factor
  - definitions, 197
  - filter, 184, 196
- sideband
  - amplitude, relative, 245
  - density, relative, 246
- signal with noise, effect of, 128
- simple push–pull, 154
- simulation, 3
- single
  - frequency spur, 168
  - IF, conversion to, Example 7.5, 186
- sideband
  - decomposition of, 220
  - density, 246
  - transfer from LO, 226
- Smith Chart, 310
- soft limiting, 223
- source impedance, effect on noise factor, 341
- source resistance, effect on Op-Amp noise
  - factor, 274
- specifications, creating and using, 1
- spectrum, oscillator, 250
- spot noise figure, 49
- spreadsheet
  - enhancements, 146
  - getting from Wiley site, xix
  - spur plot, 180
  - use of, 2, 3
- spur(ious), 168
  - crossover, 170, 182
    - Appendix X, 359
  - free dynamic range, 137
  - internal, 168
  - level
    - chart, 168
    - in DBM from balance parameters, 217
    - in mixer, 168, 171
    - dependence on signal strength, 171
    - estimating, 173
- m*-by-*n*, 168
- plot
  - IF reference, 186
  - LO reference, 180
  - normalized to LO, 184
  - representation of bands, Appendix B, 279
  - spreadsheet, 180
  - single-frequency, 168
- standard
  - cascade, 16
  - overall response, 25
- CATV system, 133
- impedance, 8
  - changing, Appendix I, 321